







Chapter 1: Introducing Networks and Protocols


























```

Windows PowerShell
PS C:\> tracert example.com

Tracing route to example.com [93.184.216.34]
over a maximum of 30 hops:
  0  <1 ms  <1 ms  <1 ms  192.168.50.1
  1  *      *      *      Request timed out.
  2  *      *      *      Request timed out.
  3  *      *      *      Request timed out.
  4  2 ms   2 ms   1 ms   my.jetpack [192.168.1.1]
  5  119 ms 47 ms  41 ms  172.26.96.169
  6  66 ms  39 ms  38 ms  107.79.227.124
  7  *      *      *      Request timed out.
  8  58 ms  79 ms  70 ms  12.83.186.145
  9  61 ms  40 ms  41 ms  cgcil403igs.ip.att.net [12.122.133.33]
 10  78 ms  38 ms  39 ms  dcr1-so-4-0-0.atlanta.savvis.net [192.205.32.118]
 11  116 ms 198 ms  47 ms  192.229.225.133
 12  76 ms  40 ms  37 ms  93.184.216.34

Trace complete.
PS C:\>
  
```





```

Windows PowerShell
PS C:\Users\honp> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : localdomain
    Link-local IPv6 Address . . . . . : fe80::cd70:e700:5486:fb1a%5
    IPv4 Address. . . . . : 192.168.182.133
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.182.2

Tunnel adapter isatap.localdomain:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : localdomain

Tunnel adapter Local Area Connection* 2:

    Connection-specific DNS Suffix  . :
    IPv6 Address. . . . . : 2001:0:9d38:6ab8:8ba:2c5a:5950:c03c
    Link-local IPv6 Address . . . . . : fe80::8ba:2c5a:5950:c03c%2
    Default Gateway . . . . . : ::

PS C:\Users\honp>


```


```
bob — bash — 80x20
Last login: Mon Sep 17 19:22:53 on ttys000
m1:~ honp$ ifconfig
lo0: flags=8049<UP,LOOPBACK,RUNNING,MULTICAST> mtu 16384
    options=3<RXCSUM,TXCSUM>
    inet6 fe80::1%lo0 prefixlen 64 scopeid 0x1
    inet 127.0.0.1 netmask 0xff000000
    inet6 ::1 prefixlen 128
gif0: flags=8010<POINTOPOINT,MULTICAST> mtu 1280
stf0: flags=0<> mtu 1280
en0: flags=8863<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    options=b<RXCSUM,TXCSUM,VLAN_HWTAGGING>
    ether 00:0c:29:59:17:6f
    inet6 fe80::20c:29ff:fe59:176f%en0 prefixlen 64 scopeid 0x4
    inet 192.168.182.128 netmask 0xffffffff00 broadcast 192.168.182.255
    media: autoselect (1000baseT <full-duplex>)
    status: active
m1:~ honp$
```

```
honp@ubby18: ~
honp@ubby18:~$ ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 00:0c:29:74:ba:ce brd ff:ff:ff:ff:ff:ff
    inet 192.168.182.145/24 brd 192.168.182.255 scope global dynamic noprefixroute ens33
        valid_lft 1515sec preferred_lft 1515sec
    inet6 fe80::df60:954e:211:7ff0/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
honp@ubby18:~$
```


```
http://api.ipify.org/
+ http://api.ipify.org/ Google
Apple Yahoo! Google Maps YouTube Wikipedia News (11) Popular
107.77.85.86
```

Chapter 2: Getting to Grips with Socket APIs







```
m1:Desktop honp$ gcc time_server.c -o time_server
m1:Desktop honp$ ./time_server
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connection...
Client is connected... 127.0.0.1
Reading request...
Received 320 bytes.
Sending response...
Sent 79 of 79 bytes.
Sent 25 of 25 bytes.
Closing connection...
Closing listening socket...
Finished.
m1:Desktop honp$ █
```




```
Desktop — bash — 80x20
m1:Desktop honp$ gcc time_server.c -o time_server
m1:Desktop honp$ ./time_server
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connection...
Client is connected... ::1
Reading request...
Received 316 bytes.
Sending response...
Sent 79 of 79 bytes.
Sent 25 of 25 bytes.
Closing connection...
Closing listening socket...
Finished.
m1:Desktop honp$ █
```



```
Desktop — bash — 80x20
m1:Desktop honp$ gcc time_server_dual.c -o time_server_dual
m1:Desktop honp$ ./time_server_dual
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connection...
Client is connected... ::ffff:127.0.0.1
Reading request...
Received 320 bytes.
Sending response...
Sent 79 of 79 bytes.
Sent 25 of 25 bytes.
Closing connection...
Closing listening socket...
Finished.
m1:Desktop honp$ > █
```



Chapter 3: An In-Depth Overview of TCP Connections




```
root@ubby16: /home/lv/chap03
root@ubby16:/home/lv/chap03# ./tcp_client example.com http
Configuring remote address...
Remote address is: 93.184.216.34 http
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
GET / HTTP/1.1
Sending: GET / HTTP/1.1
Sent 15 bytes.
Host: example.com
Sending: Host: example.com
Sent 18 bytes.

Sending:
Sent 1 bytes.
Received (1592 bytes): HTTP/1.1 200 OK
Cache-Control: max-age=604800
Content-Type: text/html; charset=UTF-8
Date: Tue, 30 Oct 2018 19:59:46 GMT
Etag: "1541025663+ident"
Expires: Tue, 06 Nov 2018 19:59:46 GMT
Last-Modified: Fri, 09 Aug 2013 23:54:35 GMT
Server: ECS (ord/4CD5)
Vary: Accept-Encoding
X-Cache: HIT
Content-Length: 1270

<!doctype html>
<html>
<head>
  <title>Example Domain</title>

  <meta charset="utf-8" />
  <meta http-equiv="Content-type" content="text/html; charset=utf-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1" />
  <style type="text/css">
  body {
    background-color: #f0f0f2;
    margin: 0;
    padding: 0;
    font-family: "Open Sans", "Helvetica Neue", Helvetica, Arial, sans
-serif;
  }
}
```



```
root@ubby16: /home/lv/chap03
root@ubby16:/home/lv/chap03# ./tcp_serve_toupper
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connections...
New connection from 127.0.0.1
█

lv@ubby16: ~/chap03
lv@ubby16:~/chap03$ ./tcp_client 127.0.0.1 8080
Configuring remote address...
Remote address is: 127.0.0.1 http-alt
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
Hello World!
Sending: Hello World!
Sent 13 bytes.
Received (13 bytes): HELLO WORLD!
█
```

```
root@ubby16: /home/lv/chap03
root@ubby16: /home/lv/chap03# ./tcp_serve_chat
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connections...
New connection from 127.0.0.1
New connection from 127.0.0.1
New connection from 127.0.0.1

```

```
lv@ubby16: ~/chap03
lv@ubby16:~/chap03$ ./tcp_client 127.0.0.1 8080
Configuring remote address...
Remote address is: 127.0.0.1 http-alt
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
Received (23 bytes): Hello from terminal 1.
Hello from a different terminal!
Sending: Hello from a different terminal!
Sent 33 bytes.

```


```
lv@ubby16: ~/chap03
lv@ubby16:~/chap03$ ./tcp_client 127.0.0.1 8080
Configuring remote address...
Remote address is: 127.0.0.1 http-alt
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
Hello from terminal 1.
Sending: Hello from terminal 1.
Sent 23 bytes.
Received (33 bytes): Hello from a different terminal!


```


```
lv@ubby16:~/chap03$ ./tcp_client 127.0.0.1 8080
Configuring remote address...
Remote address is: 127.0.0.1 http-alt
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
Received (23 bytes): Hello from terminal 1.
Received (33 bytes): Hello from a different terminal!

```

Chapter 4: Establishing UDP Connections







```
Command Prompt - udp_recvfrom.exe
$ gcc udp_recvfrom.c -o udp_recvfrom.exe -lws2_32
$ udp_recvfrom.exe
Configuring local address...
Creating socket...
Binding socket to local address...
```


The image displays two screenshots of a Windows Command Prompt window. The top window, titled "Command Prompt", shows the compilation of a C program named `udp_recvfrom.c` into an executable `udp_recvfrom.exe` using the `gcc` compiler with the `-lws2_32` flag. The program is then executed, displaying the following output: "Configuring local address...", "Creating socket...", "Binding socket to local address...", "Received (11 bytes): Hello World", "Remote address is: 127.0.0.1 55476", and "Finished.". The bottom window, titled "C:\WINDOWS\system32\cmd.exe", shows the compilation of a C program named `udp_sendto.c` into an executable `udp_sendto.exe` using the `gcc` compiler with the `-lws2_32` flag. The program is then executed, displaying the following output: "Configuring remote address...", "Remote address is: 127.0.0.1 8080", "Creating socket...", "Sending: Hello World", "Sent 11 bytes.", and "Finished.". Both windows show a prompt character (\$) at the end of each line of input and output.

```
C:\> gcc udp_recvfrom.c -o udp_recvfrom.exe -lws2_32


C:\> udp_recvfrom.exe
Configuring local address...
Creating socket...
Binding socket to local address...
Received (11 bytes): Hello World
Remote address is: 127.0.0.1 55476
Finished.


C:\>

C:\WINDOWS\system32> gcc udp_sendto.c -o udp_sendto.exe -lws2_32

C:\WINDOWS\system32> udp_sendto.exe
Configuring remote address...
Remote address is: 127.0.0.1 8080
Creating socket...
Sending: Hello World
Sent 11 bytes.
Finished.

C:\WINDOWS\system32>
```







The image shows two overlapping Windows Command Prompt windows. The top window, titled "Command Prompt - udp_serve_toupper.exe", displays the compilation of a server program and its execution. The bottom window, titled "C:\WINDOWS\system32\cmd.exe - udp_client.exe 127.0.0.1 8080", displays the compilation of a client program and its execution, which sends a message to the server and receives a response.


```
CA: Command Prompt - udp_serve_toupper.exe
$ gcc udp_serve_toupper.c -o udp_serve_toupper.exe -lws2_32
$ udp_serve_toupper.exe
Configuring local address...
Creating socket...
Binding socket to local address...
Waiting for connections...

CA: C:\WINDOWS\system32\cmd.exe - udp_client.exe 127.0.0.1 8080
$ gcc udp_client.c -o udp_client.exe -lws2_32
$ udp_client.exe 127.0.0.1 8080
Configuring remote address...
Remote address is: 127.0.0.1 8080
Creating socket...
Connecting...
Connected.
To send data, enter text followed by enter.
Example string to convert.
Sending: Example string to convert.
Sent 27 bytes.
Received (27 bytes): EXAMPLE STRING TO CONVERT.
```



Chapter 5: Hostname Resolution and DNS



```
ca. Command Prompt
$ gcc lookup.c -o lookup.exe -lws2_32
$ lookup example.com
Resolving hostname 'example.com'
Remote address is:
    93.184.216.34
    2606:2800:220:1:248:1893:25c8:1946
$
```



Header	Information about the message
Question	Question for the name server
Answer	Answer(s) to the question
Authority	Pointers to other name servers
Additional	Additional information



Name Example

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

3	'w'
'w'	'w'
7	'e'
'x'	'a'
'm'	'p'
'l'	'e'
3	'c'
'o'	'm'
0	

Answer Format

0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

NAME
TYPE
CLASS
TTL
RDLENGTH
RDATA


```
m1:Desktop honp$ gcc dns_query.c -o dns_query
m1:Desktop honp$ ./dns_query example.com a
Configuring remote address...
Creating socket...
Sent 29 bytes.
ID = AB CD
QR = 0 query
OPCODE = 0 standard
AA = 0
TC = 0
RD = 1 recursion desired
QDCOUNT = 1
ANCOUNT = 0
NSCOUNT = 0
ARCOUNT = 0
Query 1
  name: example.com
  type: 1
  class: 1



Received 45 bytes.
ID = AB CD
QR = 1 response
OPCODE = 0 standard
AA = 0
TC = 0
RD = 1 recursion desired
RCODE = 0 success
QDCOUNT = 1
ANCOUNT = 1
NSCOUNT = 0
ARCOUNT = 0
Query 1
  name: example.com
  type: 1
  class: 1
Answer 1
  name: (pointer 12) example.com
  type: 1
  class: 1
  ttl: 20576
  rdlen: 4
Address 93.184.216.34

m1:Desktop honp$ █
```

```
Desktop — bash — 80x46
m1:Desktop honp$ ./dns_query gmail.com mx
Configuring remote address...
Creating socket...
Sent 27 bytes.
ID = AB CD
QR = 0 query
OPCODE = 0 standard
AA = 0
TC = 0
RD = 1 recursion desired
QDCOUNT = 1
ANCOUNT = 0
NSCOUNT = 0
ARCOUNT = 0
Query 1
  name: gmail.com
  type: 15
  class: 1

Received 150 bytes.
ID = AB CD
QR = 1 response
OPCODE = 0 standard
AA = 0
TC = 0
RD = 1 recursion desired
RCODE = 0 success
QDCOUNT = 1
ANCOUNT = 5
NSCOUNT = 0
ARCOUNT = 0
Query 1
  name: gmail.com
  type: 15
  class: 1
Answer 1
  name: (pointer 12) gmail.com
  type: 15
  class: 1
  ttl: 3599
  rdlen: 32
  pref: 30
MX: alt3.gmail-smtp-in.l.google. (pointer 18) com
Answer 2
  name: (pointer 12) gmail.com
  type: 15
```

Chapter 6: Building a Simple Web Client



```
m1:Desktop honp$ gcc web_get.c -o web_get
m1:Desktop honp$ ./web_get example.com
URL: example.com
hostname: example.com
port: 80
path:
Configuring remote address...
Remote address is: 93.184.216.34 http
Creating socket...
Connecting...
Connected.

Sent Headers:
GET / HTTP/1.1
Host: example.com:80
Connection: close
User-Agent: honpwc web_get 1.0

Received Headers:
HTTP/1.1 200 OK
Cache-Control: max-age=604800
Content-Type: text/html; charset=UTF-8
Date: Mon, 17 Dec 2018 03:17:29 GMT
Etag: "1541025663+ident"
Expires: Mon, 24 Dec 2018 03:17:29 GMT
Last-Modified: Fri, 09 Aug 2013 23:54:35 GMT
Server: ECS (ord/4CB8)
Vary: Accept-Encoding
X-Cache: HIT
Content-Length: 1270
Connection: close

Received Body:
<!doctype html>
<html>
<head>
  <title>Example Domain</title>
```

The image shows a screenshot of a web browser window. The title bar reads "Example Form". The address bar contains the URL "http://127.0.0.1:8080/form.html". The search bar contains the text "Google". The browser's menu bar includes "Apple", "Yahoo!", "Google Maps", "YouTube", "Wikipedia", "News (13)", and "Popular". The main content area features a large heading "Example Form" in a bold, serif font. Below the heading is a paragraph: "You can fill out this form to make a POST request." The form consists of two input fields: "Name:" with the value "Alice" and "Comment:" with the value "Well Done!". A "submit" button is located below the comment field.


Example Form

You can fill out this form to make a POST request.

Name:

Comment:

Chapter 7: Building a Simple Web Server







```
chap07 — bash — 80x15
m1:chap07 honp$ file --mime-type public/index.html
public/index.html: text/html
m1:chap07 honp$ file --mime-type public/smile.png
public/smile.png: image/png
m1:chap07 honp$ file --mime-type public/test.txt
public/test.txt: text/plain
m1:chap07 honp$
```

```
chap07 — web_server — 80x15
m1:chap07 honp$ gcc web_server.c -o web_server
m1:chap07 honp$ ./web_server
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
New connection from 127.0.0.1.
serve_resource 127.0.0.1 /index.html
New connection from 127.0.0.1.
serve_resource 127.0.0.1 /smile.png
```



Chapter 8: Making Your Program Send Email





```
Windows PowerShell
PS C:\> nslookup -type=mx gmail.com
Server: UnKnown
Address: 192.168.182.2

Non-authoritative answer:
gmail.com      MX preference = 40, mail exchanger = alt4.gmail-smtp-in.l.google.com
gmail.com      MX preference = 5, mail exchanger = gmail-smtp-in.l.google.com
gmail.com      MX preference = 10, mail exchanger = alt1.gmail-smtp-in.l.google.com
gmail.com      MX preference = 20, mail exchanger = alt2.gmail-smtp-in.l.google.com
gmail.com      MX preference = 30, mail exchanger = alt3.gmail-smtp-in.l.google.com
PS C:\>
```

```
m1:Desktop honp$ dig mx gmail.com

; <<>> DiG 9.7.3 <<>> mx gmail.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 18189
;; flags: qr rd ra; QUERY: 1, ANSWER: 5, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;gmail.com.                IN      MX

;; ANSWER SECTION:
gmail.com.                 5       IN      MX      5 gmail-smtp-in.l.google.com.
gmail.com.                 5       IN      MX      10 alt1.gmail-smtp-in.l.google.com.
gmail.com.                 5       IN      MX      20 alt2.gmail-smtp-in.l.google.com.
gmail.com.                 5       IN      MX      30 alt3.gmail-smtp-in.l.google.com.
gmail.com.                 5       IN      MX      40 alt4.gmail-smtp-in.l.google.com.

;; Query time: 51 msec
;; SERVER: 192.168.182.2#53(192.168.182.2)
;; WHEN: Tue Jan 15 15:17:09 2019
;; MSG SIZE rcvd: 150

m1:Desktop honp$
```

```
m1:Desktop honp$ dig mx yahoo.com

; <<>> DiG 9.7.3 <<>> mx yahoo.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 30161
;; flags: qr rd ra; QUERY: 1, ANSWER: 3, AUTHORITY: 0, ADDITIONAL: 0

;; QUESTION SECTION:
;yahoo.com.                IN      MX

;; ANSWER SECTION:
yahoo.com.                 5       IN      MX      1 mta7.am0.yahoodns.net.
yahoo.com.                 5       IN      MX      1 mta5.am0.yahoodns.net.
yahoo.com.                 5       IN      MX      1 mta6.am0.yahoodns.net.

;; Query time: 63 msec
;; SERVER: 192.168.182.2#53(192.168.182.2)
;; WHEN: Thu Jan 17 20:08:12 2019
;; MSG SIZE rcvd: 106


m1:Desktop honp$
```



```
m1:Desktop honp$ gcc smtp_send.c -o smtp_send
m1:Desktop honp$ ./smtp_send
mail server: gmail-smtp-in.l.google.com
Connecting to host: gmail-smtp-in.l.google.com:25
Configuring remote address...
Remote address is: 74.125.124.26 smtp
Creating socket...
Connecting...
Connected.



S: 220 mx.google.com ESMTP z5si775139ioi.6 - gsmt
C: HELO HONPWC
S: 250 mx.google.com at your service
from: alice@handsonnetworkprogramming.com
C: MAIL FROM:<alice@handsonnetworkprogramming.com>
S: 250 2.1.0 OK z5si775139ioi.6 - gsmt
to: [REDACTED]@gmail.com
C: RCPT TO:<[REDACTED]@gmail.com>
S: 250 2.1.5 OK z5si775139ioi.6 - gsmt
C: DATA
S: 354 Go ahead z5si775139ioi.6 - gsmt
subject: Test Email
C: From:<alice@handsonnetworkprogramming.com>
C: To:<[REDACTED]@gmail.com>
C: Subject:Test Email
C: Date:Sat, 19 Jan 2019 00:02:46 +0000
C:
Enter your email text, end with "." on a line by itself.
> Hi,
C: Hi,
> This email will be in the book!
C: This email will be in the book!
> .
C: .
S: 250 2.0.0 OK 1547856174 z5si775139ioi.6 - gsmt
C: QUIT
S: 221 2.0.0 closing connection z5si775139ioi.6 - gsmt

Closing socket...
Finished.
m1:Desktop honp$ █
```

Chapter 9: Loading Secure Web Pages with HTTPS and OpenSSL







```

honn@ubby18: ~/Desktop
$ openssl version
OpenSSL 1.1.0g  2 Nov 2017
$

```

```

honn@ubby18: ~/Desktop
$ gcc openssl_version.c -o openssl_version -lcrypto
$ ./openssl_version
OpenSSL version: OpenSSL 1.1.0g  2 Nov 2017
$

```

```
honn@ubby18: ~/Desktop
$ gcc https_simple.c -o https_simple -lssl -lcrypto -Wall
$ ./https_simple example.org 443
Configuring remote address...
Remote address is: 93.184.216.34 https
Creating socket...
Connecting...
Connected.

SSL/TLS using ECDHE-RSA-AES128-GCM-SHA256
subject: /C=US/ST=California/L=Los Angeles/O=Internet Corporation for
Assigned Names and Numbers/OU=Technology/CN=www.example.org
issuer: /C=US/O=DigiCert Inc/CN=DigiCert SHA2 Secure Server CA
Sent Headers:
GET / HTTP/1.1
Host: example.org:443
Connection: close
User-Agent: https_simple

Received (341 bytes): 'HTTP/1.1 200 OK
Cache-Control: max-age=604800
Content-Type: text/html; charset=UTF-8
Date: Thu, 24 Jan 2019 23:50:51 GMT
Etag: "1541025663+ident"
Expires: Thu, 31 Jan 2019 23:50:51 GMT
Last-Modified: Fri, 09 Aug 2013 23:54:35 GMT
Server: ECS (ord/4CDA)
Vary: Accept-Encoding
X-Cache: HIT
Content-Length: 1270
Connection: close

'
Received (1270 bytes): '<!doctype html>
<html>
<head>
  <title>Example Domain</title>
...
'

Connection closed by peer.

Closing socket...
Finished.
$ █
```



Chapter 10: Implementing a Secure Web Server

```
honp@ubby18: ~/Desktop
$ openssl req -x509 -newkey rsa:2048 -nodes -sha256 -keyout key.pem -out cert.pem
-days 36500
Generating a 2048 bit RSA private key
.....+++
.....
.+++
writing new private key to 'key.pem'
-----
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:
State or Province Name (full name) [Some-State]:
Locality Name (eg, city) []:
Organization Name (eg, company) [Internet Widgits Pty Ltd]:
Organizational Unit Name (eg, section) []:
Common Name (e.g. server FQDN or YOUR name) []:
Email Address []:
$ █
```




```
honp@ubby18: ~/Desktop
$ openssl x509 -text -noout -in cert.pem
Certificate:
  Data:
    Version: 3 (0x2)
    Serial Number:
      d5:e8:c8:77:6a:18:c6:80
    Signature Algorithm: sha256WithRSAEncryption
    Issuer: C = AU, ST = Some-State, O = Internet Widgits Pty Ltd
    Validity
      Not Before: Feb  7 21:10:06 2019 GMT
      Not After : Jan 14 21:10:06 2119 GMT
    Subject: C = AU, ST = Some-State, O = Internet Widgits Pty Ltd
    Subject Public Key Info:
      Public Key Algorithm: rsaEncryption
      Public-Key: (2048 bit)
      Modulus:
        00:de:21:8c:e1:d1:37:a1:1b:57:96:f4:bc:1d:8f:
        da:c3:4b:a7:2e:85:f7:2d:17:f7:87:ac:a0:67:cb:
        c3:08:c1:f5:e3:67:fd:8b:46:8a:91:23:a2:8e:e9:
        f0:c4:3e:94:ad:d7:3e:dc:7f:55:ce:b8:ed:85:f5:
        b1:9a:0b:ad:71:fe:0e:22:82:a8:bc:9f:60:f2:94:
        a2:68:32:b2:32:58:e5:2d:60:75:62:24:b7:ac:cc:
        cc:19:18:1d:54:1c:d0:4c:b3:91:3d:44:de:fb:6d:
```

```
honp@ubby18: ~/Desktop
$ gcc tls_time_server.c -o tls_time_server -lssl -lcrypto
$ ./tls_time_server
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
Waiting for connection...
Client is connected... 127.0.0.1
SSL connection using ECDHE-RSA-AES128-GCM-SHA256
Reading request...
Received 0 bytes.
Sending response...
Sent 79 of 79 bytes.
Sent 25 of 25 bytes.
Closing connection...
Waiting for connection...
Client is connected... 127.0.0.1
SSL connection using ECDHE-RSA-AES128-GCM-SHA256
Reading request...
Received 0 bytes.
Sending response...
Sent 79 of 79 bytes.
Sent 25 of 25 bytes.
Closing connection...
Waiting for connection...
█
```



```
honn@ubby18: ~/Desktop
$ gcc https_server.c -o https_server -lssl -lcrypto
$ ./https_server
Configuring local address...
Creating socket...
Binding socket to local address...
Listening...
New connection from 127.0.0.1.
SSL connection using ECDHE-RSA-AES128-GCM-SHA256
serve_resource 127.0.0.1 /
New connection from 127.0.0.1.
SSL connection using ECDHE-RSA-AES128-GCM-SHA256
serve_resource 127.0.0.1 /smile.png
```





Chapter 11: Establishing SSH Connections with libssh

```
honn@ubby18: ~/Desktop
$ gcc ssh_version.c -o ssh_version -lssh
$ ./ssh_version
libssh version: 0.8.6/openssl/zlib
$
```

```
honn@ubby18: ~/Desktop
$ gcc ssh_connect.c -o ssh_connect -lssh
$ ./ssh_connect localhost
[2019/02/15 19:44:44.037146, 2] ssh_connect: libssh 0.8.6 (c) 2003-2018 Aris Adamantiadis, Andreas Schneider and libssh contributors. Distributed under the LGPL, please refer to COPYING file for information about your rights, using threading threads_pthread
[2019/02/15 19:44:44.037397, 2] ssh_socket_connect: Nonblocking connection socket: 3
[2019/02/15 19:44:44.037414, 2] ssh_connect: Socket connecting, now waiting for the callbacks to work
[2019/02/15 19:44:44.037431, 1] socket_callback_connected: Socket connection callback: 1 (0)
[2019/02/15 19:44:44.275512, 1] ssh_client_connection_callback: SSH server banner: SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
[2019/02/15 19:44:44.275561, 1] ssh_analyze_banner: Analyzing banner: SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
[2019/02/15 19:44:44.275594, 1] ssh_analyze_banner: We are talking to an OpenSSH client version: 7.6 (70600)
[2019/02/15 19:44:44.342304, 1] ssh_known_hosts_read_entries: Failed to open the known_hosts file '/etc/ssh/ssh_known_hosts': No such file or directory
[2019/02/15 19:44:44.352247, 2] ssh_kex_select_methods: Negotiated curve25519-sha256,ecdsa-sha2-nistp256,aes256-ctr,aes256-ctr,hmac-sha2-256,hmac-sha2-256,none,none,,
[2019/02/15 19:44:44.387545, 2] ssh_packet_dh_reply: Received SSH_KEXDH_REPLY
[2019/02/15 19:44:44.402617, 2] ssh_client_curve25519_reply: SSH_MSG_NEWKEYS sent
[2019/02/15 19:44:44.402662, 2] ssh_packet_newkeys: Received SSH_MSG_NEWKEYS
[2019/02/15 19:44:44.440037, 2] ssh_packet_newkeys: Signature verified and valid
Connected to localhost on port 22.
Banner:
SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
$
```

```
homp@ubby18: ~/Desktop
$ gcc ssh_auth.c -o ssh_auth -lssh
$ ./ssh_auth localhost 22 alice
Connected to localhost on port 22.
Banner:
SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
Host public key hash:
SHA1:UWXxDB3ArslAr7i2YBW07rLugtE
Checking ssh_session_is_known_server()
Host Known.
Password: password123
Authentication successful!
$
```

```
homp@ubby18: ~/Desktop
$ gcc ssh_command.c -o ssh_command -lssh
$ ./ssh_command localhost 22 alice
Connected to localhost on port 22.
Banner:
SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
Host public key hash:
SHA1:UWXxDB3ArslAr7i2YBW07rLugtE
Checking ssh_session_is_known_server()
Host Known.
Password: password123
Authentication successful!
Remote command to execute: ls -l
total 24
-rw-rw-r-- 1 alice alice 312 Feb 15 07:52 credits.txt
-rw-r--r-- 1 alice alice 8980 Apr 16 2018 examples.desktop
-rw-rw-r-- 1 alice alice 2124 Feb 15 07:51 schedule.txt
-rw-rw-r-- 1 alice alice 35 Feb 15 07:51 test.txt
ssh_channel_read() failed.
$
```

```
homp@ubby18: ~/Desktop
$ gcc ssh_download.c -o ssh_download -lssh
$ ./ssh_download localhost 22 alice
Connected to localhost on port 22.
Banner:
SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.2
Host public key hash:
SHA1:UWXxDB3ArslAr7i2YBW07rLugtE
Checking ssh_session_is_known_server()
Host Known.
Password: password123
Authentication successful!
Remote file to download: test.txt
Downloading file test.txt (48 bytes, permissions 0664
Received test.txt:
Hello World!
This file exists only for testing.


$ █
```

Chapter 12: Network Monitoring and Security

```
honn@ubby18: ~/Desktop
$ ping example.com
PING example.com (93.184.216.34) 56(84) bytes of data.
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=1 ttl=128 time=49.2 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=2 ttl=128 time=355 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=3 ttl=128 time=39.3 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=4 ttl=128 time=151 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=5 ttl=128 time=34.6 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=6 ttl=128 time=66.8 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=7 ttl=128 time=65.0 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=8 ttl=128 time=62.9 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=9 ttl=128 time=186 ms
64 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=10 ttl=128 time=134 ms
^C
--- example.com ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9018ms
rtt min/avg/max/mdev = 34.696/114.537/355.360/94.093 ms
$
```

```
honn@ubby18: ~/Desktop
$ ping -s 1000 example.com
PING example.com (93.184.216.34) 1000(1028) bytes of data.
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=1 ttl=128 time=39.4 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=2 ttl=128 time=82.0 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=3 ttl=128 time=64.4 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=4 ttl=128 time=270 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=5 ttl=128 time=253 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=6 ttl=128 time=53.1 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=7 ttl=128 time=48.9 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=8 ttl=128 time=48.5 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=9 ttl=128 time=50.3 ms
1008 bytes from 93.184.216.34 (93.184.216.34): icmp_seq=10 ttl=128 time=49.5 ms
s
^C
--- example.com ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9013ms
rtt min/avg/max/mdev = 39.400/96.117/270.959/83.954 ms
$
```

```
honn@ubby18: ~/Desktop
$ traceroute -n example.com
traceroute to example.com (93.184.216.34), 30 hops max, 60 byte packets
 1  23.92.28.3  0.584 ms  0.683 ms  0.807 ms
 2  74.207.239.24  0.701 ms  74.207.239.20  0.687 ms  74.207.239.6  0.758 ms
 3  198.32.132.86  1.927 ms  74.207.239.8  0.733 ms  0.720 ms
 4  198.32.132.86  1.888 ms  152.195.80.131  3.866 ms  198.32.132.86  1.860 ms
 5  93.184.216.34  0.347 ms  0.345 ms  152.195.80.131  3.815 ms
 6  93.184.216.34  0.353 ms  0.379 ms  0.362 ms
$
```



```

honn@ubby18: ~/Desktop
$ netstat -nt
Active Internet connections (w/o servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State
tcp    0      0 192.168.182.140:57926  93.184.216.34:80      ESTABLISHED
tcp    0      0 192.168.182.140:57922  93.184.216.34:80      TIME_WAIT
tcp    0      0 192.168.182.140:37488  216.58.192.174:80     ESTABLISHED
$

```

```

honn@ubby18: ~/Desktop
$ sudo netstat -ntlp
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State       PID/Program name
tcp    0      0 127.0.0.53:53          0.0.0.0:*               LISTEN      434/systemd-resolve
tcp    0      0 0.0.0.0:22            0.0.0.0:*               LISTEN      72522/ssh
tcp    0      0 127.0.0.1:631         0.0.0.0:*               LISTEN      92531/cupsd
tcp6   0      0 :::80                 :::*                    LISTEN      20762/apache2
tcp6   0      0 :::22                 :::*                    LISTEN      72522/ssh
tcp6   0      0 :::1:631              :::*                    LISTEN      92531/cupsd
$

```

```
Administrator: C:\Windows\system32\cmd.exe

C:\>netstat -nao -p TCP | findstr LISTEN
TCP    0.0.0.0:135          0.0.0.0:0        LISTENING        792
TCP    0.0.0.0:445          0.0.0.0:0        LISTENING         4
TCP    0.0.0.0:7680         0.0.0.0:0        LISTENING       968
TCP    0.0.0.0:49664        0.0.0.0:0        LISTENING       524
TCP    0.0.0.0:49665        0.0.0.0:0        LISTENING       340
TCP    0.0.0.0:49666        0.0.0.0:0        LISTENING       968
TCP    0.0.0.0:49667        0.0.0.0:0        LISTENING       648
TCP    0.0.0.0:49668        0.0.0.0:0        LISTENING      1580
TCP    0.0.0.0:49670        0.0.0.0:0        LISTENING       632
TCP    192.168.182.133:139  0.0.0.0:0        LISTENING         4

C:\>
```

```
Command Prompt

C:\>tshark -D
1. \Device\NPF_{3AB66933-5962-40BE-A2E8-A81CA26146DF} (Npcap Loopback Adapter)
2. \Device\NPF_{EF47CA2C-66BA-4BD5-BA92-3C7B6409238E} (Local Area Connection* 9)
3. \Device\NPF_{48F60EBF-01DD-4513-A732-43B40E47780B} (Local Area Connection* 8)
4. \Device\NPF_{07CFAB26-8E1B-41A9-89CF-4B56E74D963D} (Local Area Connection* 7)
5. \Device\NPF_{9B8B549E-60B1-4F5C-B617-EE55F26E347F} (Wire)
6. \Device\NPF_{A19D5A49-3286-4C52-ADB8-317354849FE1} (VMware Network Adapter VMnet8)
7. \Device\NPF_{BF91FBC0-ECEE-44BA-929A-F78A5C424B01} (VMware Network Adapter VMnet1)
8. \Device\NPF_{2AA46A79-14D2-4E2A-8F8C-95479B164777} (Ethernet)

C:\>
```

```
Command Prompt

C:\>tshark -i 5
Capturing on 'Wire'
 1  0.000000 184.29.93.254 → 192.168.50.119 TCP 60 80 → 2200 [FIN, ACK] Seq=1 Ack=1 Win=903 Len=0
 2  0.000031 192.168.50.119 → 184.29.93.254 TCP 54 2200 → 80 [ACK] Seq=1 Ack=2 Win=256 Len=0
 3  0.000073 192.168.50.119 → 184.29.93.254 TCP 54 2200 → 80 [FIN, ACK] Seq=1 Ack=2 Win=256 Len=0
 4  0.000910 192.168.50.1 → 192.168.50.119 ICMP 82 Redirect (Redirect for host)
 5  0.061462 184.29.93.254 → 192.168.50.119 TCP 60 80 → 2200 [ACK] Seq=2 Ack=2 Win=903 Len=0
 6  0.420941 192.168.50.1 → 239.255.255.250 SSDP 303 NOTIFY * HTTP/1.1
 7  0.421612 192.168.50.1 → 239.255.255.250 SSDP 375 NOTIFY * HTTP/1.1
 8  0.422272 192.168.50.1 → 239.255.255.250 SSDP 371 NOTIFY * HTTP/1.1
 9  0.422915 192.168.50.1 → 239.255.255.250 SSDP 351 NOTIFY * HTTP/1.1
10  0.423566 192.168.50.1 → 239.255.255.250 SSDP 383 NOTIFY * HTTP/1.1
11  0.424233 192.168.50.1 → 239.255.255.250 SSDP 365 NOTIFY * HTTP/1.1
12  0.424869 192.168.50.1 → 239.255.255.250 SSDP 367 NOTIFY * HTTP/1.1
13  0.425493 192.168.50.1 → 239.255.255.250 SSDP 367 NOTIFY * HTTP/1.1
14  0.654610 192.168.50.119 → 239.255.255.250 SSDP 179 M-SEARCH * HTTP/1.1
15  0.656185 192.168.50.1 → 192.168.50.119 SSDP 341 HTTP/1.1 200 OK
16  1.650339 BelkinIn_6e:5c:a8 → AsustekC_c5:79:0d ARP 60 Who has 192.168.50.119? Tell 192.168.50.1
17  1.650348 AsustekC_c5:79:0d → BelkinIn_6e:5c:a8 ARP 42 192.168.50.119 is at 08:62:66:c5:79:0d
18  3.654787 192.168.50.119 → 239.255.255.250 SSDP 179 M-SEARCH * HTTP/1.1
19  3.656344 192.168.50.1 → 192.168.50.119 SSDP 341 HTTP/1.1 200 OK
```

```
Command Prompt
C:\>tshark -i 5 host 8.8.8.8
Capturing on 'Wire'
  1  0.000000 192.168.50.119 → 8.8.8.8      DNS 71 Standard query 0xabcd A example.com
  2  0.146698   8.8.8.8 → 192.168.50.119 DNS 87 Standard query response 0xabcd A example.com A 93.184.216.34
2 packets captured

C:\>
```

```
Command Prompt
C:\>tshark -i 5 host 93.184.216.34 and port 80
Capturing on 'Wire'
  1  0.000000 192.168.50.119 → 93.184.216.34 TCP 66 5521 → 80 [SYN, Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM=1
  2  0.054634 93.184.216.34 → 192.168.50.119 TCP 66 80 → 5521 [SYN, ACK] Seq=0 Ack=1 Win=27800 Len=0 MSS=1370 SACK_PER
M=1 WS=32
  3  0.054705 192.168.50.119 → 93.184.216.34 TCP 54 5521 → 80 [ACK] Seq=1 Ack=1 Win=65536 Len=0
  4  0.054982 192.168.50.119 → 93.184.216.34 HTTP 145 GET / HTTP/1.1
  5  0.095022 93.184.216.34 → 192.168.50.119 TCP 60 80 → 5521 [ACK] Seq=1 Ack=92 Win=27808 Len=0
  6  0.098056 93.184.216.34 → 192.168.50.119 TCP 1424 HTTP/1.1 200 OK [TCP segment of a reassembled PDU]
  7  0.098057 93.184.216.34 → 192.168.50.119 HTTP 300 HTTP/1.1 200 OK (text/html)
  8  0.098057 93.184.216.34 → 192.168.50.119 TCP 60 80 → 5521 [FIN, ACK] Seq=1617 Ack=92 Win=27808 Len=0
  9  0.098140 192.168.50.119 → 93.184.216.34 TCP 54 5521 → 80 [ACK] Seq=92 Ack=1618 Win=65536 Len=0
 10  0.102372 192.168.50.119 → 93.184.216.34 TCP 54 5521 → 80 [FIN, ACK] Seq=92 Ack=1618 Win=65536 Len=0
 11  0.155505 93.184.216.34 → 192.168.50.119 TCP 60 80 → 5521 [ACK] Seq=1618 Ack=93 Win=27808 Len=0
11 packets captured

C:\>
```

```
Command Prompt
C:\>tshark -i 5 -x host 93.184.216.34 and port 80
Capturing on 'Wire'
0000  14 91 82 6e 5c a8 08 62 66 c5 79 0d 08 00 45 00  ...n\..bf.y...E.
0010  00 34 56 4a 40 00 80 06 7b 7f c0 a8 32 77 5d b8  .4VJ@...{...2w}.
0020  d8 22 58 69 00 50 a4 b0 17 bb 00 00 00 00 80 02  ."Xi.P.....
0030  fa f0 36 00 00 00 02 04 05 b4 01 03 03 08 01 01  ..6.....
0040  04 02  ..

0000  08 62 66 c5 79 0d 00 24 1d 7d ac 29 08 00 45 58  .bf.y..$.}.).EX
0010  00 34 00 00 40 00 3c 06 15 72 5d b8 d8 22 c0 a8  .4..@.<..r].."..
0020  32 77 00 50 58 69 8f 5b 75 d9 a4 b0 17 bc 80 12  2w.PXi.[u.....
0030  6c 98 bf 6f 00 00 02 04 05 5a 01 01 04 02 01 03  1..o.....Z.....
0040  03 05  ..

0000  14 91 82 6e 5c a8 08 62 66 c5 79 0d 08 00 45 00  ...n\..bf.y...E.
0010  00 28 56 4b 40 00 80 06 7b 8a c0 a8 32 77 5d b8  .(VK@...{...2w}.
0020  d8 22 58 69 00 50 a4 b0 17 bc 8f 5b 75 da 50 10  ."Xi.P.....[u.P.
0030  01 00 6b 7e 00 00  ..kω..

0000  14 91 82 6e 5c a8 08 62 66 c5 79 0d 08 00 45 00  ...n\..bf.y...E.
0010  00 83 56 4c 40 00 80 06 7b 2e c0 a8 32 77 5d b8  ..VL@...{...2w}.
0020  d8 22 58 69 00 50 a4 b0 17 bc 8f 5b 75 da 50 18  ."Xi.P.....[u.P.
0030  01 00 ea fb 00 00 47 45 54 20 2f 20 48 54 54 50  .....GET / HTTP
0040  2f 31 2e 31 0d 0a 48 6f 73 74 3a 20 65 78 61 6d  /1.1..Host: exam
0050  70 6c 65 2e 63 6f 6d 3a 38 30 0d 0a 43 6f 6e 6e  ple.com:80..Conn
0060  65 63 74 69 6f 6e 3a 20 63 6c 6f 73 65 0d 0a 55  ection: close..U
0070  73 65 72 2d 41 67 65 6e 74 3a 20 68 6f 6e 70 77  ser-Agent: honpw
0080  63 20 77 65 62 5f 67 65 74 20 31 2e 30 0d 0a 0d  c web_get 1.0...
0090  0a  .
```

```
Command Prompt
C:\example>tshark -i 5 -w capture.pcap -c 50 tcp and port 80
Capturing on 'Wire'
50

C:\example>_
```

capture.pcap

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

Apply a display filter ... <Ctrl-/> Expression... +

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	192.168.50.119	93.184.216.34	TCP	66	22699
2	0.071997	93.184.216.34	192.168.50.119	TCP	66	80 →
3	0.072053	192.168.50.119	93.184.216.34	TCP	54	22699
4	0.072307	192.168.50.119	93.184.216.34	HTTP	145	GET /
5	0.112223	93.184.216.34	192.168.50.119	TCP	60	80 →
6	0.113881	93.184.216.34	192.168.50.119	TCP	1424	80 →
7	0.113881	93.184.216.34	192.168.50.119	HTTP	295	HTTP
8	0.113882	93.184.216.34	192.168.50.119	TCP	60	80 →
9	0.113944	192.168.50.119	93.184.216.34	TCP	54	22699
10	0.117526	192.168.50.119	93.184.216.34	TCP	54	22699
11	0.191755	93.184.216.34	192.168.50.119	TCP	60	80 →
12	1.398024	192.168.50.119	13.33.155.31	TCP	54	22697
13	1.511914	13.33.155.31	192.168.50.119	TCP	60	80 →


> Frame 4: 145 bytes on wire (1160 bits), 145 bytes captured (1160 bits) on interface 0
 > Ethernet II, Src: Asustek_C5:79:0d (08:62:66:c5:79:0d), Dst: BelkinIn_6e:5c:a8 (14:91:82:6e:5c:a8)
 > Internet Protocol Version 4, Src: 192.168.50.119, Dst: 93.184.216.34
 > Transmission Control Protocol, Src Port: 22699, Dst Port: 80, Seq: 1, Ack: 1, Len: 91
 √ Hypertext Transfer Protocol
 > GET / HTTP/1.1\r\n
 Host: example.com:80\r\n
 Connection: close\r\n
 User-Agent: Mozilla/5.0 (Windows NT 6.0; rv:1.9.2.13) Gecko/20100308 Firefox/3.6.13

```

0000  14 91 82 6e 5c a8 08 62 66 c5 79 0d 08 00 45 00  ..n...b f.y...E.
0010  00 83 56 79 40 00 80 06 7b 01 c0 a8 32 77 5d b8  ..Vy@... {...2w}.
  
```

capture.pcap | Packets: 50 · Displayed: 50 (100.0%) | Profile: Default

Chapter 13: Socket Programming Tips and Pitfalls




```
C:\WINDOWS\system32\cmd.exe

C:\>gcc error_text.c -o error_text.exe -lws2_32


C:\>error_text
Calling socket() with invalid parameters.
Last error was: An invalid argument was supplied.
Finished.


C:\>
```





```
honp@ubby18: ~


honp@ubby18:~$ gcc error_text.c -o error_text
honp@ubby18:~$ ./error_text
Calling socket() with invalid parameters.
Last error was: Address family not supported by protocol
Finished.
honp@ubby18:~$
```


















```
honn@ubby18: ~  
honn@ubby18:~$ gcc server_noreuse.c -o server_noreuse  
honn@ubby18:~$ ./server_noreuse  
Configuring local address...  
Creating socket...  
Binding socket to local address...  
Listening...  
Waiting for connection...  
Client is connected.  
Waiting for connection...  
^C  
honn@ubby18:~$ ./server_noreuse  
Configuring local address...  
Creating socket...  
Binding socket to local address...  
bind() failed. (98)  
honn@ubby18:~$
```

```
C:\WINDOWS\system32\cmd.exe  
C:\>gcc setsize.c -o setsize.exe  
C:\>setsize  
FD_SETSIZE is 64.  
C:\>
```


Chapter 14: Web Programming for the Internet of Things

