


# Chapter 1: Setting Up a Development Environment

Explore Start a project

KICKSTARTER

Search Q Sign in

## Blynk - build an app for your Arduino project in 5 minutes



Platform with iOS and Android apps to control Arduino, Raspberry Pi and similar microcontroller boards over Internet.

[Website](#)

Created by  
Pasha Baiborodin

2,321 backers pledged \$49,235 to help bring this project to life.


Campaign    FAQ <sup>5</sup>    Updates <sup>27</sup>    Comments <sup>457</sup>    Community

# Widget Box

YOUR ENERGY BALANCE



 ⚡ 2,000 + Add

## CONTROLLERS

- 



**Button**

⚡ 200


- 



**Slider**

⚡ 200


- 



**Vertical Slider**

⚡ 200


- 



**Timer**

⚡ 200


- 



**Joystick**

⚡ 400


- 



**zeRGBa**

⚡ 400



- 

**Step H**

⚡ 500








- 

**Step V**



← blynk

Apps

-  **Blynk - Arduino, ESP8266, RPi** :  
Blynk Inc.  
4.6 ★  
FREE
-  **House of MG** :  
Blynk  
5.0 ★  
FREE
-  **Blynk** :  
Africa Topten  
FREE
-  **Blynk Shayari** :  
Top Best Free Apps by Sismatik, India  
FREE
-  **Blynk Biryani Recipes** :  
Top Best Free Apps by Sismatik, India  
FREE
-  **Blynk MNC Mantra** :

← blynk 



**Blynk - Arduino, ESP8266, RPi**  
Blynk Inc.  
4.6 ★ (3,865) • 100 thousand ⬇



[MORE INFO](#)

[INSTALL](#)

In-app purchases

You Might Also Like

[MORE](#)



Arduino Tutorials  
4.2 ★ **FREE**



Arduino Tutorials  
4.2 ★ **FREE**



Arduino Sensors  
4.4 ★ **FREE**



ESP8266 WiFi  
4.0 ★


Similar Apps







[MORE](#)





← blynk

 Blynk - Arduino, ESP8266, RPi  
needs access to

-  In-app purchases
-  Location
-  Photos/Media/Files
-  Camera
-  Wi-Fi connection information
-  Bluetooth connection information

Google Play **ACCEPT**

Similar Apps [MORE](#)



## Blynk - Arduino, ESP8266, RPi

Blynk Inc.

3+

UNINSTALL

OPEN

In-app purchases



Downloads



3,865



Tools



Similar

Control Arduino, ESP8266, Raspberry Pi  
and others with a smartphone in a  
minute!



### WHAT'S NEW

Several updates and fixes for push



Blynk

[Log In](#) | [Create New Account](#)



Log In with Facebook



[Why do I need an account?](#)



# Create New Account

E-mail

Password



## Sign Up





# Create New Account

E-mail


Password



## Sign Up



# ← How energy works



Each widget needs Energy to operate

When you delete a widget Energy is returned

You can always get more Energy in our Store.

Cool! Got it.



75% 22:11



Blynk



New Project



My Apps



Community



# ← Create New Project

demo

CHOOSE DEVICE

ESP8266



THEME

DARK



LIGHT

Create





46% 18:36

## ← Create New Project

demo

CHOOSE DEVICE

ESP8266



THEME

DARK



LIGHT

Select your hardware

OK


Particle Photon

Raspberry Pi 2/A+/B+

**Raspberry Pi 3 B**

Raspberry Pi A/B (Rev2)

Raspberry Pi B (Rev1)



43% 18:51

## ← Create New Project

demo

CHOOSE DEVICE

Raspberry Pi 3 B



CONNECTION TYPE

WiFi



THEME

DARK



LIGHT

Create



demo



Auth Token was sent to:  
pradeeka@outlook.com

You can also find it in Project Settings

OK



Don't show again



46% 18:36



## Project Settings

### HOME SCREEN SHORTCUT

Add Shortcut

Your Launcher app may not support adding shortcuts

### DEVICES



demo

Raspberry Pi 3 B (WiFi)



### AUTH TOKENS



Email all



Copy all

### THEME

DARK



LIGHT

### KEEP SCREEN ALWAYS ON

OFF



ON

### NOTIFY DEVICES WHEN APP CONNECTED



← My Devices

MY DEVICES



demo  
Raspberry Pi 3 B (WiFi)



New Device

MY TAGS



New Tag

← My Devices

demo

HARDWARE MODEL

Raspberry Pi 3 B ↓

CONNECTION TYPE

WiFi ↓

AUTH TOKEN

\*\*\*\*\*c5c2

Refresh

E-mail



BLOG


DOWNLOADS

COMMUNITY

HELP

## DOWNLOADS

**Raspbian** is the Foundation's official supported Operating System. Download it here, or use **NOOBS**, our easy installer for Raspbian and more.



NOOBS



RASPBIAN



BLOG

DOWNLOADS

COMMUNITY

HELP

FORUMS

EDUCATION

[Unarchiver](#) (Macintosh). Both are free of charge and have been tested to unzip the image correctly.



### RASPBIAN STRETCH WITH DESKTOP

Image with desktop based on Debian Stretch

Version: November 2017  
Release date: 2017-11-29  
Kernel version: 4.9  
Release notes: [Link](#)

[Download Torrent](#) [Download ZIP](#)



### RASPBIAN STRETCH LITE

Minimal image based on Debian Stretch

Version: November 2017  
Release date: 2017-11-29  
Kernel version: 4.9  
Release notes: [Link](#)

[Download Torrent](#) [Download ZIP](#)

SHA-256: e942b70072f2e83c446b9de6f202eb8f9692c06e7d92c343361340c

SHA-256: 64c4103316efe2a85fd2814f2af16313abac7d4ad68e3d95ae6709e c016e0c9f2e894cc1b

# Burn. Better.

Burn images to SD cards & USB drives, safely and easily.


Download for Windows x64

or, use our experimental CLI  
version v1.2.1 - See what's new!



Tweet


Star



9,129













## Device List

Index	Computer Name	MAC Address	IP Address	Lease Time	Status	Type	Operation
1	Pradeeka	9C:2A:70:C3:69:3F	192.168.1.2	0 days 12 hours 12 minutes 15 seconds	Active	Wi-Fi	<a href="#">Kick Out</a>
2	raspberrypi	B8:27:EB:2F:02:10	192.168.1.5	0 days 23 hours 57 minutes 5 seconds	Active	Ethernet	<a href="#">Kick Out</a>
3	Unknown	90:23:EC:99:C7:57	192.168.1.3	0 days 22 hours 25 minutes 46 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>
4	android-f545d0c9	94:FE:22:65:B3:47	192.168.1.4	0 days 20 hours 45 minutes 26 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>

## Device List

Index	Computer Name	MAC Address	IP Address	Lease Time	Status	Type	Operation
1	Pradeeka	9C:2A:70:C3:69:3F	192.168.1.2	0 days 12 hours 12 minutes 15 seconds	Active	Wi-Fi	<a href="#">Kick Out</a>
2	raspberrypi	B8:27:EB:2F:02:10	192.168.1.5	0 days 23 hours 57 minutes 5 seconds	Active	Ethernet	<a href="#">Kick Out</a>
3	Unknown	90:23:EC:99:C7:57	192.168.1.3	0 days 22 hours 25 minutes 46 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>
4	android-f545d0c9	94:FE:22:65:B3:47	192.168.1.4	0 days 20 hours 45 minutes 26 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>



```
pi@raspberrypi: ~  
login as: pi  
pi@192.168.1.5's password:  
Linux raspberrypi 4.9.59-v7+ #1047 SMP Sun Oct 29 12:19:23 GMT 2017 armv7l  
  
The programs included with the Debian GNU/Linux system are free software;  
the exact distribution terms for each program are described in the  
individual files in /usr/share/doc/*/copyright.  
  
Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent  
permitted by applicable law.  
Last login: Sat Jan 6 04:14:55 2018 from 192.168.1.2  
  
SSH is enabled and the default password for the 'pi' user has not been changed.  
This is a security risk - please login as the 'pi' user and type 'passwd' to set  
a new password.  
  
pi@raspberrypi:~ $ ifconfig wlan0  
wlan0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.1.6 netmask 255.255.255.0 broadcast 192.168.1.255  
    inet6 fe80::5234:39bb:a832:763a prefixlen 64 scopeid 0x20<link>  
    ether 10:fe:ed:18:bf:eb txqueuelen 1000 (Ethernet)  
    RX packets 253 bytes 75467 (73.6 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 43 bytes 6406 (6.2 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0  
  
pi@raspberrypi:~ $ █
```

## Device List

Index	Computer Name	MAC Address	IP Address	Lease Time	Status	Type	Operation
1	Pradeeka	9C:2A:70:C3:69:3F	192.168.1.2	0 days 21 hours 59 minutes 25 seconds	Active	Wi-Fi	<a href="#">Kick Out</a>
2	raspberrypi	B8:27:EB:2F:02:10	192.168.1.5	0 days 22 hours 49 minutes 47 seconds	Active	Ethernet	<a href="#">Kick Out</a>
3	Unknown	90:23:EC:99:C7:57	192.168.1.3	0 days 20 hours 12 minutes 55 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>
4	android-f545dbea0572d0c9	94:FE:22:65:B3:47	192.168.1.4	0 days 18 hours 32 minutes 35 seconds	Inactive	Ethernet	<a href="#">Kick Out</a>
5	raspberrypi	10:FE:ED:18:BF:EB	192.168.1.6	0 days 22 hours 49 minutes 47 seconds	Inactive	Wi-Fi	<a href="#">Kick Out</a>

```
pi@raspberrypi: ~  
pi@raspberrypi:~ $ sudo apt-get update  
Get:1 http://mirrordirector.raspbian.org/raspbian stretch InRelease [15.0 kB]  
Get:2 http://archive.raspberrypi.org/debian stretch InRelease [25.3 kB]  
Get:3 http://mirrordirector.raspbian.org/raspbian stretch/main armhf Packages [11.7 MB]  
Get:4 http://archive.raspberrypi.org/debian stretch/main armhf Packages [127 kB]  
Get:5 http://mirrordirector.raspbian.org/raspbian stretch/contrib armhf Packages [56.8 kB]  
Get:6 http://mirrordirector.raspbian.org/raspbian stretch/non-free armhf Packages [95.2 kB]  
Fetched 12.0 MB in 37s (319 kB/s)  
Reading package lists... Done  
pi@raspberrypi:~ $ █
```

```
pi@raspberrypi: ~  
pi@raspberrypi:~ $ sudo apt-get dist-upgrade  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
Calculating upgrade... Done  
The following packages will be upgraded:  
  base-files curl dbus iproute2 libcurl3 libcurl3-gnutls libdbus-1-3 libicu57  
  libpython2.7-minimal libpython2.7-stdlib libsqlite3-0 libssl1.0.2  
  openssh-client openssh-server openssh-sftp-server python2.7  
  python2.7-minimal raspberrypi-sys-mods raspi-config rsync sensible-utils ssh  
  tzdata  
23 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.  
Need to get 16.1 MB of archives.  
After this operation, 114 kB disk space will be freed.  
Do you want to continue? [Y/n] y  
Get:1 http://archive.raspberrypi.org/debian stretch/main armhf raspberrypi-sys-m  
ods armhf 20180103 [8,932 B]  
Get:3 http://archive.raspberrypi.org/debian stretch/main armhf raspi-config all  
20171201 [19.9 kB]
```

```
pi@raspberrypi: ~  
pi@raspberrypi:~ $ sudo apt-get install git-core  
Reading package lists... Done  
Building dependency tree  
Reading state information... Done  
The following additional packages will be installed:  
  git git-man liberror-perl  
Suggested packages:  
  git-daemon-run | git-daemon-sysvinit git-doc git-el git-email git-gui gitk gitweb git-arch  
  git-cvs git-mediawiki git-svn  
The following NEW packages will be installed:  
  git git-core git-man liberror-perl  
0 upgraded, 4 newly installed, 0 to remove and 0 not upgraded.  
Need to get 4,841 kB of archives.  
After this operation, 26.3 MB of additional disk space will be used.  
Do you want to continue? [Y/n] y  
Get:4 http://mirrordirector.raspbian.org/raspbian stretch/main armhf git-core all 1:2.11.0-3+deb9u  
2 [1,410 B]  
Get:1 http://mirror.ossplanet.net/raspbian/raspbian stretch/main armhf liberror-perl all 0.17024-1  
[26.9 kB]
```

```
pi@raspberrypi: ~  
pi@raspberrypi:~ $ git --version  
git version 2.11.0  
pi@raspberrypi:~ $ █
```



```
pi@raspberrypi: ~
pi@raspberrypi:~ $ git --version
git version 2.11.0
pi@raspberrypi:~ $ git clone git://git.drogon.net/wiringPi
Cloning into 'wiringPi'...
remote: Counting objects: 1151, done.
remote: Compressing objects: 100% (957/957), done.
remote: Total 1151 (delta 803), reused 214 (delta 142)
Receiving objects: 100% (1151/1151), 366.90 KiB | 246.00 KiB/s, done.
Resolving deltas: 100% (803/803), done.
pi@raspberrypi:~ $
```

```
pi@raspberrypi: ~/wiringPi
pi@raspberrypi:~ $ ls
wiringPi
pi@raspberrypi:~ $ clear
pi@raspberrypi:~ $ cd wiringPi
pi@raspberrypi:~/wiringPi $ ./build
wiringPi Build script
=====



WiringPi Library
[UnInstall]
[Compile] wiringPi.c
[Compile] wiringSerial.c
[Compile] wiringShift.c
[Compile] piHiPri.c
[Compile] piThread.c
[Compile] wiringPiSPI.c
[Compile] wiringPiI2C.c
[Compile] softPwm.c
[Compile] softTone.c
[Compile] mcp23008.c
[Compile] mcp23016.c
[Compile] mcp23017.c

warning: `      ' defined but not used [-Wunused-function]
static void digitalWrite8Dummy (UNU struct wiringPiNodeStruct *node, UNU int pin, U
NU int value) { return ; }
      ^~~~~~
warning: `      ' defined but not used [-Wunused-function]
static unsigned int digitalRead8Dummy (UNU struct wiringPiNodeStruct *node, UNU int UNU pi
n)
      { return 0 ; }
      ^~~~~~
[Compile] mcp23s08.c
```

```
pi@raspberrypi: ~
pi@raspberrypi:~/wiringPi $ cd
pi@raspberrypi:~ $ git clone https://github.com/blynkkk/blynk-library.git
Cloning into 'blynk-library'...
remote: Counting objects: 10548, done.
remote: Total 10548 (delta 0), reused 0 (delta 0), pack-reused 10547
Receiving objects: 100% (10548/10548), 9.02 MiB | 1.33 MiB/s, done.
Resolving deltas: 100% (6535/6535), done.
pi@raspberrypi:~ $
```





# Chapter 2: Building Your First Blynk Application



fritzing


```
pi@raspberrypi:~ $ gpio readall
```

Pi 3											
BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM	
		3.3v			1	2		5v			
2	8	SDA.1	ALT0	1	3	4		5V			
3	9	SCL.1	ALT0	1	5	6		0v			
4	7	GPIO. 7	IN	0	7	8	1	IN	TxD	15	14
		0v			9	10	1	IN	RxD	16	15
17	0	GPIO. 0	IN	0	11	12	0	IN	GPIO. 1	1	18
27	2	GPIO. 2	IN	0	13	14		0v			
22	3	GPIO. 3	IN	0	15	16	0	IN	GPIO. 4	4	23
		3.3v			17	18	0	IN	GPIO. 5	5	24
10	12	MOSI	ALT0	1	19	20		0v			
9	13	MISO	ALT0	1	21	22	0	IN	GPIO. 6	6	25
11	14	SCLK	ALT0	0	23	24	1	OUT	CE0	10	8
		0v			25	26	1	OUT	CE1	11	7
0	30	SDA.0	IN	1	27	28	1	OUT	SCL.0	31	1
5	21	GPIO.21	IN	0	29	30		0v			
6	22	GPIO.22	IN	0	31	32	0	IN	GPIO.26	26	12
13	23	GPIO.23	IN	1	33	34		0v			
19	24	GPIO.24	IN	0	35	36	0	IN	GPIO.27	27	16
26	25	GPIO.25	IN	0	37	38	0	IN	GPIO.28	28	20
		0v			39	40	0	IN	GPIO.29	29	21
BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM	



fritzing

-----Pi 2-----											
BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM	
		3.3v			1	2		5v			
2	8	SDA.1	ALTO	1	3	4		5V			
3	9	SCL.1	ALTO	1	5	6		0v			
4	7	GPIO. 7	IN	1	7	8	1	ALTO	TxD	15 14	
		0v			9	10	1	ALTO	RxD	16 15	
17	0	GPIO. 0	IN	0	11	12	0	IN	GPIO. 1	1 18	
27	2	GPIO. 2	OUT	0	13	14			0v		
22	3	GPIO. 3	OUT	0	15	16	1	OUT	GPIO. 4	4 23	
		3.3v			17	18	0	IN	GPIO. 5	5 24	
10	12	MOSI	IN	0	19	20			0v		
9	13	MISO	IN	0	21	22	0	IN	GPIO. 6	6 25	
11	14	SCLK	IN	0	23	24	1	IN	CEO	10 8	
		0v			25	26	1	IN	CE1	11 7	
0	30	SDA.0	IN	1	27	28	1	IN	SCL.0	31 1	
5	21	GPIO.21	OUT	0	29	30			0v		
6	22	GPIO.22	IN	1	31	32	1	IN	GPIO.26	26 12	
13	23	GPIO.23	IN	0	33	34			0v		
19	24	GPIO.24	IN	0	35	36	0	IN	GPIO.27	27 16	
26	25	GPIO.25	IN	0	37	38	0	IN	GPIO.28	28 20	
		0v			39	40	1	IN	GPIO.29	29 21	
BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM	
-----Pi 2-----											



fritzing



```
pi@raspberrypi ~ $ gpio readall
```

BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM	
		3.3v			1	2		5v			
2	8	SDA.1	ALTO	1	3	4		5V			
3	9	SCL.1	ALTO	1	5	6		0v			
4	7	GPIO.7	IN	0	7	8	1	ALTO	TxD	15	14
		0v			9	10	1	ALTO	RxD	16	15
17	0	GPIO.0	IN	0	11	12	0	IN	GPIO.1	1	18
27	2	GPIO.2	IN	0	13	14		0v			
22	3	GPIO.3	IN	0	15	16	0	IN	GPIO.4	4	23
		3.3v			17	18	0	IN	GPIO.5	5	24
10	12	MOSI	ALTO	0	19	20		0v			
9	13	MISO	ALTO	0	21	22	0	IN	GPIO.6	6	25
11	14	SCLK	ALTO	0	23	24	1	OUT	CEO	10	8
		0v			25	26	1	OUT	CE1	11	7
0	30	SDA.0	IN	1	27	28	1	IN	SCL.0	31	1
5	21	GPIO.21	IN	1	29	30		0v			
6	22	GPIO.22	IN	1	31	32	0	IN	GPIO.26	26	12
13	23	GPIO.23	IN	0	33	34		0v			
19	24	GPIO.24	IN	0	35	36	0	IN	GPIO.27	27	16
26	25	GPIO.25	IN	0	37	38	0	IN	GPIO.28	28	20
		0v			39	40	0	IN	GPIO.29	29	21





Blynk



New Project



My Apps



Community



← Create New Project

LED Controller

CHOOSE DEVICE

ESP8266



THEME

DARK



LIGHT

Create



3G 73% 22:57

## ← Create New Project

LED Controller

CHOOSE DEVICE

ESP8266



THEME

DARK



LIGHT

Select your hardware

OK

Particle Photon

Raspberry Pi 2/A+/B+

Raspberry Pi 3 B

Raspberry Pi A/B (Rev2)

Raspberry Pi B (Rev1)



# Create New Project

LED Controller

CHOOSE DEVICE

Raspberry Pi 3 B



CONNECTION TYPE

WiFi



THEME

DARK



LIGHT


Create



3G 73% 22:57



LED Controll





# Widget Box



## YOUR ENERGY BALANCE



 ⚡ 1,800



+ Add


## CONTROLLERS



 **Button**  
+200 



 **Slider**  
+200 

 **Vertical Slider**  
+200 

 **Timer**  
+200 

 **Joystick**  
+400 

 **zeRGBa**  
+400 

 **Step H**  
+500 

 **Step V** 




3G 73% 22:58



LED Controll




BUTTON





# Button Settings



Button



## OUTPUT

GP18

0

1

## MODE

PUSH



SWITCH

## ON/OFF LABELS

ON

ON

OFF

OFF





3G 66% 00:05



# LED Controll



BUTTON



gp18




# LED Controll



BUTTON

gp18




3G 68% 17:39




# LED Controll



BUTTON



gp18



3G 68% 17:40



BUTTON



gp18

# LED Controll



# LED Controll

A dark grid background with a central button labeled "gp18". The button is a rounded rectangle with a light blue fill and a dark border. Above the button, the word "BUTTON" is written in white. The grid consists of approximately 10 columns and 10 rows of small squares.

BUTTON

gp18



3G 63% 00:19



# LED Controll



BUTTON

gp18



3G 66% 00:03



# LED Controller





BUTTON

OFF





# LED Controller




## LED Controller

Online



BUTTON




OFF



3G 72% 23:00



# LED Controller





## LED Controller

Wasn't online yet


BUTTON

OFF





# Button Settings



Button



## OUTPUT

V1

0

1

## MODE

PUSH



SWITCH

## ON/OFF LABELS

ON

ON

OFF

OFF



3G 72% 23:03



# LED Controll



BUTTON




V1





## Chapter 3: Using Controller Widgets







3G 94% 23:18



## Project Settings

### How it Works

#### HOME SCREEN SHORTCUT

Add Shortcut

Your Launcher app may not support adding shortcuts

#### DEVICES



### LED Controller

Raspberry Pi A/B (Rev2) (WiFi)



#### AUTH TOKENS



Email all



Copy all

#### THEME

DARK




LIGHT


#### KEEP SCREEN ALWAYS ON

OFF



ON





← My Devices

MY DEVICES



LED Controller  
Raspberry Pi A/B (Rev2) (WiFi)



New Device

MY TAGS



New Tag

# ← My Devices

Controllers

HARDWARE MODEL



Raspberry Pi A/B (Rev2) ↓

CONNECTION TYPE

WiFi ↓

Controllers | Controller | Controlled | Contro

QWERTY keyboard with a Done button



fritzing



# Widget Box

## YOUR ENERGY BALANCE



⚡ 2,000

+ Add

## CONTROLLERS



Button

⚡ 200



Slider

⚡ 200



Vertical Slider

⚡ 200



Timer

⚡ 200



Joystick

⚡ 400



zeRGBa

⚡ 400



Step H

⚡ 500






# Controllers



SLIDER

0







# Controllers




SLIDER

0




0





# Slider Settings



Slider



## OUTPUT

PIN

0



255

## SEND ON RELEASE

OFF




ON



Delete

# Slider Settings



Slider



OUTPUT


## Select pin OK

Digital  
Virtual

PIN  
gp18 PWM



# Slider Settings



Slider



OUTPUT

GP18

0



1023

SEND ON RELEASE

OFF





ON




Delete





# Slider Settings



Slider



### OUTPUT

V1 0 1023


### SEND ON RELEASE

OFF  ON

Delete




# Controllers



SLIDER

185









3G 82% 23:39



# Controllers




STEP H

0



STEP V

0



# ← Step H Settings ⓘ

Step



OUTPUT

PIN

0



255

STEP

1.0

SEND STEP

NO




YES

LOOP VALUES

# Step H Settings

## OUTPUT

V1 0  1023

## STEP

1.0

## SEND STEP

NO  YES

## LOOP VALUES

OFF  ON

## ICONS

↑↓  +/-

## WRITE INTERVAL

100 ms ↓





3G 82% 23:39



# Controllers



ZERGBA

36


196

142





# zeRGBa Settings



zeRGBa

OUTPUT

SPLIT



MERGE

[R] PIN

0

255

[G] PIN

0

255

[B] PIN

0

255

SEND ON RELEASE

# zeRGBa Settings



zeRGBa

OUTPUT

SPLIT



MERGE

PIN

```
r = param[0].asInt();  
g = param[1].asInt();  
b = param[2].asInt();
```

[R]	0	255
[G]	0	255
[B]	0	255



# zeRGBa Settings



OUTPUT

SPLIT



MERGE

V1

```
r = param[0].asInt();  
g = param[1].asInt();  
b = param[2].asInt();
```

[R]

0

255

[G]

0

255

[B]

0

255

SEND ON RELEASE

OFF



ON



Delete



# Controllers



ZERGBA  
V1

36

196

142





# Controllers



ZERGBA

36

196

142





3G 68% 23:09




# Controllers




JOYSTICK

128  
128





# Joystick Settings



Joystick



OUTPUT


SPLIT



MERGE

PIN


To access values use:  
`x = param[0].asInt();`  
`y = param[1].asInt();`



AUTORETURN



# Joystick Settings



Joystick



OUTPUT


SPLIT



MERGE

V1


To access values use:  
x = param[0].asInt();  
y = param[1].asInt();



AUTORETURN

# Joystick Settings

```
y = param[1].asInt();
```



### AUTORETURN

OFF  ON

### ROTATE ON TILT

OFF  ON

### WRITE INTERVAL

100 ms ↓

 Delete



3G 71% 23:15




# Controllers



JOYSTICK

V1: 128  
V1: 128








3G 75% 23:23



# Controllers



JOYSTICK


128  
128




Controllers



JOYSTICK

V1 128  
V1 128



# Chapter 4: Using Display Widgets






fritzing



3G 94% 21:56



# Value Display Settings



Value



INPUT

Select pin

OK

Digital

Virtual

gp15

gp17

gp18 PWM

gp22


gp23



3G 94% 21:56



# Value Display Settings



Value



## INPUT

GP18

0



1023

## READING RATE

1 sec



Delete






3G 94% 21:57



# Value Display Settings



Value



INPUT

V1

0



1023

READING RATE

PUSH



Delete








3G 93% 21:59



# Labeled Value Settings



Labeled



## INPUT

PIN

0



1023

## LABEL



e.g: Temp: /pin/ °C

## READING RATE

1 sec





3G 18% 23:25



# Widget Box


## YOUR ENERGY BALANCE



⚡ 2,000


+ Add

## DISPLAYS



Value Display

⚡ 200



Labeled Value

⚡ 400




LED

⚡ 100




Gauge

⚡ 300



LCD

⚡ 400



SuperChart



⚡ 900



Terminal


⚡ 200





fritzing

# LED Settings



LED




INPUT

PIN



Delete

## Chapter 5: Using Notification Widgets






Bluetooth, Wi-Fi, 3G signal strength, 92% battery, 18:23



# Controllers





3G 92% 18:23



# Twitter Settings



Blynk.tweet("Hey, Blynkers!");

TWITTER ACCOUNT

Connect Twitter



Delete





3G 92% 18:24



Sign up for Twitter >

## Authorise The Blynk to use your account?



The Blynk

By Blynk

[www.blynk.cc/](http://www.blynk.cc/)

Remember me · [Forgot password?](#)

Authorise app

Cancel

### This application will be able to:

- Read Tweets from your timeline.
- See who you follow, and follow new people.
- Update your profile.
- Post Tweets for you.

### Will not be able to:

- Access your direct messages.



3G 92% 18:24



# Twitter Settings



Blynk.tweet("Hey, Blynkers!");

TWITTER ACCOUNT

@pradeeka7 connected

Disconnect



Delete

Tweets

Tweets & replies

Media



**Pradeeka Seneviratne** @pradeeka7 · 4h

My Raspberry Pi is tweeting using [@blynk\\_app](#) and it's awesome!  
Tweeting time since startup: 120 seconds.



**Pradeeka Seneviratne** @pradeeka7 · 4h

My Raspberry Pi is tweeting using [@blynk\\_app](#) and it's awesome!  
Tweeting time since startup: 90 seconds.



**Pradeeka Seneviratne** @pradeeka7 · 4h



My Raspberry Pi is tweeting using [@blynk\\_app](#) and it's awesome!  
Tweeting time since startup: 60 seconds.



**Pradeeka Seneviratne** @pradeeka7 · 4h

My Raspberry Pi is tweeting using [@blynk\\_app](#) and it's awesome!  
Tweeting time since startup: 30 seconds.





fritzing

Tweets

Tweets & replies

Media



**Pradeeka Seneviratne** @pradeeka7 · 15s



Twitter button is pressed!

Tweeting time since startup: 30 seconds.



**Pradeeka Seneviratne** @pradeeka7 · 33s



Twitter button is pressed!

Tweeting time since startup: 12 seconds.




**Pradeeka Seneviratne** @pradeeka7 · 3h



Twitter button is pressed!

Tweeting time since startup: 9 seconds.






3G 100% 07:13



# Controllers



# Notification Settings



NOTIFY WHEN HARDWARE GOES OFFLINE

OFF  ON

PRIORITY

NORMAL  HIGH

SOUND

DEFAULT RINGTONE (BONGO) →


 Delete



3G 100% 07:14



# Notification Settings



NOTIFY WHEN HARDWARE GOES OFFLINE

OFF



ON

OFFLINE IGNORE PERIOD

Instant



PRIORITY

NORMAL



HIGH

SOUND


DEFAULT RINGTONE (BONGO)







# Notification Settings



NOTIFY WHEN HARDWARE GOES OFFLINE

OFF



ON

Offline ignore period

OK

Instant

1 sec


2 sec



3G 100% 07:15



# Notification Settings



Complete action using



Media Storage



Themes

Always

Just once

DEFAULT RINGTONE (BONGO)



Delete



3G 82% 13:53



# Controllers



## Controllers - Notification

Yaaay... button is pressed!


OK



100% 07:15





# Controllers





# Chapter 6: Connecting with Sensors on Your Mobile Device






Bluetooth, Wi-Fi, 3G signal strength, 51% battery, 19:19



# Smartphone



ACCELMTR



# Accelerometer Settings ⓘ

Accelermtr

### OUTPUT



### WRITE INTERVAL

100 ms ↓

✕ Delete







# Smartphone




ACCELMTR
























# Light Sensor Settings



Light



OUTPUT

V1

WRITE INTERVAL

100 ms



Delete



```
pi@raspberrypi: ~/blynk-library/linux
v0.5.0 on Linux

[1] Connecting to blynk-cloud.com:8442
[3387] Ready (ping: 71ms).
light level: 12 lx
light level: 10 lx
light level: 4 lx
light level: 12 lx
light level: 10 lx
light level: 8 lx
light level: 12 lx
light level: 10 lx
light level: 6 lx
light level: 12 lx
light level: 10 lx
light level: 12 lx
light level: 12 lx
light level: 10 lx
light level: 8 lx
light level: 10 lx
```




Smartphone




PROXIMITY

Far




# ← Proximity Sensor Setting ⓘ



Proximity



OUTPUT




WRITE INTERVAL

100 ms ↓

 Delete

## Chapter 7: Setting Up a Personal Blynk Server



```
pi@raspberrypi: ~
GNU nano 2.7.4 File: /etc/rc.local


#!/bin/sh -e
#
# rc.local
#
# This script is executed at the end of each multiuser runlevel.
# Make sure that the script will "exit 0" on success or any other
# value on error.
#
# In order to enable or disable this script just change the execution
# bits.
#
# By default this script does nothing.

# Print the IP address
_IP=$(hostname -I) || true
if [ "$_IP" ]; then
    printf "My IP address is %s\n" "$_IP"
fi

java -jar /home/pi/server-0.33.4.jar -dataFolder /home/pi/Blynk &

exit 0

^G Get Help  ^O Write Out  ^W Where Is  ^K Cut Text  ^J Justify   ^C Cur Pos
^X Exit      ^R Read File  ^\ Replace   ^U Uncut Text ^T To Linter ^_ Go To Line
```



```
pi@raspberrypi:~ $ crontab -e
no crontab for pi - using an empty one

Select an editor. To change later, run 'select-editor'.
 1. /bin/ed
 2. /bin/nano      <---- easiest
 3. /usr/bin/vim.tiny

Choose 1-3 [2]: █
```

```
pi@raspberrypi: ~
GNU nano 2.7.4 File: /tmp/crontab.V67Nvc/crontab Modified
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h dom mon dow  command
@reboot java -jar /home/pi/server-0.33.4.jar -dataFolder /home/pi/Blynk &
```

^G	Get Help	^O	Write Out	^W	Where Is	^K	Cut Text	^J	Justify	^C	Cur Pos
^X	Exit	^R	Read File	^\	Replace	^U	Uncut Text	^T	To Spell	^_	Go To Line



```
pi@raspberrypi: ~  
[ - ] hwclock.sh  
[ - ] keyboard-setup.sh  
[ + ] kmod  
[ + ] networking  
[ - ] nfs-common  
[ - ] paxctld  
[ - ] plymouth  
[ - ] plymouth-log  
[ + ] procps  
[ + ] raspi-config  
[ - ] rpcbind  
[ - ] rsync  
[ + ] rsyslog  
[ + ] ssh  
[ - ] sudo  
[ + ] triggerhappy  
[ + ] udev  
[ - ] x11-common  
pi@raspberrypi:~ $ ps -aux | grep java  
pi      843 34.2  6.1 358340 58644 pts/0    Sl+  17:05   0:23 java -jar serve  
r-0.33.4-java8.jar -dataFolder /home/pi/Blynk  
pi      1123 0.0  0.0  4372   540 pts/1    S+   17:07   0:00 grep --color=au  
to java  
pi@raspberrypi:~ $
```



Blynk

[Log In](#) | [Create New Account](#)




Log In with Facebook



Why do I need an account?

# ← Create New Account

E-mail

Password 




# Sign Up



# ← Create New Account

E-mail

Password 

## Server Settings OK



BLYNK



CUSTOM

Host address

9443

← Create New Account

E-mail

Server Settings

OK



BLYNK




CUSTOM

192.168.1.4

8443

*	1	2	3	-
+	4	5	6	.
#	7	8	9	⌫
👉	ABC	0	⌂	Done

# ← How energy works



Each widget needs Energy to operate

When you delete a widget Energy is returned

You can always get more Energy in our Store.

Cool! Got it.

← Create New Project

Project Name

CHOOSE DEVICE

ESP8266 ↓

THEME

DARK  LIGHT

Create

← Create New Project

Testing local server

CHOOSE DEVICE

ESP8266 ↓

THEME

DARK  LIGHT

Select your hardware OK

Particle Electron

Particle Photon

Raspberry Pi 2/A+/B+

Raspberry Pi 3 B

Raspberry Pi A/B (Rev2)



← Create New Project

Testing local server

CHOOSE DEVICE

Raspberry Pi 2/A+/B+ ↓

CONNECTION TYPE

WiFi ↓


THEME

DARK  LIGHT

Create



Auth Token was sent to:  
pradeeka@outlook.com

You can also find it in  Project Settings

OK



Don't show again

# ← Project Settings

## How it Works

### HOME SCREEN SHORTCUT

Add Shortcut

Your Launcher app may not support adding shortcuts

### DEVICES



Testing local server

Raspberry Pi 2/A+/B+ (WiFi)



### AUTH TOKENS



Email all



Copy all

### THEME

DARK



LIGHT

### KEEP SCREEN ALWAYS ON

OFF



ON

### NOTIFY DEVICES WHEN APP CONNECTED



Edit note



30 Mar 2018 19:50

e6d7cfa77b9e4dce9ca15bd7bdfd27e6





Bullet



Image

e6d7cfa77b9e4dce9ca15bd7bdfd27e6





Blynk Administration

Users

## Users list

Export

Search

Email	AppName	# Of Projects	LastModifiedTs
admin@blynk.cc	Blynk	0	2018-03-24 22:51:24

1 - 1 on 1

Blynk Administration

Users

Stats

- Realtime
- Request per user
- Messages
- Board types
- Login types
- Widgets
- Projects per user
- Cells per project
- Size of user profile
- Webhook hosts
- IPs

Hardware Info

- Library versions

## Configurations

Export

Name

- twitter4j.properties
- single\_token\_mall\_body.txt
- server.properties
- mall.properties
- gcm.properties
- db.properties

1 - 6 on 6




## Chapter 8: Controlling a Robot with Blynk

```
pi@raspberrypi:~ $ gpio readall
```

-Pi 3-										
BCM	wPi	Name	Mode	V	Physical	V	Mode	Name	wPi	BCM
		3.3v			1	2		5v		
2	8	SDA.1	ALT0	1	3	4		5V		
3	9	SCL.1	ALT0	1	5	6		0v		
4	7	GPIO. 7	IN	0	7	8	1	IN	15	14
		0v			9	10	1	IN	16	15
17	0	GPIO. 0	IN	0	11	12	0	IN	1	18
27	2	GPIO. 2	IN	0	13	14		0v		
22	3	GPIO. 3	IN	0	15	16	0	IN	4	23
		3.3v			17	18	0	IN	5	24
10	12	MOSI	ALT0	1	19	20		0v		
9	13	MISO	ALT0	1	21	22	0	IN	6	25
11	14	SCLK	ALT0	0	23	24	1	OUT	10	8
		0v			25	26	1	OUT	11	7
0	30	SDA.0	IN	1	27	28	1	OUT	31	1
5	21	GPIO.21	IN	0	29	30		0v		
6	22	GPIO.22	IN	0	31	32	0	IN	26	12
13	23	GPIO.23	IN	1	33	34		0v		
19	24	GPIO.24	IN	0	35	36	0	IN	27	16
26	25	GPIO.25	IN	0	37	38	0	IN	28	20
		0v			39	40	0	IN	29	21











Blynk



New Project



My Apps



Community





# Create New Project

Robot Car

CHOOSE DEVICE

Raspberry Pi 2/A+/B+



CONNECTION TYPE

WiFi



THEME

DARK



LIGHT

Create




3G 39% 20:41



Robot Car



Auth Token was sent to:  
pradeeka@outlook.com

You can also find it in  Project Settings

OK



Don't show again



# Robot Car




BUTTON





BUTTON



BUTTON



BUTTON





# Robot Car



BUTTON

OFF

BUTTON

OFF

BUTTON

OFF

BUTTON

OFF





# Robot Car



FORWARD

V0

LEFT




V1

RIGHT

V2


BACKWARD

V3





# Robot Car




FORWARD



LEFT



RIGHT



BACKWARD

