

## Chapter 1: Developer Workflow

### Available commands:

```
about      Short information about Composer
archive    Create an archive of this composer package
browse     Opens the package's repository URL or homepage in your browser.
clear-cache Clears composer's internal package cache.
clearcache Clears composer's internal package cache.
config     Set config options
create-project Create new project from a package into given directory.
```

```
cchumley@forumone:~/Sandbox|⇒ composer create-project drupal-composer/drupal-project:8.x-dev mastering --stability dev --no-interaction
Installing drupal-composer/drupal-project (8.x-dev a271d50e329428529e85f473db3a55c8f5514a7e)
- Installing drupal-composer/drupal-project (8.x-dev a271d50) Cloning a271d50e32 from cache
Created project in mastering
```



```
▼ mastering
  ► drush
  ► scripts
  ► vendor
  ▼ web
    ► core
    ► modules
    ► profiles
    ► sites
    ► themes
    ► autoload.php
    ► index.php
    ► robots.txt
    ► update.php
    ► web.config
    ► composer.json
    ► composer.lock
    ► LICENSE
    ► phpunit.xml.dist
    ► README.md
```

### Core Drush commands: (core)

```
archive-dump (ard,      Backup your code, files, and database into a single file.
archive-backup, arb)
archive-restore        Expand a site archive into a Drupal web site.
(arr)
core-cli (php)        Open an interactive shell on a Drupal site.
```

```
cchumley@forumone:~/Sandbox|⇒ drush dl drupal
Project drupal (8.3.4) downloaded to /Users/cchumley/Sandbox/drupal-8.3.4.
```

```
cchumley@forumone:~/Sandbox |⇒ ll
total 0
drwxr-xr-x 24 cchumley staff 816B Jun 21 14:28 drupal-8.3.4
drwxr-xr-x 13 cchumley staff 442B Jul 2 09:54 mastering
```

admin ☆

[View](#) [Shortcuts](#) [Edit](#)

[Home](#) » [admin](#)

✓ You have just used your one-time login link. It is no longer necessary to use this link to log in. Please change your password.

**Email address \***

A valid email address. All emails from the system will be sent to this address. The email address is not made public and will only be used if you wish to receive a new password or wish to receive certain news or notifications by email.

**Username \***

Several special characters are allowed, including space, period (.), hyphen (-), apostrophe ('), underscore (\_), and the @ sign.

**Password**

Password strength:

**Confirm password**

Passwords match:

```
⇒ ./vendor/drupal/console/bin/drupal
```

```
Drupal Console (1.0.0-rc23)
```

```
=====
```

```
⇒ ./vendor/drupal/console/bin/drupal site:install
```

```
Select Drupal profile to be installed:
```

```
[0] minimal
```

```
[1] standard
```

```
> 1
```

```
Select language for your Drupal installation [English]:
```

```
> English
```

```
Drupal Database type:
[0] MySQL, MariaDB, Percona Server, or equivalent
[1] PostgreSQL
[2] SQLite
> 2
```

```
Database File [sites/default/files/.ht.sqlite]:
> mastering.sqlite
```

```
Database Prefix [ ]:
>
```

```
Provide your Drupal site name [Drupal 8]:
> Mastering Drupal 8
```

```
Provide your Drupal site mail [admin@example.com]:
> admin@example.com
```

```
Provide your Drupal administrator account name [admin]:
> admin
```

```
Provide your Drupal administrator account password:
>
```

```
Provide your Drupal administrator account mail [admin@example.com]:
> admin@example.com
```

```
Starting Drupal 8 install process
```

```
[OK] Your Drupal 8 installation was completed successfully
```

#### Available commands:

about	Display basic information about Drupal Console project
chain	Chain command execution
check	System requirement checker
exec	Execute an external command.
help	Displays help for a command
init	Copy configuration files.
list	Lists all available commands

```
⇒ drupal server
```

```
[OK] Executing php from "/Applications/MAMP/bin/php/php7.0.13/bin/php".
```

```
Listening on "127.0.0.1:8088".
```



## Mastering Drupal 8

Home

Search

## Welcome to Mastering Drupal 8

No front page content has been created yet.



```
⇒ which git  
/usr/local/bin/git
```



# Built for developers

GitHub is a development platform inspired by the way you work. Host code, manage projects, and build software alongside millions of other developers.

Use at least one letter, one numeral, and seven characters.


[Sign up for GitHub](#)

By clicking "Sign up for GitHub", you agree to our [terms of service](#) and [privacy policy](#). We'll occasionally send you account related emails.

## Create a new repository

A repository contains all the files for your project, including the revision history.

Owner

 chazchumley ▾

Repository name

Mastering-Drupal-8 ✓

Great repository names are short and memorable. Need inspiration? How about **stunning-octo-meme**.

Description (optional)

Mastering Drupal 8 - A book by Chaz Chumley and William Hurley

 **Public**

Anyone can see this repository. You choose who can commit.

 **Private**

You choose who can see and commit to this repository.

**Initialize this repository with a README**

This will let you immediately clone the repository to your computer. Skip this step if you're importing an existing repository.

Add .gitignore: **None** ▾

Add a license: **None** ▾



**Create repository**

```
cchumley@forumone:~/Sandbox/mastering|
⇒ git init
Initialized empty Git repository in /Users/cchumley/Sandbox/mastering/.git/
```

Mastering Drupal 8 - A book by Chaz Chumley and William Hurley

Edit

New Add topics

1 commit 1 branch 0 releases 1 contributor GPL-2.0

Branch: master

New pull request

Create new file

Upload files

Find file

Clone or download

chazchumley	Initial Drupal instance added to repo	Latest commit ac5d8e5 5 minutes ago
console/cache/6f1abcc3-4e21-45a2-babf-89f7a...	Initial Drupal instance added to repo	5 minutes ago
drush	Initial Drupal instance added to repo	5 minutes ago
scripts/composer	Initial Drupal instance added to repo	5 minutes ago
web	Initial Drupal instance added to repo	5 minutes ago
.gitignore	Initial Drupal instance added to repo	5 minutes ago
.travis.yml	Initial Drupal instance added to repo	5 minutes ago
LICENSE	Initial Drupal instance added to repo	5 minutes ago
README.md	Initial Drupal instance added to repo	5 minutes ago
composer.json	Initial Drupal instance added to repo	5 minutes ago
composer.lock	Initial Drupal instance added to repo	5 minutes ago
phpunit.xml.dist	Initial Drupal instance added to repo	5 minutes ago

# DRUPAL VM

GETTING STARTED

DOCS

SCREENSHOTS

ABOUT

A VM for local Drupal development, built with Vagrant + Ansible

macOS Windows Linux

View on GitHub

Download Drupal VM

## Chapter 2: Site Configuration



Search

### Welcome to Mastering Drupal 8

No front page content has been created yet.



[Home](#)

Search

### Log in

[Log in](#)

[Create new account](#)

[Reset your password](#)

**Username \***

Enter your Mastering Drupal 8 username.

**Password \***

Enter the password that accompanies your username.

[Log in](#)





# Mastering Drupal 8

Home

Home

Search



## admin

View Shortcuts Edit

Member for 20 hours 1 minute

Tools

[Add content](#)

## Content ★

Content

Comments

Files

Home » Administration

[+ Add content](#)

Published status Content type Title Language  
- Any - - Any -

Filter

TITLE	CONTENT TYPE	AUTHOR	STATUS	UPDATED	OPERATIONS
-------	--------------	--------	--------	---------	------------

No content available.

## Structure ☆

[Home](#) » [Administration](#)

### ➤ [Block layout](#)

Configure what block content appears in your site's sidebars and other regions.

### ➤ [Comment types](#)

Manage form and displays settings of comments.

### ➤ [Contact forms](#)

Create and manage contact forms.

### ➤ [Content types](#)

Create and manage fields, forms, and display settings for your content.

### ➤ [Display modes](#)

Configure what displays are available for your content and forms.

### ➤ [Menus](#)

Manage menus and menu links.

### ➤ [Taxonomy](#)

Manage tagging, categorization, and classification of your content.

### ➤ [Views](#)

Manage customized lists of content.

## Appearance ☆

[List](#)

[Update](#)

[Settings](#)


[Home](#) » [Administration](#)

Set and configure the default theme for your website. Alternative [themes](#) are available.

You can place blocks for each theme on the [block layout](#) page.

[+ Install new theme](#)

### Installed themes



#### **Bartik 8.3.4 (default theme)**

A flexible, recolorable theme with many regions and a responsive, mobile-first layout.

[Settings](#)

## Extend

List

Update

Uninstall

[Home](#) » [Administration](#)

Download additional contributed modules to extend your site's functionality.

Regularly review and install [available updates](#) to maintain a secure and current site. Always run the [update script](#) each time a module is updated.

[+ Install new module](#)

Filter by name or description

Enter a part of the module name or description

► CORE

► CORE (EXPERIMENTAL)

► FIELD TYPES


► MULTILINGUAL

► WEB SERVICES

[Install](#)

## Configuration

[Home](#) » [Administration](#)

 One or more problems were detected with your Drupal installation. Check the [status report](#) for more information.

Hide descriptions

### PEOPLE

➤ [Account settings](#)

Configure default user account settings, including fields, registration requirements, and email messages.

### CONTENT AUTHORIZING

➤ [Text formats and editors](#)

Select and configure text editors, and how content is filtered when displayed.

### SYSTEM

➤ [Basic site settings](#)

Change site name, email address, slogan, default front page, and error pages.

➤ [Cron](#)

Manage automatic site maintenance tasks.

### USER INTERFACE

➤ [Shortcuts](#)

## People

List

Permissions

Roles

Home » Administration

[+ Add user](#)

Name or email contains

Role

Permission

Status

[Filter](#)

Action

[Apply to selected items](#)

<input type="checkbox"/>	USERNAME	STATUS	ROLES	MEMBER FOR	LAST ACCESS	OPERATIONS
<input type="checkbox"/>	admin	Active	• Administrator	20 hours 32 minutes	5 minutes 18 seconds ago	<a href="#">Edit</a>

[Apply to selected items](#)

## Reports

Home » Administration

### [Available updates](#)

Get a status report about available updates for your installed modules and themes.

### [Recent log messages](#)

View events that have recently been logged.

### [Field list](#)

Overview of fields on all entity types.

### [Status report](#)

Get a status report about your site's operation.

### [Top 'access denied' errors](#)

View 'access denied' errors (403s).

### [Top 'page not found' errors](#)

View 'page not found' errors (404s).

### [Top search phrases](#)

View most popular search phrases.

### [Views plugins](#)

Overview of plugins used in all views.

## Help ☆

[Home](#) » [Administration](#)

### Getting Started

Follow these steps to set up and start using your website:

1. **Configure your website** Once logged in, visit the [Administration page](#), where you may [customize and configure](#) all aspects of your website.
2. **Enable additional functionality** Next, visit the [Extend page](#) and enable modules that suit your specific needs. You can find additional modules at the [Drupal.org modules page](#).
3. **Customize your website design** To change the "look and feel" of your website, visit the [Appearance page](#). You may choose from one of the included themes or download additional themes from the [Drupal.org themes page](#).
4. **Start posting content** Finally, you may [add new content](#) to your website.

For more information, refer to the help listed on this page or to the [online documentation](#) and [support pages](#) at [drupal.org](#).

## Basic site settings ☆

[Home](#) » [Administration](#) » [Configuration](#) » [System](#)

▶ SITE DETAILS

▶ FRONT PAGE

▶ ERROR PAGES

Save configuration

### ▼ SITE DETAILS

#### Site name \*

Mastering Drupal 8

#### Slogan

How this is used depends on your site's theme.

#### Email address \*

admin@example.com

The *From* address in automated emails sent during registration and new password requests, and other notifications. (Use an address ending in your site's domain to help prevent this email being flagged as spam.)

### ▼ FRONT PAGE

#### Default front page

http://127.0.0.1:8888 /node

Optionally, specify a relative URL to display as the front page. Leave blank to display the default front page.

#### ▼ ERROR PAGES

##### Default 403 (access denied) page

This page is displayed when the requested document is denied to the current user. Leave blank to display a generic "access denied" page.

##### Default 404 (not found) page

This page is displayed when no other content matches the requested document. Leave blank to display a generic "page not found" page.

## Performance ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Development](#)

#### ▼ CLEAR CACHE

Clear all caches

#### ▼ CACHING

Note: Drupal provides an internal page cache module that is recommended for small to medium-sized websites.

##### Page cache maximum age

<no caching> ▼

The maximum time a page can be cached by browsers and proxies. This is used as the value for max-age in Cache-Control headers.

#### ▼ BANDWIDTH OPTIMIZATION

External resources can be optimized automatically, which can reduce both the size and number of requests made to your website.

- Aggregate CSS files
- Aggregate JavaScript files

#### ▼ CLEAR CACHE

Clear all caches

```
⇒ drush cr
Cache rebuild complete.
```

```
⇒ drupal cache:rebuild all
Rebuilding cache(s), wait a moment please.
```

```
[OK] Done clearing cache(s).
```

```
/**
 * Configuration overrides.
 *
 * To globally override specific configuration values for this site,
 * set them here. You usually don't need to use this feature. This is
 * useful in a configuration file for a vhost or directory, rather than
 * the default settings.php.
 *
 * Note that any values you provide in these variable overrides will not be
 * viewable from the Drupal administration interface. The administration
 * interface displays the values stored in configuration so that you can stage
 * changes to other environments that don't have the overrides.
 *
 * There are particular configuration values that are risky to override. For
 * example, overriding the list of installed modules in 'core.extension' is not
 * supported as module install or uninstall has not occurred. Other examples
 * include field storage configuration, because it has effects on database
 * structure, and 'core.menu.static_menu_link_overrides' since this is cached in
 * a way that is not config override aware. Also, note that changing
 * configuration values in settings.php will not fire any of the configuration
 * change events.
 */
# $config['system.site']['name'] = 'My Drupal site';
# $config['system.theme']['default'] = 'stark';
# $config['user.settings']['anonymous'] = 'Visitor';
```



My Drupal site

Home

#### ▼ SITE DETAILS

Site name \*

```
⇒ drush config-list
automated_cron.settings
block.block.bartik_account_menu
block.block.bartik_branding
block.block.bartik_breadcrumbs
block.block.bartik_content
```

```
⇒ drush config-get system.site
uuid: 6f1abcc3-4e21-45a2-babf-89f7ad960ad6
name: 'Mastering Drupal 8'
mail: admin@example.com
slogan: ''
page:
  403: ''
  404: ''
  front: /node
admin_compact_mode: false
weight_select_max: 100
langcode: en
default_langcode: en
_core:
  default_config_hash: AyT9s80UcclfALRE_imBy0MgtZ19e0lqdF6zI3p7yqo
```

```
⇒ drush config-get system.site --include-overridden

uuid: 6f1abcc3-4e21-45a2-babf-89f7ad960ad6
name: 'My Drupal site'
mail: admin@example.com
slogan: ''
page:
  403: ''
  404: ''
  front: /node
admin_compact_mode: false
weight_select_max: 100
langcode: en
default_langcode: en
_core:
  default_config_hash: AyT9s80UcclfALRE_imBy0MgtZ19e0lqdF6zI3p7yqo
```

```
⇒ drush config-set system.site mail 'test@example.com'
Do you want to update mail key in system.site config? (y/n): y
```

```
⇒ drupal config:debug

Configuration name.
automated_cron.settings
block.block.bartik_account_menu
block.block.bartik_branding
block.block.bartik_breadcrumbs
block.block.bartik_content
```



```
⇒ drupal config:debug system.site
```

### system.site

```
uuid: 6f1abcc3-4e21-45a2-babf-89f7ad960ad6
name: 'Mastering Drupal 8'
mail: 'test@example.com'
slogan: ''
page:
  403: ''
  404: ''
  front: /node
admin_compact_mode: false
weight_select_max: 100
langcode: en
default_langcode: en
_core:
  default_config_hash: AyT9s80Ucc1fALRE_imBy0MgtZ19e0lqdf6zI3p7yqo
```

```
uuid: 6f1abcc3-4e21-45a2-babf-89f7ad960ad6
name: 'Mastering Drupal 8'
mail: 'test@example.com'
slogan: ''
page:
  403: ''
  404: ''
  front: /node
admin_compact_mode: false
weight_select_max: 100
langcode: en
default_langcode: en
_core:
  default_config_hash: AyT9s80Ucc1fALRE_imBy0MgtZ19e0lqdf6zI3p7yqo
```

## File system ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Media](#)

### Public file system path

sites/default/files

A local file system path where public files will be stored. This directory must exist and be writable by Drupal. This directory must be relative to the Drupal installation directory and be accessible over the web. This must be changed in settings.php

### Public file base URL

http://127.0.0.1:8888/sites/default/files

The base URL that will be used for public file URLs. This can be changed in settings.php

### Private file system path

Not set

An existing local file system path for storing private files. It should be writable by Drupal and not accessible over the web. This must be changed in settings.php

### Temporary directory

A local file system path where temporary files will be stored. This directory should not be accessible over the web.

### Default download method

Public local files served by the webserver.

This setting is used as the preferred download method. The use of public files is more efficient, but does not provide any access control.

### Delete orphaned files after

Orphaned files are not referenced from any content but remain in the file system and may appear in administrative listings. **Warning:** If enabled, orphaned files will be permanently deleted and may not be recoverable.

```
/**
 * Public file path:
 *
 * A local file system path where public files will be stored. This directory
 * must exist and be writable by Drupal. This directory must be relative to
 * the Drupal installation directory and be accessible over the web.
 */
# $settings['file_public_path'] = 'sites/default/files';
```

#### Public file system path

sites/default/files/test

A local file system path where public files will be stored. This directory must exist and be writable by Drupal. This directory must be relative to the Drupal installation directory and be accessible over the web. This must be changed in settings.php

## Regional settings ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#)

### ▼ LOCALE

#### Default country

United States ▼

#### First day of week

Sunday ▼

### ▼ TIME ZONES

#### Default time zone

America/New York ▼

Users may set their own time zone

Remind users at login if their time zone is not set  
Only applied if users may set their own time zone.

#### Time zone for new users

Default time zone

Empty time zone

Users may set their own time zone at registration

Only applied if users may set their own time zone.

## Date and time formats ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#)

[+ Add format](#)

NAME	PATTERN	OPERATIONS
Default long date	Sunday, July 2, 2017 – 17:14	<a href="#">Edit</a> ▼
Default medium date	Sun, 07/02/2017 – 17:14	<a href="#">Edit</a> ▼
Default short date	07/02/2017 – 17:14	<a href="#">Edit</a> ▼
Fallback date format	Sun, 07/02/2017 – 17:14	
HTML Date	2017-07-02	
HTML Datetime	2017-07-02T17:14:07+0200	
HTML Month	2017-07	
HTML Time	17:14:07	
HTML Week	2017-W26	
HTML Year	2017	
HTML Yearless date	07-02	

## Edit date format ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Date and time formats](#)

### Name

Machine name: long

Name of the date format

### Format string \*

Displayed as *Sunday, July 2, 2017 – 17:15 PM*

A user-defined date format. See the [PHP manual](#) for available options.

[Save format](#)

## Add date format

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Date and time formats](#)

### Name

Machine name: `day` [\[Edit\]](#)

Name of the date format

### Format string <sup>\*</sup>

Displayed as *Wednesday*

A user-defined date format. See the [PHP manual](#) for available options.

[Add format](#)

## Chapter 3: Managing Users, Roles, and Permissions

### People ☆

List Permissions Roles

Home » Administration

[+ Add user](#)

Name or email contains  Role - Any - Permission - Any - Status - Any -

[Filter](#)

Action

Add the Administrator role to the selected users

[Apply to selected items](#)

<input type="checkbox"/>	USERNAME	STATUS	ROLES	MEMBER FOR	LAST ACCESS	OPERATIONS
<input type="checkbox"/>	admin	Active	• Administrator	5 days 21 hours	2 minutes 14 seconds ago	<a href="#">Edit</a>

[Apply to selected items](#)

### Roles ☆

List Permissions Roles

Home » Administration » People

A role defines a group of users that have certain privileges. These privileges are defined on the [Permissions page](#). Here, you can define the names and the display sort order of the roles on your site. It is recommended to order roles from least permissive (for example, Anonymous user) to most permissive (for example, Administrator user). Users who are not logged in have the Anonymous user role. Users who are logged in have the Authenticated user role, plus any other roles granted to their user account.

[+ Add role](#)

[Show row weights](#)

NAME	OPERATIONS
<input type="checkbox"/> Anonymous user	<a href="#">Edit</a>
<input type="checkbox"/> Authenticated user	<a href="#">Edit</a>
<input type="checkbox"/> Administrator	<a href="#">Edit</a>

[Save](#)

## Add role ☆

[Home](#) » [Administration](#) » [People](#) » [Roles](#)

**Role name \***

Machine name: developer [\[Edit\]](#)

The name for this role. Example: "Moderator", "Editorial board", "Site architect".

[Save](#)

[Show row weights](#)

NAME	OPERATIONS
✚ Anonymous user	<a href="#">Edit</a> ▾
✚ Authenticated user	<a href="#">Edit</a> ▾
✚ Administrator	<a href="#">Edit</a> ▾
✚ Developer	<a href="#">Edit</a> ▾

⚠ \* You have unsaved changes.

NAME	OPERATIONS
✚ Anonymous user	<a href="#">Edit</a> ▾
✚ Authenticated user	<a href="#">Edit</a> ▾
✚ Developer*	<a href="#">Edit</a> ▾
✚ Administrator	<a href="#">Edit</a> ▾

[Save](#)

## Edit role ☆

[Home](#) » [Administration](#) » [People](#) » [Roles](#)

**Role name \***

Machine name: developer

The name for this role. Example: "Moderator", "Editorial board", "Site architect".

[Save](#)

[Delete](#)

## Permissions ☆

[List](#) [Permissions](#) [Roles](#)

[Home](#) » [Administration](#) » [People](#)

Permissions let you control what users can do and see on your site. You can define a specific set of permissions for each role. (See the [Roles](#) page to create a role.) Any permissions granted to the Authenticated user role will be given to any user who is logged in to your site. From the [Account settings](#) page, you can make any role into an Administrator role for the site, meaning that role will be granted all new permissions automatically. You should be careful to ensure that only trusted users are given this access and level of control of your site.

[Hide descriptions](#)

PERMISSION	ANONYMOUS USER	AUTHENTICATED USER	DEVELOPER	ADMINISTRATOR
<b>Block</b>				
Administer blocks	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

PERMISSION	ANONYMOUS USER	AUTHENTICATED USER	DEVELOPER	ADMINISTRATOR
<b>Block</b>				
Administer blocks	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

[Show row weights](#)

NAME	OPERATIONS
✚ Anonymous user	<a href="#">Edit</a>
✚ Authenticated user	<a href="#">Edit</a>
✚ Developer	<a href="#">Edit</a> <a href="#">Edit permissions</a> <a href="#">Delete</a>
✚ Administrator	

## Edit role ☆

[Home](#) » [Administration](#) » [People](#) » [Permissions](#)

[Hide descriptions](#)

PERMISSION	DEVELOPER
<b>Block</b>	
Administer blocks	<input checked="" type="checkbox"/>

## Add user ☆

[Home](#) » [Administration](#) » [People](#)

This web page allows administrators to register new users. Users' email addresses and usernames must be unique.

### Email address

A valid email address. All emails from the system will be sent to this address. The email address is not made public and will only be used if you wish to receive a new password or wish to receive certain news or notifications by email.

### Username \*

Several special characters are allowed, including space, period (.), hyphen (-), apostrophe ('), underscore (\_), and the @ sign.

### Password \*

■ Password strength: Weak

### Confirm password \*

Passwords match: yes

### Action

Apply to selected items

<input type="checkbox"/>	USERNAME	STATUS	ROLES	MEMBER FOR	LAST ACCESS	OPERATIONS
<input checked="" type="checkbox"/>	developer	Active		3 seconds	never	<a href="#">Edit</a>
<input type="checkbox"/>	admin	Active	• Administrator	5 days 21 hours	3 seconds ago	<a href="#">Edit</a>

Apply to selected items



## Account settings

Settings

Manage fields

Manage form display

Manage display

Home » Administration » Configuration » People

### ▶ CONTACT SETTINGS

### ▶ ANONYMOUS USERS

### ▶ ADMINISTRATOR ROLE

### ▶ REGISTRATION AND CANCELLATION

#### Notification email address

The email address to be used as the 'from' address for all account notifications listed below. If 'Visitors, but administrator approval is required' is selected above, a notification email will also be sent to this address for any new registrations. Leave empty to use the default system email address (*admin@example.com*).

#### Emails

##### Welcome (new user created by administrator)

##### Welcome (awaiting approval)

##### Admin (user awaiting approval)

##### Welcome (no approval required)

##### Account activation

##### Account blocked

##### Account cancellation confirmation

##### Account canceled

##### Password recovery

Edit the welcome email messages sent to new member accounts created by an administrator. Available variables are: [site:name], [site:url], [user:display-name], [user:account-name], [user:mail], [site:login-url], [site:url-brief], [user:edit-url], [user:one-time-login-url], [user:cancel-url].

#### Subject

An administrator created an account for you at [site:name]

#### Body

[user:display-name],

A site administrator at [site:name] has created an account for you. You may now log in by clicking this link or copying and pasting it into your browser:

[user:one-time-login-url]

This link can only be used once to log in and will lead you to a page where you can set your password.

After setting your password, you will be able to log in at [site:login-url] in the future using:

username: [user:name]

password: Your password

-- [site:name] team

### ▼ CONTACT SETTINGS

- Enable the personal contact form by default for new users  
Changing this setting will not affect existing users.

### ▼ ADMINISTRATOR ROLE

#### Administrator role

Administrator ▼

This role will be automatically assigned new permissions whenever a module is enabled. Changing this setting will not affect existing permissions.

## ▼ REGISTRATION AND CANCELLATION

### Who can register accounts?

- Administrators only
- Visitors
- Visitors, but administrator approval is required

### Require email verification when a visitor creates an account

New users will be required to validate their email address prior to logging into the site, and will be assigned a system-generated password. With this setting disabled, users will be logged in immediately upon registering, and may select their own passwords during registration.

### Enable password strength indicator

### When cancelling a user account

- Disable the account and keep its content.
- Disable the account and unpublish its content.
- Delete the account and make its content belong to the *Anonymous* user.

Users with the *Select method for cancelling account* or *Administer users permissions* can override this default method.

## Manage fields ☆

[Settings](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Configuration](#) » [People](#) » [Account settings](#)

This form lets administrators add and edit fields for storing user data.

[+ Add field](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Picture	user_picture	Image	<a href="#">Edit</a> ▾

## Add field ☆

[Home](#) » [Administration](#) » [Configuration](#) » [People](#) » [Account settings](#) » [Manage fields](#)

### Add a new field

### Label \*

 Machine name: field\_full\_name [\[Edit\]](#)[Save and continue](#)

## Full name ☆

[Edit](#)[Field settings](#)

[Home](#) » [Administration](#) » [Configuration](#) » [People](#) » [Account settings](#) » [Manage fields](#) » Full name

These settings apply to the *Full name* field everywhere it is used. These settings impact the way that data is stored in the database and cannot be changed once data has been created.

### Maximum length \*

The maximum length of the field in characters.

Allowed number of values

[Save field settings](#)

## Full name settings for User ☆

[Edit](#)[Field settings](#)

[Home](#) » [Administration](#) » [Configuration](#) » [People](#) » [Account settings](#) » [Manage fields](#)

✓ Updated field *Full name* field settings.

### Label \*

### Help text

Instructions to present to the user below this field on the editing form.

Allowed HTML tags: <a> <b> <big> <code> <del> <em> <i> <ins> <pre> <q> <small> <span> <strong> <sub> <sup> <tt> <ol> <ul> <li> <p> <br> <img>

This field supports tokens.

Required field

### ▼ DEFAULT VALUE

The default value for this field, used when creating new content.

Full name

[Save settings](#)[Delete](#)[+ Add field](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Full name	field_full_name	Text (plain)	<a href="#">Edit</a> ▼
Picture	user_picture	Image	<a href="#">Edit</a> ▼

## Manage form display ☆

[Settings](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Configuration](#) » [People](#) » [Account settings](#)

This form lets administrators configure how form fields should be displayed when editing a user profile.

[Show row weights](#)

⚠ \* You have unsaved changes.

FIELD	WIDGET	
✚ Full name*	Textfield ▾	Textfield size: 60 ⚙
✚ User name and password	Visible ▾	

## developer ☆

[View](#)[Shortcuts](#)[Edit](#)[Contact](#)

[Home](#) » [developer](#)

Full name

Email address \*

A valid email address. All emails from the system will be sent to this address. The email address is not made public and will only be used if you wish to receive a new password or wish to receive certain news or notifications by email.

```
Role commands: (role)
role-add-perm (rap) Grant specified permission(s) to a role.
role-create (rcrt) Create a new role.
role-delete (rdel) Delete a role.
role-list (rls) Display a list of all roles defined on the system. If a role name is
provided as an argument, then all of the permissions of that role will be
listed. If a permission name is provided as an option, then all of the roles
that have been granted that permission will be listed.
role-remove-perm (rmp) Remove specified permission(s) from a role.
```

```
⇒ drush role-list
ID          Role Label
anonymous  Anonymous user
authenticated Authenticated user
developer   Developer
administrator Administrator
```

```
⇒ drush role-create editor
```

```
Created "editor"
```

```
[success]
```

```
⇒ drush role-list
ID          Role Label
anonymous   Anonymous user
authenticated Authenticated user
developer    Developer
administrator Administrator
editor       Editor
```

```
⇒ drush role-delete editor
```

```
Deleted "editor"
```

```
[success]
```

```
⇒ drush role-list
ID          Role Label
anonymous   Anonymous user
authenticated Authenticated user
developer    Developer
administrator Administrator
```

```
⇒ drush role-list developer
```

```
Permission
administer blocks
```

```
⇒ drush role-add-perm developer 'administer comment types'
```

```
Added "administer comment types" to "Developer"
Cache rebuild complete.
```

```
[success]
```

```
[ok]
```

```
⇒ drush role-list developer
```

```
Permission
administer blocks
administer comment types
```

```
⇒ drush role-remove-perm developer 'administer comment types'
```

```
Removed "administer comment types" from "Developer"
Cache rebuild complete.
```

```
[ok]
```

```
[ok]
```

```
User commands: (user)
user-add-role (urole) Add a role to the specified user accounts.
user-block (ublk)    Block the specified user(s).
user-cancel (ucan)   Cancel a user account with the specified name.
user-create (ucrt)   Create a user account with the specified name.
user-information     Print information about the specified user(s).
(ufreq)
user-login (uli)     Display a one time login link for the given user account (defaults to uid 1).
user-password (upwd) (Re)Set the password for the user account with the specified name.
user-remove-role     Remove a role from the specified user accounts.
(urrole)
user-unblock (uublk) Unblock the specified user(s).
```

```
⇒ drush user-information 2
```

```
User ID      : 2
User name    : developer
User mail    : developer@example.com
User roles   : authenticated
              developer
User status  : 1
```

```
⇒ drush user-add-role 'administrator' 2
Added role administrator role to developer
```

```
[success]
```

```
⇒ drush user-information 2
```

```
User ID      : 2
User name    : developer
User mail    : developer@example.com
User roles   : authenticated
              developer
              administrator
User status  : 1
```

```
⇒ drush user-remove-role 'administrator' 2
Removed administrator role from developer
```

```
[success]
```

```
⇒ drush user-information 2

User ID      : 2
User name    : developer
User mail    : developer@example.com
User roles   : authenticated
              developer
User status  : 1
```

```
⇒ drush user-block 2
Blocked user(s): developer [success]
```

```
⇒ drush user-unblock 2
Unblocked user(s): developer [success]
```

```
⇒ drush user-create editor --mail='editor@email.com' --password='letmein'

User ID      : 3
User name    : editor
User mail    : editor@email.com
User roles   : authenticated
User status  : 1
```

```
⇒ drush user-cancel editor

Cancel user account?: (y/n): y
Cancelled user(s): editor [success]
The update has been performed. [status]
editor has been deleted. [status]
```

```
⇒ drush user-password developer --password='new-password'

Changed password for developer [success]
```

```
⇒ drush user-login --uri='http://127.0.0.1:8088'

http://127.0.0.1:8088/user/reset/1/1488730930/4sM6LkLojZeREIdUqJWhvn4sTJV3yZS8Kf0XZxKUmzQ/login
```

# admin ☆

[View](#)[Shortcuts](#)[Edit](#)

[Home](#) » [admin](#)

✓ You have just used your one-time login link. It is no longer necessary to use this link to log in. Please change your password.

**Full name**

**Email address \***

A valid email address. All emails from the system will be sent to this address. The email address is not made public and will only be used if you wish to receive a new password or wish to receive certain news or notifications by email.

**Username \***

Several special characters are allowed, including space, period (.), hyphen (-), apostrophe ('), underscore (\_), and the @ sign.

**Password**

Password strength:

**Confirm password**

Passwords match:



# Chapter 4: Content Types, Taxonomy, and Comment Types

## Content types ☆

[Home](#) » [Administration](#) » [Structure](#)

[+ Add content type](#)

NAME	DESCRIPTION	OPERATIONS
Article	Use <i>articles</i> for time-sensitive content like news, press releases or blog posts.	<a href="#">Manage fields</a> ▾
Basic page	Use <i>basic pages</i> for your static content, such as an 'About us' page.	<a href="#">Manage fields</a> ▾

## Edit *Basic page* content type ☆

[Edit](#)

[Manage fields](#)

[Manage form display](#)

[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#)

### Name \*

Machine name: page

The human-readable name of this content type. This text will be displayed as part of the list on the *Add content* page. This name must be unique.

### Description

Use `<em>basic pages</em>` for your static content, such as an 'About us' page.

This text will be displayed on the *Add new content* page.

### Submission form settings

Title

#### Publishing options

Published, Create new revision

#### Display settings

Don't display post information

#### Menu settings

### Title field label \*

### Preview before submitting

Disabled

Optional

Required

### Explanation or submission guidelines

This text will be displayed at the top of the page when creating or editing content of this type.

<b>Submission form settings</b>	
Title	<b>Title field label *</b> <input type="text" value="Title"/>
<b>Publishing options</b> Published , Create new revision	<b>Preview before submitting</b> <input type="radio"/> Disabled <input checked="" type="radio"/> Optional <input type="radio"/> Required
<b>Display settings</b> Don't display post information	<b>Explanation or submission guidelines</b> <div style="border: 1px solid #ccc; height: 40px; width: 100%;"></div> <p>This text will be displayed at the top of the page when creating or editing content of this type.</p>
<b>Menu settings</b>	

## Add content ★

- [Home](#)
- 
- [Article](#)  
Use *articles* for time-sensitive content like news, press releases or blog posts.

---

  - [Basic page](#)  
Use *basic pages* for your static content, such as an 'About us' page.

## Create Basic page ★

[Home](#) » [Add content](#)

<b>Title *</b> <input type="text" value="About Us"/>	<p><i>Last saved: Not saved yet</i></p> <p><b>Author:</b> admin</p> <input checked="" type="checkbox"/> Create new revision <p><b>Revision log message</b></p> <div style="border: 1px solid #ccc; height: 30px; width: 100%;"></div> <p>Briefly describe the changes you have made.</p>
<b>Body (Edit summary)</b> <div style="border: 1px solid #ccc; padding: 5px;"> <p><b>B</b> <b>I</b>       Normal   Source</p> <p>Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut nec massa nec mauris tincidunt ultricies. Sed vehicula eros ac egestas mollis. Duis rhoncus dui vitae sapien feugiat blandit. Cras convallis eget nulla vitae mattis. Ut nunc mi, efficitur eget purus nec, mattis semper lorem. Suspendisse varius, quam ac lobortis hendrerit, diam mauris porttitor risus, a convallis elit tortor sed turpis. Etiam aliquam, neque eu laoreet aliquam, massa eros tristique enim, eu pulvinar erat enim at nibh. Praesent bibendum purus sit amet turpis vestibulum congue.</p> </div>	
<p>body p</p> <p>Text format <span style="border: 1px solid #ccc; padding: 2px;">Basic HTML</span> <a href="#">About text formats ?</a></p>	
<p><span style="background-color: #0070c0; color: white; padding: 5px 10px; border-radius: 3px;">Save and publish</span> <span style="border: 1px solid #ccc; padding: 5px 10px; border-radius: 3px;">Preview</span></p>	
<p>▶ MENU SETTINGS</p> <p>▶ URL PATH SETTINGS</p> <p>▶ AUTHORIZING INFORMATION</p> <p>▶ PROMOTION OPTIONS</p>	



[Home](#)

Search



Tools

[Add content](#)

## About Us

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut nec massa nec mauris tincidunt ultricies. Sed vehicula eros ac egestas mollis. Duis rhoncus dui vitae sapien feugiat blandit. Cras convallis eget nulla vitae mattis. Ut nunc mi, efficitur eget purus nec, mattis semper lorem. Suspendisse varius, quam ac lobortis hendrerit, diam mauris porttitor risus, a convallis elit tortor sed turpis. Etiam aliquam, neque eu laoreet aliquam, massa eros tristique enim, eu pulvinar erat enim at nibh. Praesent bibendum purus sit amet turpis vestibulum congue.

<b>Submission form settings</b>	<b>Default options</b> <ul style="list-style-type: none"><li><input checked="" type="checkbox"/> Published</li><li><input type="checkbox"/> Promoted to front page</li><li><input type="checkbox"/> Sticky at top of lists</li><li><input checked="" type="checkbox"/> Create new revision</li></ul> <p>Users with the <i>Administer content</i> permission will be able to override these options.</p>
Title	
<b>Publishing options</b> Published , Create new revision	
<b>Display settings</b> Don't display post information	
<b>Menu settings</b>	

## Edit Basic page About Us ☆

[View](#)[Edit](#)[Delete](#)[Home](#) » [About Us](#)**Title \*****Body (Edit summary)**

**B** **I**      Format ▾  Source

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut nec massa nec mauris tincidunt ultricies. Sed vehicula eros ac egestas mollis. Duis rhoncus dui vitae sapien feugiat blandit. Cras convallis eget nulla vitae mattis. Ut nunc mi, efficitur eget purus nec, mattis semper lorem. Suspendisse varius, quam ac lobortis hendrerit, diam mauris porttitor risus, a convallis elit tortor sed turpis. Etiam aliquam, neque eu laoreet aliquam, massa eros tristique enim, eu pulvinar erat enim at nibh. Praesent bibendum purus sit amet turpis vestibulum congue.

Text format Basic HTML ▾ [About text formats ?](#)

**Published****Last saved:** 11/07/2016 - 14:01**Author:** admin Create new revision**Revision log message**

Briefly describe the changes you have made.

[▶ MENU SETTINGS](#)[▶ URL PATH SETTINGS](#)[▶ AUTHORING INFORMATION](#)[▶ PROMOTION OPTIONS](#)[Save and keep published ▾](#)[Preview](#)[Delete](#)

## About

[View](#)[Edit](#)[Delete](#)[Revisions](#)

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut nec massa nec mauris tincidunt ultricies. Sed vehicula eros ac egestas mollis. Duis rhoncus dui vitae sapien feugiat blandit. Cras convallis eget nulla vitae mattis. Ut nunc mi, efficitur eget purus nec, mattis semper lorem. Suspendisse varius, quam ac lobortis hendrerit, diam mauris porttitor risus, a convallis elit tortor sed turpis. Etiam aliquam, neque eu laoreet aliquam, massa eros tristique enim, eu pulvinar erat enim at nibh. Praesent bibendum purus sit amet turpis vestibulum congue.

## Revisions for *About* ☆

[View](#)[Edit](#)[Delete](#)[Revisions](#)

[Home](#) > [About Us](#)

Revisions allow you to track differences between multiple versions of your content, and revert to older versions.

REVISION	OPERATIONS
11/07/2016 - 14:49 by admin Changed title	<i>Current revision</i>
11/07/2016 - 14:01 by admin	<a href="#">Revert</a> ▼

Revisions allow you to track differences between multiple versions of your content, and revert to older versions.

REVISION	OPERATIONS
11/07/2016 - 14:01 by admin Copy of the revision from <i>Mon, 11/07/2016 - 14:01</i> .	<i>Current revision</i>
11/07/2016 - 14:49 by admin Changed title	<a href="#">Revert</a> ▼
11/07/2016 - 14:01 by admin	<a href="#">Revert</a> ▼

### Submission form settings

Title

### Publishing options

Published , Create new revision

### Display settings

Don't display post information

### Menu settings

- Display author and date information  
Author username and publish date will be displayed.

<b>Submission form settings</b>	<p><b>Available menus</b></p> <p><input type="checkbox"/> Administration</p> <p><input type="checkbox"/> Footer</p> <p><input checked="" type="checkbox"/> Main navigation</p> <p><input type="checkbox"/> Tools</p> <p><input type="checkbox"/> User account menu</p> <p>The menus available to place links in for this content type.</p> <p><b>Default parent item</b></p> <p>&lt;main&gt; ▼</p> <p>Choose the menu item to be the default parent for a new link in the content authoring form.</p>
<b>Publishing options</b>	
<b>Display settings</b>	
<b>Menu settings</b>	

**Edit Basic page About Us** ☆

Home » About Us

**Title \***

About Us

**Body (Edit summary)**

**B I** **Format** ▼ **Source**

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut nec massa nec mauris tincidunt ultricies. Sed vehicula eros ac egestas mollis. Duis rhoncus dui vitae sapien feugiat blandit. Cras convallis eget nulla vitae mattis. Ut nunc mi, efficitur eget purus nec, mattis semper lorem. Suspendisse varius, quam ac lobortis hendrerit, diam mauris porttitor risus, a convallis elit tortor sed turpis. Etiam aliquam, neque eu laoreet aliquam, massa eros tristique enim, eu pulvinar erat enim at nibh. Praesent bibendum purus sit amet turpis vestibulum congue.

Text format **Basic HTML** ▼ [About text formats](#) ?

**Published**

*Last saved: 11/07/2016 - 14:01*

Author: admin

Create new revision

**Revision log message**

Briefly describe the changes you have made.

---

**▼ MENU SETTINGS**

Provide a menu link

**Menu link title**

About Us

**Description**

Shown when hovering over the menu link.

**Parent item**

<Main navigation> ▼

**Weight**

0

Menu links with lower weights are displayed before links with higher weights.

## Manage fields ☆

[Edit](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Page](#)

[+ Add field](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Body	body	Text (formatted, long, with summary)	<a href="#">Edit</a> ▼

### Body settings for Basic page ☆

[Edit](#)[Field settings](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Page](#) » [Manage fields](#)

**Label \***

**Help text**

Instructions to present to the user below this field on the editing form.

Allowed HTML tags: <a> <b> <big> <code> <del> <em> <i> <ins> <pre> <q> <small> <span> <strong> <sub> <sup> <tt> <ol> <ul> <li> <p> <br> <img>  
This field supports tokens.

Required field

▼ DEFAULT VALUE

The default value for this field, used when creating new content.

Body ([Edit summary](#))

**B** *I* Normal - Source

body p

Text format: Basic HTML

[About text formats](#) ?

Summary input

This allows authors to input an explicit summary, to be displayed instead of the automatically trimmed text when using the "Summary or trimmed" display type.

[Save settings](#)[Delete](#)

## Body ☆

[Edit](#)[Field settings](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Page](#) » [Manage fields](#) » [Body](#)

✘ There is data for this field in the database. The field settings can no longer be changed.

These settings apply to the *Body* field everywhere it is used. These settings impact the way that data is stored in the database and cannot be changed once data has been created.

Allowed number of values: Limited ▼

[Save field settings](#)

## Add content type ☆

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#)

Individual content types can have different fields, behaviors, and permissions assigned to them.

### Name \*

Machine name: post [\[Edit\]](#)

The human-readable name of this content type. This text will be displayed as part of the list on the *Add content* page. This name must be unique.

### Description

This text will be displayed on the *Add new content* page.

<b>Submission form settings</b> Title	<b>Title field label *</b> <input type="text" value="Title"/>
<b>Publishing options</b> Published , Promoted to front page , Create new revision	<b>Preview before submitting</b> <input type="radio"/> Disabled <input checked="" type="radio"/> Optional <input type="radio"/> Required
<b>Display settings</b> Display author and date information	<b>Explanation or submission guidelines</b> <input type="text"/>
<b>Menu settings</b>	This text will be displayed at the top of the page when creating or editing content of this type.

<b>Submission form settings</b> Title	<b>Default options</b> <input checked="" type="checkbox"/> Published <input type="checkbox"/> Promoted to front page <input type="checkbox"/> Sticky at top of lists <input checked="" type="checkbox"/> Create new revision Users with the <i>Administer content</i> permission will be able to override these options.
<b>Publishing options</b> Published , Create new revision	
<b>Display settings</b> Display author and date information	
<b>Menu settings</b>	



<b>Submission form settings</b>	<input type="checkbox"/> Display author and date information Author username and publish date will be displayed.
Title	
<b>Publishing options</b>	
Published , Create new revision	
<b>Display settings</b>	
Don't display post information	
<b>Menu settings</b>	

<b>Submission form settings</b>	
Title	
<b>Publishing options</b>	
Published , Create new revision	
<b>Display settings</b>	
Don't display post information	
<b>Menu settings</b>	

**Available menus**

- Administration
- Footer
- Main navigation
- Tools
- User account menu

The menus available to place links in for this content type.

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Body	body	Text (formatted, long, with summary)	<div style="border: 1px solid #ccc; padding: 2px;"> <div style="border-bottom: 1px solid #ccc; padding: 2px;">Edit</div> <div style="border-bottom: 1px solid #ccc; padding: 2px;">Storage settings</div> <div style="padding: 2px;">Delete</div> </div>

**Add field** ☆

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#) » [Manage fields](#)

Add a new field Date or Re-use an existing field  
- Select an existing field -

**Label \***  
 Machine name: field\_published [Edit]

[Save and continue](#)

**Published** ☆

[Edit](#) [Field settings](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#) » [Manage fields](#) » [Published](#)

These settings apply to the *Published* field everywhere it is used. These settings impact the way that data is stored in the database and cannot be changed once data has been created.

**Date type**

Choose the type of date to create.

**Allowed number of values**

[Save field settings](#)

**Published settings for Post** ☆

[Edit](#) [Field settings](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#) » [Manage fields](#)

✓ Updated field *Published* field settings.

**Label** \*

**Help text**

Instructions to present to the user below this field on the editing form.  
 Allowed HTML tags: <a> <b> <big> <code> <del> <em> <i> <ins> <pre> <q> <small> <span> <strong> <sub> <sup> <tt> <ol> <ul> <li> <p> <br> <img>  
 This field supports tokens.

Required field

▼ **DEFAULT VALUE**  
 The default value for this field, used when creating new content.  
**Default date**  
  
 Set a default value for this date.

[Save settings](#) [Delete](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Author	field_author	Text (plain)	<a href="#">Edit</a> ▼
Content	field_content	Text (formatted, long)	<a href="#">Edit</a> ▼
Featured Image	field_featured_image	Image	<a href="#">Edit</a> ▼
Published	field_published	Date	<a href="#">Edit</a> ▼
Teaser	field_teaser	Text (plain, long)	<a href="#">Edit</a> ▼

## Taxonomy ☆

[Home](#) » [Administration](#) » [Structure](#)

Taxonomy is for categorizing content. Terms are grouped into vocabularies. For example, a vocabulary called "Fruit" would contain the terms "Apple" and "Banana".

[+ Add vocabulary](#)

VOCABULARY NAME	OPERATIONS
Tags	<a href="#">List terms</a> ▾

## Add vocabulary ☆

[Home](#) » [Administration](#) » [Structure](#) » [Taxonomy](#)

Name \*

Machine name: category [\[Edit\]](#)

Description

[Save](#)

## Category ☆

[List](#)

[Edit](#)

[Manage fields](#)

[Manage form display](#)

[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Taxonomy](#) » [Category](#)

✓ Created new vocabulary *Category*.

You can reorganize the terms in *Category* using their drag-and-drop handles, and group terms under a parent term by sliding them under and to the right of the parent.

[+ Add term](#)

[Show row weights](#)

NAME	WEIGHT	OPERATIONS
No terms available. <a href="#">Add term</a> .		

## Add term ☆

[Home](#) » [Administration](#) » [Structure](#) » [Taxonomy](#) » [Category](#)

### Name \*

The term name.

### Description

**B** *I*     Format -  Source

**Text format** Basic HTML ▾ [About text formats ?](#)

A description of the term.

### ▶ RELATIONS

### URL alias

Specify an alternative path by which this data can be accessed. For example, type "/about" when writing an about page.

[Save](#)

[Show row weights](#)

NAME	OPERATIONS
<a href="#">+ Camping</a>	<a href="#">Edit</a> ▾
<a href="#">+ Outdoors</a>	<a href="#">Edit</a> ▾
<a href="#">+ Rock climbing</a>	<a href="#">Edit</a> ▾

[Save](#) [Reset to alphabetical](#)

## Comment types ☆

[Home](#) » [Administration](#) » [Structure](#)

This page provides a list of all comment types on the site and allows you to manage the fields, form and display settings for each.

[+ Add comment type](#)

COMMENT TYPE	DESCRIPTION	OPERATIONS
Default comments	Allows commenting on content	<a href="#">Manage fields</a> ▾

## Add comment type ☆

[Home](#) » [Administration](#) » [Structure](#) » [Comment types](#)

**Label \***

Machine name: `post_comment_type` [\[Edit\]](#)

**Description**

Describe this comment type. The text will be displayed on the *Comment types* administration overview page.

**Target entity type**

The target entity type can not be changed after the comment type has been created.

[Save](#)

## Post Comments settings for Post ☆

[Edit](#)[Field settings](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#) » [Manage fields](#)

✓ Updated field *Post Comments* field settings.

### Label \*

### Help text

Instructions to present to the user below this field on the editing form.

Allowed HTML tags: <a> <b> <big> <code> <del> <em> <i> <ins> <pre> <q> <small> <span> <strong> <sub> <sup> <tt> <ol> <ul> <li> <p> <br> <img>

This field supports tokens.

Required field

### ▼ DEFAULT VALUE

The default value for this field, used when creating new content.

- Open  
Users with the "Post comments" permission can post comments.
- Closed  
Users cannot post comments, but existing comments will be displayed.
- Hidden  
Comments are hidden from view.

Threading

Show comment replies in a threaded list.

### Comments per page \*

Show reply form on the same page as comments

### Preview comment

- Disabled
- Optional
- Required

## Create Post ☆

[Home](#) » [Add content](#)

**Title \***











**Published**

11/14/2016

**Author**

**Teaser**

**Content**

**B** **I**           

Text format: Basic HTML ▾ [About text formats](#) ?

**Featured Image**

No file chosen

One file only.

32 MB limit.

Allowed types: png gif jpg jpeg.

[Show row weights](#)

**CATEGORY**

*Last saved: Not saved yet*

Author: admin

Create new revision

**Revision log message**

Briefly describe the changes you have made.

► **COMMENT SETTINGS**

► **URL PATH SETTINGS**

► **AUTHORING INFORMATION**

► **PROMOTION OPTIONS**

## Manage form display ☆

[Edit](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#)

Content items can be edited using different form modes. Here, you can define which fields are shown and hidden when *Post* content is edited in each form mode, and define how the field form widgets are displayed in each form mode.

[Show row weights](#)

FIELD	WIDGET		
✚ Title	<input type="text" value="Textfield"/>	Textfield size: 60	⚙
✚ Authored by	<input type="text" value="Autocomplete"/>	Autocomplete matching: Contains Textfield size: 60 No placeholder	⚙
✚ Authored on	<input type="text" value="Datetime Timestamp"/>		
✚ Promoted to front page	<input type="text" value="Single on/off checkbox"/>	Use field label: Yes	⚙
✚ Sticky at top of lists	<input type="text" value="Single on/off checkbox"/>	Use field label: Yes	⚙

[Show row weights](#)

CATEGORY
✚ <input type="text"/>

[Add another item](#)

### Category

- Camping
- Outdoors
- Rock climbing

### Disabled

✚ Promoted to front page	<input type="text" value="- Hidden -"/>
✚ Sticky at top of lists	<input type="text" value="- Hidden -"/>



## Post One

[View](#) [Edit](#) [Delete](#)

### Published

Sun, 03/19/2017 - 12:00 pm



### Author

Chaz Chumley

### Teaser

Life is great when you can enjoy the great outdoors.

### Content

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

### Featured Image



Category

[Camping](#)

```
⇒ drupal create:vocabularies
// Welcome to the Drupal vocabularies creator
Enter how many vocabularies would you like to create [25]:
> 1
Enter the maximum number of words in vocabulary names [5]:
> 5
-----
Vocabulary Id  Name
-----
m9510fna      Blandit Ideo Jumentum Rusticus Virtus
-----
[OK] Created "1" vocabularies successfully
```

```
⇒ drupal create:comments

// Welcome to the Drupal comments generator

Node ID where the comments will be created:
> 2

Enter how many comments would you like to generate [25]:
> 5

Enter the maximum number of words in titles [5]:
> 5

How far back in time should the comments be dated?:
[0] N | Now
[1] H | 1 hour ago
[2] D | 1 day ago
[3] W | 1 week ago
[4] M | 1 month ago
[5] Y | 1 year ago
> 1

-----
Node Id  Comment Id  Title                               Created Time
-----
2        1           Aliquam                             2017-03-05 05:40:45
2        2           Caecus Capto Pala Sudo              2017-03-05 06:10:58
2        3           Consequat Utinam Vereor            2017-03-05 06:15:15
2        4           Acsi                                 2017-03-05 05:38:44
2        5           Elit Patria Ratis                   2017-03-05 06:11:32
-----

[OK] Created "5" comments successfully
```

```
⇒ drupal create:nodes

// Welcome to the Drupal nodes generator

Select content type(s) to be used on node creation:
[0] Article
[1] Basic page
[2] Post
> 2

Enter how many nodes would you like to generate [25]:
> 5

Enter the maximum number of words in titles [5]:
> 5

How far back in time should the nodes be dated?:
[0] N | Now
[1] H | 1 hour ago
[2] D | 1 day ago
[3] W | 1 week ago
[4] M | 1 month ago
[5] Y | 1 year ago
> 1

-----
Node Id  Content type  Title                               Created Time
-----
3        Post         Decet Jumentum                     2017-03-05 06:17:55
4        Post         Eros Hendrerit Iriure Iustum       2017-03-05 06:09:27
5        Post         Esca                                2017-03-05 05:59:15
6        Post         Lobortis Minim Vel                 2017-03-05 06:17:38
7        Post         Commodo Qui                         2017-03-05 06:10:28
-----

[OK] Created "5" nodes successfully
```

# Chapter 5: Working with Blocks

**Block layout** ☆

Block layout | Custom block library

Bartik | Seven

[Home](#) » [Administration](#) » [Structure](#)

Block placement is specific to each theme on your site. Changes will not be saved until you click *Save blocks* at the bottom of the page.

[Demonstrate block regions \(Bartik\)](#)

[Show row weights](#)

BLOCK	CATEGORY	REGION	OPERATIONS
<b>Header</b> <a href="#">Place block</a>			
✚ Site branding	System	Header	<a href="#">Configure</a>
<b>Primary menu</b> <a href="#">Place block</a>			
✚ Main navigation	Menus	Primary menu	<a href="#">Configure</a>

Exit block region demonstration

Secondary menu

Header

Primary menu

Highlighted

Featured top

Breadcrumb

Sidebar first | Content | Sidebar second

**Sidebar second** [Place block](#)

✚ Powered by Drupal	System	Sidebar second	<a href="#">Configure</a>
---------------------	--------	----------------	---------------------------

## Configure block ☆

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#)

The *Powered by Drupal* block is an optional link to the home page of the Drupal project. While there is absolutely no requirement that sites feature this link, it may be used to show support for Drupal.

**Block description:** Powered by Drupal

**Title \***

Machine name: poweredbydrupal

Display title

**Visibility**

<b>Content types</b> Not restricted	<b>Content types</b> <input type="checkbox"/> Article <input type="checkbox"/> Basic page <input type="checkbox"/> Post
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	

**Region**

Select the region where this block should be displayed.

[Save block](#)

[Delete](#)



**Visibility**

<b>Content types</b> Not restricted	<b>Content types</b> <input type="checkbox"/> Article <input type="checkbox"/> Basic page <input type="checkbox"/> Post
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	



[Home](#)

Search



Tools

[Add content](#)

## About Us

View

Edit

Delete

Revisions

Nulla porttitor accumsan tincidunt. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Donec velit neque, auctor sit amet aliquam vel, ullamcorper sit amet ligula. Curabitur non nulla sit amet nisl tempus convallis quis ac lectus. Vivamus suscipit tortor eget felis porttitor volutpat. Curabitur arcu erat, accumsan id imperdiet et, porttitor at sem. Cras ultricies ligula sed magna dictum porta. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed porttitor lectus nibh. Donec rutrum congue leo eget malesuada. Curabitur aliquet quam id dui posuere blandit.

Powered by [Drupal 8](#)

Powered by [Drupal](#)

### Visibility

<p><b>Content types</b> Article, Post</p>	<p><b>Content types</b></p> <p><input checked="" type="checkbox"/> Article</p> <p><input type="checkbox"/> Basic page</p> <p><input checked="" type="checkbox"/> Post</p>
<p><b>Pages</b> Not restricted</p>	
<p><b>Roles</b> Not restricted</p>	

### Visibility

<p><b>Content types</b> Not restricted</p>	<p><b>Pages</b></p> <div style="border: 1px solid #ccc; height: 40px; width: 100%;"></div> <p>Specify pages by using their paths. Enter one path per line. The '*' character is a wildcard. An example path is <code>/user/*</code> for every user page. <code>&lt;front&gt;</code> is the front page.</p> <p><input checked="" type="radio"/> Show for the listed pages</p> <p><input type="radio"/> Hide for the listed pages</p>
<p><b>Pages</b> Not restricted</p>	
<p><b>Roles</b> Not restricted</p>	

### Visibility

<b>Content types</b> Article, Post	<b>Pages</b> <input type="text" value="&lt;front&gt;"/>  Specify pages by using their paths. Enter one path per line. The '*' character is a wildcard. An example path is <code>/user/*</code> for every user page. <code>&lt;front&gt;</code> is the front page.  <input type="radio"/> Show for the listed pages <input checked="" type="radio"/> Hide for the listed pages
<b>Pages</b> Restricted to certain pages	
<b>Roles</b> Not restricted	

### Visibility

<b>Content types</b> Not restricted	<b>When the user has the following roles</b> <input type="checkbox"/> Anonymous user <input type="checkbox"/> Authenticated user <input type="checkbox"/> Administrator
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	

### Add custom block ☆

[Home](#)

#### Block description \*

A brief description of your block.

#### Body

**B** **I**       Format -  Source

Text format Basic HTML

[About text formats](#) ?

#### Revision information

New revision

Create new revision

#### Revision log message

Briefly describe the changes you have made.

[Save](#)

## Configure block ☆

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Configure block](#)

✓ Basic block *Our custom block* has been created.

**Block description:** Our custom block

**Title \***

Our custom block

Machine name: ourcustomblock [\[Edit\]](#)

Display title

**Visibility**

<b>Content types</b> Not restricted	<b>Content types</b> <input type="checkbox"/> Article <input type="checkbox"/> Basic page <input type="checkbox"/> Post
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	

**Region**

- None -

Select the region where this block should be displayed.

[Save block](#)

## Custom block library ☆

[Block layout](#)

[Custom block library](#)

[Blocks](#)

[Block types](#)

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#)

Blocks in the block library belong to *Custom block types*, each with its own fields and display settings. After creating a block, place it in a region from the [Block layout](#) page.

[+ Add custom block](#)

**Block description**

**Block type**

- Any -

[Apply](#)

BLOCK DESCRIPTION	BLOCK TYPE	UPDATED	OPERATIONS
<a href="#">Our custom block</a>	Basic block	01/21/2017 – 21:03	<a href="#">Edit</a>

## Edit custom block *Our custom block* ☆

Edit

Delete






[Home](#)

### Block description \*

Our custom block

A brief description of your block.

### Body

**B I**     Format -  Source

This is some basic content

Text format Basic HTML [About text formats ?](#)

### Revision information

No revision

Create new revision

#### Revision log message

Briefly describe the changes you have made.

Save

Delete

## Custom block library ☆

Block layout

Custom block library

Blocks

Block types

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » Custom block library

Each block type has its own fields and display settings. Create blocks of each type on the [Blocks](#) page in the custom block library.

[+ Add custom block type](#)

BLOCK TYPE	DESCRIPTION	OPERATIONS
Basic block	A basic block contains a title and a body.	<a href="#">Manage fields</a>



## Manage fields ☆

[Edit](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Custom block library](#) » [Basic](#)

[+ Add field](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Body	body	Text (formatted, long, with summary)	<a href="#">Edit</a> ▾

## Add field ☆

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Custom block library](#) » [Basic](#) » [Manage fields](#)

Add a new field

Label \*

 Machine name: `field_featured_image` [\[Edit\]](#)[Save and continue](#)

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Body	body	Text (formatted, long, with summary)	<a href="#">Edit</a> ▾
Featured Image	field_featured_image	Image	<a href="#">Edit</a> ▾

## Manage form display ☆

[Edit](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Custom block library](#) » [Basic](#)

[Show row weights](#)

FIELD	WIDGET		
✚ Block description	Textfield ▾	Textfield size: 60	⚙
✚ Body	Text area with a summary ▾	Number of rows: 9 Number of summary rows: 3	⚙
✚ Featured Image	Image ▾	Preview image style: Thumbnail (100×100) Progress indicator: throbber	⚙
✚ Headline	Textfield ▾	Textfield size: 60	⚙
<b>Disabled</b>			
<i>No field is hidden.</i>			

[Save](#)

⚠ \* You have unsaved changes.

FIELD	WIDGET		
✚ Block description	Textfield ▾	Textfield size: 60	⚙
✚ Headline*	Textfield ▾	Textfield size: 60	⚙
✚ Featured Image*	Image ▾	Preview image style: Thumbnail (100×100) Progress indicator: throbber	⚙
✚ Body	Text area with a summary ▾	Number of rows: 9 Number of summary rows: 3	⚙
<b>Disabled</b>			
<i>No field is hidden.</i>			

[Save](#)

**Block description \***

A brief description of your block.

**Headline**

**Featured Image**

No file chosen

One file only.

32 MB limit.

Allowed types: png gif jpg jpeg.

**Body**

**B** *I* Format - Source

⊕ **Headline**

Widget settings: **Textfield**

**Size of textfield \***

**Placeholder**

Text that will be shown inside the field until a value is entered. This hint is usually a sample value or a brief description of the expected format.

## Add custom block ☆

[Home](#)

**Block description \***

A brief description of your block.

**Headline**

## Manage display ☆

[Edit](#)[Manage fields](#)[Manage form display](#)[Manage display](#)

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Custom block library](#) » [Basic](#)

[Show row weights](#)

FIELD	LABEL	FORMAT		
✚ Body	<input type="text" value="- Hidden -"/>	<input type="text" value="Default"/>		
✚ Featured Image	<input type="text" value="Above"/>	<input type="text" value="Image"/>	Original image	⚙
✚ Headline	<input type="text" value="Above"/>	<input type="text" value="Plain text"/>		⚙

### Disabled

*No field is hidden.*

▶ CUSTOM DISPLAY SETTINGS

Save

FIELD	LABEL	FORMAT		
✚ Headline	<input type="text" value="Above"/>	<input type="text" value="Plain text"/>		⚙
✚ Featured Image	<input type="text" value="Above"/>	<input type="text" value="Image"/>	Original image	⚙
✚ Body	<input type="text" value="- Hidden -"/>	<input type="text" value="Default"/>		

## Edit custom block *Our custom block* ☆

Edit

Delete

[Home](#)

### Block description \*

Our custom block

A brief description of your block.

### Headline

Forum One

### Featured Image



### Alternative text \*








Forum One

This text will be used by screen readers, search engines, or when the image cannot be loaded.

 f1logo.png (30.9 KB)

Remove

### Body

**B** *I*       Normal -  Source

Helping you make an impact so that you can focus on changing the world.



## Mastering Drupal 8

[About Us](#)

[Home](#)

Search



Tools

[Add content](#)

Dignissim

[Read more](#)



Our custom block

Forum One



Helping you make an impact so that you can focus on changing the world.

## Extend ☆

List

Update

Uninstall

[Home](#) » [Administration](#)

Download additional [contributed modules](#) to extend your site's functionality.

Regularly review and install [available updates](#) to maintain a secure and current site. Always run the [update script](#) each time a module is updated.

[+ Install new module](#)

Filter by name or description

Enter a part of the module name or description



▼ **CORE**

**Actions** ▶ Perform tasks on specific events triggered within the system.

**Activity Tracker** ▶ Enables tracking of recent content for users.

The screenshot shows the top of the Drupal 8 administration interface. At the top, there is a dark navigation bar with a hamburger menu icon, the text 'Manage', a star icon for 'Shortcuts', a user icon for 'admin', and icons for 'Place block' and 'Edit'. Below this is a secondary navigation bar with icons and labels for 'Content', 'Structure', 'Appearance', 'Extend', 'Configuration', 'People', 'Reports', and 'Help'. In the top right corner of this bar are 'My account' and 'Log out' links. Below the navigation bars is a blue banner with the Drupal logo and the text 'Mastering Drupal 8'.

The screenshot shows a page layout with a blue header. The header contains a hamburger menu icon, a star icon, and the text 'Mastering Drupal 8'. In the top right corner of the header are 'My account' and 'Log out' links. Below the header are several grey content blocks, each with a dashed border and a plus sign icon in the center, indicating they are placeholders for content.



✓ The block configuration has been saved.




Block placement is specific to each theme on your site. Changes will not be saved until you click *Save blocks* at the bottom of the page.

[Demonstrate block regions \(Bartik\)](#)

[Show row weights](#)

BLOCK	CATEGORY	REGION	OPERATIONS
Header			Place block
✚ Search form	Forms	Header	Configure
✚ Site branding	System	Header	Configure

# Chapter 6: Content Authoring, HTML5, and Media












## Create Basic page ☆

[Home](#) > [Add content](#)

Title \*

Body (Edit summary)

**B** *I*       Format -  Source

Text format [About text formats](#) ?  
Basic HTML

*Last saved: Not saved yet*

Author: admin

Create new revision

Revision log message

Briefly describe the changes you have made.

▶ MENU SETTINGS

▶ URL PATH SETTINGS








▶ AUTHORING INFORMATION

▶ PROMOTION OPTIONS

Save and publish

Preview

Body (Edit summary)

**B** *I*       Format -  Source

Text format Basic HTML [About text formats](#) ?

## Text formats and editors ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Content authoring](#)

Text formats define how text is filtered for output and how HTML tags and other text is displayed, replaced, or removed. **Improper text format configuration is a security risk.** Learn more on the [Filter module help page](#).

Text formats are presented on content editing pages in the order defined on this page. The first format available to a user will be selected by default.

[+ Add text format](#)

[Show row weights](#)

NAME	TEXT EDITOR	ROLES	OPERATIONS
+ Basic HTML	CKEditor	Authenticated user,Administrator	<a href="#">Configure</a> ▾
+ Restricted HTML	—	Anonymous user,Administrator	<a href="#">Configure</a> ▾
+ Full HTML	CKEditor	Administrator	<a href="#">Configure</a> ▾
+ Plain text	—	<i>This format is shown when no other formats are available</i>	<a href="#">Configure</a>

[Save](#)

## Basic HTML ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Content authoring](#) » [Text formats and editors](#)

A text format contains filters that change the display of user input; for example, stripping out malicious HTML or making URLs clickable. Filters are executed from top to bottom and the order is important, since one filter may prevent another filter from doing its job. For example, when URLs are converted into links before disallowed HTML tags are removed, all links may be removed. When this happens, the order of filters may need to be rearranged.

**Name \***

Basic HTML

Machine name: basic\_html

**Roles**

- Anonymous user
- Authenticated user
- Administrator

**Text editor**

CKEditor ▾

### TOOLBAR CONFIGURATION


Move a button into the *Active toolbar* to enable it, or into the list of *Available buttons* to disable it. Buttons may be moved with the mouse or keyboard arrow keys. Toolbar group names are provided to support screen reader users. Empty toolbar groups will be removed upon save.

**Available buttons**



**Button divider**

**Active toolbar**



[Show group names](#)

## CKEditor plugin settings

<b>Image</b> Uploads enabled, max size: 32 MB	<input checked="" type="checkbox"/> Enable image uploads
	<b>Upload directory</b> <input type="text" value="inline-images"/> A directory relative to Drupal's files directory where uploaded images will be stored.
	<b>Maximum file size</b> <input type="text" value="32 MB"/> If this is left empty, then the file size will be limited by the PHP maximum upload size of 32 MB.
	<b>Maximum dimensions</b> <input type="text" value="width"/> x <input type="text" value="height"/> pixels Images larger than these dimensions will be scaled down.

### Enabled filters

- Limit allowed HTML tags and correct faulty HTML
- Display any HTML as plain text
- Convert line breaks into HTML (i.e. `<br>` and `<p>`)
- Convert URLs into links
- Align images  
Uses a `data-align` attribute on `<img>` tags to align images.
- Caption images  
Uses a `data-caption` attribute on `<img>` tags to caption images.
- Restrict images to this site  
Disallows usage of `<img>` tag sources that are not hosted on this site by replacing them with a placeholder image.
- Correct faulty and chopped off HTML
- Track images uploaded via a Text Editor  
Ensures that the latest versions of images uploaded via a Text Editor are displayed.

### Filter processing order

[Show row weights](#)

- + Limit allowed HTML tags and correct faulty HTML

---

- + Align images

---

- + Caption images

---

- + Restrict images to this site

---

- + Track images uploaded via a Text Editor

---

## Filter settings

### Limit allowed HTML tags and correct faulty HTML

Enabled

#### Allowed HTML tags

`<a href hreflang> <em> <strong> <cite> <blockquote cite> <code> <ul type> <ol start type> <`

A list of HTML tags that can be used. By default only the *lang* and *dir* attributes are allowed for all HTML tags. Each HTML tag may have attributes which are treated as allowed attribute names for that HTML tag. Each attribute may allow all values, or only allow specific values. Attribute names or values may be written as a prefix and wildcard like *jump-\**. JavaScript event attributes, JavaScript URLs, and CSS are always stripped.

- Display basic HTML help in long filter tips
- Add rel="nofollow" to all links


The screenshot shows a CMS interface for creating a basic page. The main area is titled "Create Basic page" and includes a breadcrumb "Home » Add content". The "Title" field contains "Contact Us". The "Body" section has a rich text editor with a toolbar showing bold, italic, link, unlink, list, and image icons. A "Text format" dropdown is set to "Basic HTML". A "Save and publish" button is at the bottom left. An "Insert Image" dialog box is open in the foreground, featuring a "Choose File" button, an "Alternative text" field with the placeholder "Short description for the visually impaired", radio buttons for alignment (None, Left, Center, Right), a "Caption" checkbox, and a "Save" button. On the right side of the page, a sidebar shows "Last saved: Not saved yet", "Author: admin", a checked "Create new revision" option, and a "Revision log message" field.

Title \*

Contact Us

Body (Edit summary)

**B** *I* Normal - Source



body p image

Text format Basic HTML ▾ [About text formats ?](#)

Edit Image ✕

Image \*  
 [va.jpg](#) Remove

Alternative text \*

Align  
 None:  Left:  Center:  Right:

Caption

Save

Edit Image ✕

Image \*  
 [va.jpg](#) Remove







Alternative text \*


Align  
 None:  Left:  Center:  Right:

Caption

Save

Body (Edit summary)



**B** *I*       Format - Source



*Enter caption here*

Forum One is a **full-service digital agency** that works with **mission-driven organizations** to **extend their influence**.

body image

Text format Basic HTML  [About text formats](#) 

## My Basic Page

- [View](#) [Edit](#) [Delete](#) [Revisions](#)



Forum One - 2200 Mount Vernon Ave. Alexandria, VA

Forum One is a **full-service digital agency** that works with **mission-driven organizations** to **extend their influence**.

## Post One

View

Edit

Delete

---

### Published

Sun, 03/19/2017 - 12:00 pm

### Author

Chaz Chumley

### Teaser

Life is great when you can enjoy the great outdoors.

### Content

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

### Featured Image



## Manage display ☆

[Edit](#) [Manage fields](#) [Manage form display](#) [Manage display](#)

[Default](#) [Teaser](#)

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#)

Content items can be displayed using different view modes: Teaser, Full content, Print, RSS, etc. *Teaser* is a short format that is typically used in lists of multiple content items. *Full content* is typically used when the content is displayed on its own page.

Here, you can define which fields are shown and hidden when *Post* content is displayed in each view mode, and define how the fields are displayed in each view mode.

[Show row weights](#)

FIELD	LABEL	FORMAT		
+ Links		Visible		
+ Published	Above	Default	Format: Sun, 03/19/2017 - 09:06 pm	⚙
+ Author	Above	Plain text		⚙
+ Teaser	Above	Plain text		
+ Content	Above	Default		
+ Featured Image	Above	Image	Original image	⚙
+ Category	Above	Label	Link to the referenced entity	⚙
+ Post Comments	Above	Comment list	Comment view mode: Default	⚙
<b>Disabled</b>				
<i>No field is hidden.</i>				

FIELD	LABEL	FORMAT		
+ Featured Image	Above	Image	Original image	⚙
+ Author	Above	Plain text		⚙
+ Published	Above	Default	Format: Sun, 03/19/2017 - 09:23 pm	⚙
+ Category	Above	Label	Link to the referenced entity	⚙
+ Content	Above	Default		
<b>Disabled</b>				
+ Post Comments	Above	- Hidden -		
+ Teaser	Above	- Hidden -		
+ Links		- Hidden -		



# Post One

## Featured Image



## Author

Chaz Chumley

## Published

Sun, 03/19/2017 - 12:00 pm

Category

[Camping](#)

## Content

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

FIELD	LABEL	FORMAT		
⊕ Featured Image	- Hidden -	Image	Original image	⚙
⊕ Author	Inline	Plain text		⚙
⊕ Published	Inline	Default	Format: Sun, 03/19/2017 - 09:27 pm	⚙
⊕ Category	Inline	Label	Link to the referenced entity	⚙
⊕ Content	- Hidden -	Default		

## Post One



**Author:** Chaz Chumley

**Published:** Sun, 03/19/2017 - 12:00 pm

Category: [Camping](#)

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

+ Published

Inline

Format settings: **Default**

**Time zone override**

- None selected -

The time zone selected here will always be used

**Date format**

Default long date (Sunday, March 19, 2017 - 09:41 pm)

Choose a format for displaying the date. Be sure to set a format appropriate for the field, i.e. omitting time for a field that only has a date.

Update

Cancel

[Home](#) » [Administration](#) » [Structure](#) » [Content types](#) » [Post](#) » [Manage display](#)

Content items can be displayed using different view modes: Teaser, Full content, Print, RSS, etc. *Teaser* is a short format that is typically used in lists of multiple content items. *Full content* is typically used when the content is displayed on its own page.

Here, you can define which fields are shown and hidden when *Post* content is displayed in each view mode, and define how the fields are displayed in each view mode.

[Show row weights](#)

FIELD	LABEL	FORMAT		
+ Featured Image	- Hidden -	Image	Original image	⚙
+ Author	Inline	Plain text		⚙
+ Teaser	- Hidden -	Plain text		

[Back to content editing](#)
View mode: Teaser

## Mastering Drupal 8

About Us
Home

[Home](#)

Search


Q

Tools

[Add content](#)

## Post One

Post One



**Author:** Chaz Chumley  
Life is great when you can enjoy the great outdoors.

### ▼ **CUSTOM DISPLAY SETTINGS**

Use custom display settings for the following view modes

- Full content
- RSS
- Search index
- Search result highlighting input
- Teaser

[Manage view modes](#)

## View modes ☆

[Home](#) » [Administration](#) » [Structure](#) » [Display modes](#)

[+ Add view mode](#)

### Content

NAME	OPERATIONS
Full content	<a href="#">Edit</a> ▼
RSS	<a href="#">Edit</a> ▼
Search index	<a href="#">Edit</a> ▼
Search result highlighting input	<a href="#">Edit</a> ▼
Teaser	<a href="#">Edit</a> ▼

[Add new Content view mode](#)

## Choose view mode entity type ☆

[Home](#) » [Administration](#) » [Structure](#) » [Display modes](#) » [View modes](#)

- › [Custom block](#)
- › [Comment](#)
- › [Contact message](#)
- › [Content](#)
- › [Taxonomy term](#)
- › [User](#)

## Add new *Content* view mode ☆

[Home](#) » [Administration](#) » [Structure](#) » [Display modes](#) » [View modes](#) » [Choose view mode entity type](#)

Name

Machine name: node.card [\[Edit\]](#)

Save

### ▼ CUSTOM DISPLAY SETTINGS

Use custom display settings for the following view modes

- Card
- Full content
- RSS
- Search index
- Search result highlighting input
- Teaser

[Manage view modes](#)

+ Featured Image

- Hidden - ▼

Image ▼

Original image

+ Featured Image - Hidden - ▼

Format settings: Image

Image style  
Medium (220x220) ▼  
[Configure Image Styles](#)

Link image to  
Nothing ▼

Update Cancel

### Post One



**Author:** Chaz Chumley

Life is great when you can enjoy the great outdoors.

## Image styles ☆



[Home](#) » [Administration](#) » [Configuration](#) » [Media](#)

Image styles commonly provide thumbnail sizes by scaling and cropping images, but can also add various effects before an image is displayed. When an image is displayed with a style, a new file is created and the original image is left unchanged.

[+ Add image style](#)

STYLE NAME	OPERATIONS
Large (480×480)	<a href="#">Edit</a> ▾
Medium (220×220)	<a href="#">Edit</a> ▾
Thumbnail (100×100)	<a href="#">Edit</a> ▾

### Preview



### Image style name \*

Large (480×480) Machine name: large [\[Edit\]](#)

[Show row weights](#)

EFFECT	OPERATIONS
<a href="#">+</a> Scale 480×480	<a href="#">Edit</a> ▾
<a href="#">+</a> <input type="text" value="Select a new effect"/>	<a href="#">Add</a>

[Update style](#) [Delete](#)

## Add image style ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Media](#) » [Image styles](#)

### Image style name \*

Black and White Machine name: black\_and\_white [\[Edit\]](#)

[Create new style](#)

EFFECT

OPERATIONS

+ Desaturate Add

Preview

original (view actual size)



600px

800px

Black and White (view actual size)



600px

800px

Image style name \*

Black and White

Machine name: black\_and\_white [Edit]

Show row weights

EFFECT

OPERATIONS

+ Desaturate

Delete

+ Select a new effect

Add

Update style

Delete

## Post One

View

Edit

Delete



Quick edit  
Edit  
Delete

**Author:** Chaz Chumley

**Published:** Sunday, March 19, 2017 - 12:00 pm

Category: [Camping](#)

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

 Title → Post One ✕

## Post One

[View](#) [Edit](#) [Delete](#) [Revisions](#)



**Author:** Chaz Chumley

**Published:** Sunday, March 19, 2017 - 12:00 pm

**Category:** [Camping](#)

Life is great when you can enjoy the great outdoors. Including a fresh stream and the warm sunshine.

 Title → Post One [Save](#) ✕

## Camping in the Wilderness



# Chapter 7: Understanding Views

Home Management Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

### Add new view ☆

Home » Administration » Structure » Views

**VIEW BASIC INFORMATION**

View name \*

Description

**VIEW**

Show  Content  Log entries  Files  Content revisions  Taxonomy terms  Users  Custom block revisions  Access Token  Custom block

of type: All tagged with:  sorted by: Unsorted

**PAGE**

Create

Back to site Management Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

### Add new view ☆

Home » Administration » Structure » Views

**VIEW BASIC INFORMATION**

View name \*  
 Machine name: articles (Edit)

Description

**VIEW SETTINGS**

Show: Content of type: Article tagged with:  sorted by: Newest first

### articles (Content) ☆

Edit | Devel

Home » Administration » Structure » Views

✓ The view *articles* has been saved.

#### Displays

Master + Add Edit view name/description

<b>TITLE</b> Title: None	Access: <a href="#">Permission</a>   <a href="#">View published content</a>	<b>ADVANCED</b>
<b>FORMAT</b> Format: <a href="#">Unformatted list</a>   <a href="#">Settings</a> Show: <a href="#">Fields</a>   <a href="#">Settings</a>	<b>HEADER</b> <span>Add</span>	
<b>FIELDS</b> <span>Add</span>	<b>FOOTER</b> <span>Add</span>	
Content: <a href="#">Title</a>	<b>NO RESULTS BEHAVIOR</b> <span>Add</span>	
<b>FILTER CRITERIA</b> <span>Add</span>	<b>PAGER</b> Use pager: <a href="#">Full</a>   <a href="#">Paged, 10 items</a> More link: <a href="#">No</a>	
Content: <a href="#">Publishing status (= Yes)</a>	Link display: <a href="#">None</a>	
<b>SORT CRITERIA</b> <span>Add</span>	<b>LANGUAGE</b> Rendering Language: <a href="#">Content language of view row</a>	
Content: <a href="#">Type (= Article)</a>		
Content: <a href="#">Authored on (desc)</a>		

Save Cancel

#### Preview

✓ Auto preview

Preview with contextual filters:  Update preview

Separate contextual filter values with a "/". For example, 40/12/10.

```
Query
SELECT node_field_data.langcode AS node_field_data_langcode, node_field_data.created AS node_field_data_created, node_field_data.nid AS nid
FROM
(node_field_data) node_field_data
WHERE (( (node_field_data.status = '1') AND (node_field_data.type IN ('article')) ))
ORDER BY node_field_data_created DESC
LIMIT 10 OFFSET 0

Title
Path          This display has no path.
Query build time  36.67 ms
Query execute time 7.49 ms
View render time  142.81 ms
```

Title

Content

Test

Pager

# Views settings

List

Settings

Basic

Advanced

[Home](#) » [Administration](#) » [Structure](#) » [Views](#)

- Always show the master (default) display
- Always show advanced display settings
- Allow embedded displays

Embedded displays can be used in code via `views_embed_view()`.

Label for "Any" value on non-required single-select exposed filters

<Any> ▾

## ▼ LIVE PREVIEW SETTINGS

- Automatically update preview on changes
- Show information and statistics about the view during live preview
- Show the SQL query

Show SQL query

- Above the preview
- Below the preview

Home Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Views settings ☆

List Settings

Basic

Advanced

[Home](#) » [Administration](#) » [Structure](#) » [Views](#)

- Always show the master (default) display
- Always show advanced display settings
- Allow embedded displays

Embedded displays can be used in code via `views_embed_view()`.

Back to site | Manage | Shortcuts | admin | Tour

Content | Structure | Appearance | Extend | Configuration | People | Reports | Help

## articles (Content) ☆

Home » Administration » Structure » Views » Articles » Edit

⚠ You have unsaved changes.

### Displays

Page\* [+ Add](#) Edit view name/description Duplicate Page

Display name: Page

<b>TITLE</b> Title: None	<b>PAGE SETTINGS</b> Path: No path is set Menu: No menu Access: Permission   View published content	<b>▶ ADVANCED</b>
<b>FORMAT</b> Format: Unformatted list   Settings Show: Fields   Settings	<b>HEADER</b> <a href="#">Add</a>	
<b>FIELDS</b> <a href="#">Add</a> Content: Title	<b>FOOTER</b> <a href="#">Add</a>	
<b>FILTER CRITERIA</b> <a href="#">Add</a> Content: Publishing status (= Yes) Content: Type (= Article)	<b>NO RESULTS BEHAVIOR</b> <a href="#">Add</a>	
<b>SORT CRITERIA</b> <a href="#">Add</a> Content: Authored on (desc)	<b>PAGER</b> Use pager: Full   Paged, 10 items More link: No	
<b>LANGUAGE</b> Rendering Language: Content language of view row		

[Save](#) [Cancel](#)

### Page: The menu path or URL of this view

**Path**

This view will be displayed by visiting this path on your site. You may use "%" in your URL to represent values that will be used for contextual filters: For example, "node%/feed". If needed you can even specify named route parameters like taxonomy/term/%taxonomy\_term

[Apply](#) [Cancel](#)

### Page: Menu item entry

**Type**

- No menu entry
- Normal menu entry
- Menu tab
- Default menu tab

Show as expanded  
 If selected and this menu link has children, the menu will always appear expanded.

[Apply](#) [Cancel](#)

[Manage](#)
[Shortcuts](#)
[admin](#)
[Edit](#)

[Content](#)
[Structure](#)
[Appearance](#)
[Extend](#)
[Configuration](#)
[People](#)
[Reports](#)
[Help](#)
[My account](#) [Log out](#)

# Mastering Drupal 8

[Home](#)
[Articles](#)

Home

Search [Test](#)

Tools

[Add content](#)



[Back to site](#)
[Manage](#)
[Shortcuts](#)
[admin](#)
[Tour](#)

[Content](#)
[Structure](#)
[Appearance](#)
[Extend](#)
[Configuration](#)
[People](#)
[Reports](#)
[Help](#)

## articles (Content) ☆

Home » Administration » Structure » Views » Articles » Edit

⚠ You have unsaved changes.

Displays

[Master](#)
[Page](#)
[Block\\*](#)
[+ Add](#)
[Edit view name/description](#)

Display name: Block [Duplicate Block](#)

<p><b>TITLE</b></p> <p>Title: None</p> <p><b>FORMAT</b></p> <p>Format: Unformatted list   <a href="#">Settings</a></p> <p>Show: Fields   <a href="#">Settings</a></p> <p><b>FIELDS</b></p> <p>Content: Title <a href="#">Add</a></p> <p><b>FILTER CRITERIA</b></p> <p>Content: Publishing status (= Yes) <a href="#">Add</a></p> <p>Content: Type (= Article) <a href="#">Add</a></p> <p><b>SORT CRITERIA</b></p> <p>Content: Authored on (desc) <a href="#">Add</a></p>	<p><b>BLOCK SETTINGS</b></p> <p>Block name: None</p> <p>Block category: Lists (Views)</p> <p>Allow settings: Items per page</p> <p>Access: Permission   <a href="#">View published content</a></p> <p><b>HEADER</b> <a href="#">Add</a></p> <p><b>FOOTER</b> <a href="#">Add</a></p> <p><b>NO RESULTS BEHAVIOR</b> <a href="#">Add</a></p> <p><b>PAGER</b></p> <p>Use pager: Full   <a href="#">Paged, 10 items</a></p> <p>More link: No</p> <p>Link display: None</p> <p><b>LANGUAGE</b></p> <p>Rendering Language: Content language of view row</p>	<p><b>▶ ADVANCED</b></p>
--	---	--------------------------

[Save](#)
[Cancel](#)

Place block <span>✕</span>		
Search form	Forms	<a href="#">Place block</a>
Switch user	Forms	<a href="#">Place block</a>
User login	Forms	<a href="#">Place block</a>
Help	Help	<a href="#">Place block</a>
articles	Lists (Views)	<a href="#">Place block</a>
Recent comments	Lists (Views)	<a href="#">Place block</a>
Recent content	Lists (Views)	<a href="#">Place block</a>
Who's online	Lists (Views)	<a href="#">Place block</a>
Current hurricanes	Mastering Drupal 8	<a href="#">Place block</a>
Test block	Mastering Drupal 8	<a href="#">Place block</a>
Administration	Menus	<a href="#">Place block</a>
Development	Menus	<a href="#">Place block</a>
Footer	Menus	<a href="#">Place block</a>
Main navigation	Menus	<a href="#">Place block</a>

## Configure block



**Block description:** articles

Display title

**Items per block**

10 (default setting) ▾

Override title

**Visibility**

<b>Language</b> Not restricted	<b>Language selection</b> <input type="checkbox"/> English <input type="checkbox"/> Spanish Select languages to enforce. If none are selected, all languages will be allowed.
<b>Content types</b> Not restricted	
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	

**Machine-readable name \***

views\_block\_articles\_block\_1

A unique name for this block instance. Must be alpha-numeric and underscore separated.

**Region**

Content ▾

Select the region where this block should be displayed.

Save block

### Add filter criteria

Search

Type

- All -
- Comment Statistics
- Content
- Content access
- Content revision
- File Usage
- Global
- Search
- Taxonomy term

TITLE	CATEGORY	DESC
<input type="checkbox"/> Comment count	Comment Statistics	The number of comments on the entity.
<input type="checkbox"/> Comment field name	Comment Statistics	The field name from which the comment originated.
<input type="checkbox"/> Entity type	Comment Statistics	The entity type to which the comment is a reply to.
<input type="checkbox"/> Last comment time	Comment Statistics	Date and time of when the last comment was posted.
<input type="checkbox"/> Last comment uid	Comment Statistics	The User ID of the author of the last comment of an entity.
<input type="checkbox"/> Updated/commented date	Comment Statistics	The most recent of last comment posted or entity updated time.
<input type="checkbox"/> Authored by	Content	The user authoring the content. If you need more fields than the uid add the content: author relationship
<input type="checkbox"/> Authored on	Content	The time that the node was created.
<input type="checkbox"/> Body (body)	Content	Appears in: article, page.

WHERE ((node\_field\_data.status = '1') AND (node\_field\_data.type IN ('Article')))

### Configure filter criterion: Content: Changed

For

The time that the node was last edited.

Expose this filter to visitors, to allow them to change it

**Operator**

- Is less than
- Is less than or equal to
- Is equal to
- Is not equal to
- Is greater than or equal to
- Is greater than
- Is between
- Is not between
- Regular expression

**Value type**

- A date in any machine readable format. CCYY-MM-DD HH:MM:SS is preferred.
- An offset from the current time such as "+1 day" or "-2 hours -30 minutes"

**Value**

[Remove](#)



**Page: Rearrange filter criteria** ✕

All displays  
 This page (override)  
 Revert to default

[Create new filter group](#)

[Show row weights](#)

Operator: <span>And</span>	<ul style="list-style-type: none"> <li><span>+</span> Content: Publishing status = Yes <span style="float: right;">Remove</span></li> <li><span>+</span> Content: Type = Article <span style="float: right;">Remove</span></li> <li><span>+</span> Content: Changed &gt;= -10 days <span style="float: right;">Remove</span></li> </ul>
----------------------------	---

**Configure filter criterion: Content: Sticky at top of lists** ✕

**For**  
All displays

A boolean indicating whether the node should sort to the top of content lists.

Expose this filter to visitors, to allow them to change it

**Operator** **Sticky status**

Is equal to  Yes  
 Is not equal to  No

▶ ADMINISTRATIVE TITLE

Page: Rearrange filter criteria ✕

For: All displays ▼

Create new filter group Show row weights

Operator: And ▼	+ Content: Publishing status = Yes <b>AND</b>	Remove
	+ Content: Type = Article <b>AND</b>	Remove
	+ Content: Changed >= -7 days <b>AND</b>	Remove
	+ Content: Sticky at top of lists = Yes	Remove

And ▼

Operator: And ▼	No filters have been added. Drag to add filters.	Remove group
-----------------	--	--------------

Apply (all displays) Cancel

Page: Rearrange filter criteria ✕

Create new filter group Hide row weights

Operator: And ▼	Content: Publishing status = Yes	1	✓ Default group Group 2	Remove
	Content: Content type = Article	2	Default group ▼	Remove
	Content: Changed >= -7 days	3	Default group ▼	Remove
	Content: Sticky at top of lists = Yes	4	Default group ▼	Remove

And ▼

Operator: And ▼	No filters have been added. Drag to add filters.	Remove group
-----------------	--	--------------

Apply Cancel

Page: Rearrange filter criteria

For: All displays

Create new filter group [Show row weights](#)

Operator: And	+ Content: Publishing status = Yes	Remove
	+ Content: Type = Article	Remove
And		
Operator: Or	+ Content: Sticky at top of lists = Yes	Remove
	+ Content: Changed >= -7 days	Remove

Apply (all displays) Cancel

Configure filter criterion: Content: Type

The node type.

Expose this filter to visitors, to allow them to change it

**Filter type to expose**

Single filter

Grouped filters

Grouped filters allow a choice between predefined operator/value pairs.

Required

**Label**

Type

**Description**

**Operator**

Is one of

Is not one of

Is empty (NULL)

Is not empty (NOT NULL)

**Content types**

Select all

Article

Basic page

Expose operator  
Allow the user to choose the operator.

Allow multiple selections  
Enable to allow users to select multiple items.

Remember the last selection  
Enable to remember the last selection made by the user.

Apply Cancel Remove

**Master: How should each row in this view be styled** ✕

**Row**

- Content
- Fields
- Search results

You may also adjust the [settings](#) for the currently selected row style.

**Add fields** ✕

Search

TITLE	CATEGORY	DESCRIPTION
<input type="checkbox"/> Comment count	Comment Statistics	
<input type="checkbox"/> Comment field name	Comment Statistics	The field name from which the comment originated.
<input type="checkbox"/> Entity type	Comment Statistics	The entity type to which the comment is a reply to.
<input type="checkbox"/> Last comment author	Comment Statistics	The name of the author of the last posted comment.
<input type="checkbox"/> Last comment time	Comment Statistics	Date and time of when the last comment was posted.
<input type="checkbox"/> Last comment uid	Comment Statistics	The User ID of the author of the last comment of an entity.
<input type="checkbox"/> Updated/commented date	Comment Statistics	The most recent of last comment posted or entity updated time.

Display the standard add comment link used on regular nodes, which will only display if the viewing user has

**Add fields** ✕

Search  Type

TITLE	CATEGORY	DESCRIPTION
<input type="checkbox"/> Last comment author	Comment Statistics	The name of the author of the last posted comment.
<input type="checkbox"/> Last comment uid	Comment Statistics	The User ID of the author of the last comment of an entity.
<input type="checkbox"/> Authored by	Content	The user authoring the content. If you need more fields than the uid add the content: author relationship
<input type="checkbox"/> Authored on	Content	The time that the node was created.
<input type="checkbox"/> Authored by	Content revision	The username of the content author.
<input type="checkbox"/> Authored on	Content revision	The time that the node was created.

Rearrange fields ✕

[Show row weights](#)

	REMOVE
☰ Content: Title	Remove
☰ Content revision: Authored by	Remove

**Apply** Cancel

Master: Row style options ✕

View mode  
Teaser ▼

**Apply** Cancel

Content

### Test

Submitted by admin on Sun, 03/20/2016 - 23:24

test

[Read more](#) [Add new comment](#)

#### ▼ STYLE SETTINGS

- Customize field HTML
- Customize label HTML
- Customize field and label wrapper HTML

**Add default classes**

Use default Views classes to identify the field, field label and field content.

**Use field template**

If checked, field api classes will be added by field templates. This is not recommended unless your CSS depends upon these classes being used.

▼ REWRITE RESULTS

- Override the output of this field with custom text
- Output this field as a custom link
- Trim this field to a maximum number of characters
- Strip HTML tags
- Remove whitespace
- Convert newlines to HTML <br> tags

▼ NO RESULTS BEHAVIOR

No results text

Provide text to display if this field contains an empty result. You may include HTML. You may enter data from this view as per the "Replacement patterns" in the "Rewrite Results" section below.

- Count the number 0 as empty  
Enable to display the "no results text" if the field contains the number 0.
- Hide if empty  
Enable to hide this field if it is empty. Note that the field label or rewritten output may still be displayed. To hide labels, check the style or row style settings for empty fields. To hide rewritten content, check the "Hide rewriting if empty" checkbox.
- Hide rewriting if empty  
Do not display rewritten content if this field is empty.

Master: How should this view be styled



Style

- Grid
- HTML List
- Table
- Unformatted list

If the style you choose has settings, be sure to click the settings button that will appear next to it in the View summary.

You may also adjust the [settings](#) for the currently selected style.

Apply

Cancel

### Master: Style options

**Grouping field Nr.1**  
- None -

You may optionally specify a field by which to group the records. Leave blank to not group.

**Row class**

The class to provide on each row. You may use field tokens from as per the "Replacement patterns" used in "Rewrite the output of this field" for all fields.

**Add views row classes**  
Add the default row classes like views-row-1 to the output. You can use this to quickly reduce the amount of markup the view provides by default, at the cost of making it more difficult to apply CSS.

Content

[admin](#)

[Test](#)

[admin](#)

### Master: Style options

**Grouping field Nr.1**  
- None -

You may optionally specify a field by which to group the records. Leave blank to not group.

**Grouping field Nr.2**  
- None -

You may optionally specify a field by which to group the records. Leave blank to not group.

**Number of columns \***

**Automatic width**  
The width of each column will be calculated automatically based on the number of columns provided. If additional classes are entered or a theme injects classes based on a grid system, disabling this option may prove beneficial.

**Alignment**  
 Horizontal  
 Vertical

Horizontal alignment will place items starting in the upper left and moving right. Vertical alignment will place items starting in the upper left and moving down.

**Default column classes**  
Add the default views column classes like views-col, col-1 and clearfix to the output. You can use this to quickly reduce the amount of markup the view provides by default, at the cost of making it more difficult to apply CSS.

**Custom column class**

Additional classes to provide on each column. Separated by a space. You may use field tokens from as per the "Replacement patterns" used in "Rewrite the output of this field" for all fields.

**Default row classes**  
Adds the default views row classes like views-row, row-1 and clearfix to the output. You can use this to quickly reduce the amount of markup the view provides by default, at the cost of making it more difficult to apply CSS.

**Custom row class**

Additional classes to provide on each row. Separated by a space. You may use field tokens from as per the "Replacement patterns" used in "Rewrite the output of this field" for all fields.

Master: Style options
✕

**Grouping field Nr.1**

You may optionally specify a field by which to group the records. Leave blank to not group.

**Row class**

The class to provide on each row. You may use field tokens from as per the "Replacement patterns" used in "Rewrite the output of this field" for all fields.

**Add views row classes**  
 Add the default row classes like views-row-1 to the output. You can use this to quickly reduce the amount of markup the view provides by default, at the cost of making it more difficult to apply CSS.

**List type**  
 Unordered list  
 Ordered list

**Wrapper class**

The class to provide on the wrapper, outside the list.

**List class**

The class to provide on the list element itself.

Apply
Cancel

Master: Style options
✕

Place fields into columns; you may combine multiple fields into the same column. If you do, the separator in the column specified will be used to separate the fields. Check the sortable box to make that column click sortable, and check the default sort radio to determine which column will be sorted by default, if any. You may control column order and field labels in the fields section.

FIELD	COLUMN	ALIGN	SEPARATOR	SORTABLE	DEFAULT ORDER	DEFAULT SORT	HIDE EMPTY COLUMN	RESPONSIVE
Content: Title	<input type="text" value="Content: Title"/>	<input type="text" value="None"/>	<input type="text"/>	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="text" value="High"/>
Content revision: Authored by	<input type="text" value="Content revision: Authored by"/>	<input type="text" value="None"/>	<input type="text"/>	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="text" value="High"/>
None					<input checked="" type="radio"/>	<input type="radio"/>		

**Grouping field Nr.1**

You may optionally specify a field by which to group the records. Leave blank to not group.

**Row class**

The class to provide on each row. You may use field tokens from as per the "Replacement patterns" used in "Rewrite the output of this field" for all fields.

**Add views row classes**  
 Add the default row classes like views-row-1 to the output. You can use this to quickly reduce the amount of markup the view provides by default, at the cost of making it more difficult to apply CSS.

**Override normal sorting if click sorting is used**

**Enable Drupal style "sticky" table headers (Javascript)**  
 (Sticky header effects will not be active for preview below, only on live output.)

Apply
Cancel



### Add relationships

Search:  Type: - All -

	TITLE	CATEGORY	DESCRIPTION
<input type="checkbox"/>	Last comment author	Comment Statistics	The User ID of the author of the last comment of an entity.
<input type="checkbox"/>	Content author	Content	Relate content to the user who created it.
<input checked="" type="checkbox"/>	User	Content revision	The username of the content author.

Selected: User

[Add and configure relationships](#) [Cancel](#)

### Configure Relationship: User

The username of the content author.

Require this relationship  
Enable to hide items that do not contain this relationship

[Apply](#) [Cancel](#) [Remove](#)

### Add fields

Search:  Type: User

	TITLE	CATEGORY	DESCRIPTION
<input type="checkbox"/>	Bulk update	User	Add a form element that lets you run operations on multiple users.
<input type="checkbox"/>	Contact link	User	Provide a simple link to the user contact page.
<input type="checkbox"/>	Created	User	The time that the user was created.
<input type="checkbox"/>	Data	User	Provides access to the user data service.
<input type="checkbox"/>	Default translation	User	A flag indicating whether this is the default translation.
<input type="checkbox"/>	Email	User	Email address for a given user. This field is normally not shown to users, so be cautious when using it.
<input type="checkbox"/>	Initial email	User	The email address used for initial account creation.
<input type="checkbox"/>	Last access	User	The time that the user last accessed the site.
<input type="checkbox"/>	Last login	User	The time that the user last logged in.

[Add and configure fields](#) [Cancel](#)

Add contextual filters
✕

Search

Type  
User ▼

<input type="checkbox"/>	Updated date	User	The time that the user was last edited.
<input type="checkbox"/>	Updated date	User	Date in the form of CCYYMMDD.
<input type="checkbox"/>	Updated day	User	Date in the form of DD (01 - 31).
<input type="checkbox"/>	Updated month	User	Date in the form of MM (01 - 12).
<input type="checkbox"/>	Updated week	User	Date in the form of WW (01 - 53).
<input type="checkbox"/>	Updated year	User	Date in the form of YYYY.
<input type="checkbox"/>	Updated year + month	User	Date in the form of YYYYMM.
<input checked="" type="checkbox"/>	User ID	User	The user ID.
<input type="checkbox"/>	User status	User	Whether the user is active or blocked.
<input type="checkbox"/>	UUID	User	The user UUID.

Selected: User ID

Add and configure contextual filters
Cancel

▼ WHEN THE FILTER VALUE IS *NOT* IN THE URL

**Default actions**

- Display all results for the specified field
- Provide default value
  - Content ID from URL
  - Fixed
    - Query parameter
    - Raw value from URL
    - Taxonomy term ID from URL
    - User ID from logged in user
    - User ID from route context
- Display contents of "No results found"
- Display "Access Denied"

▶ EXCEPTIONS

▼ WHEN THE FILTER VALUE IS NOT IN THE URL

Default actions

- Display all results for the specified field
- Provide default value
- Show "Page not found"
- Display a summary

Sort order

- Ascending
- Descending

Sort by

- Numerical
- Number of records

Format

- List
- Unformatted

Base path

Define the base path for links in this summary view, i.e. `http://example.com/your_view_path/archive`. Do not include beginning and ending forward slash. If this value is empty, views will use the first path found as the base path, in page displays, or / if no path could be found.

- Display record count with link
- Override number of items to display
- Display contents of "No results found"
- Display "Access Denied"

► EXCEPTIONS

Content

- [admin](#) (1)

Back to site | Manage | Shortcuts | admin | Tour

Content | Structure | Appearance | Extend | Configuration | People | Reports | Help

## articles (Content) ☆

Home » Administration » Structure » Views » Articles » Edit

Displays

Master | Page | Block | + Add | Edit view name/description

<b>TITLE</b> Title: None	Access: <a href="#">Permission</a>   <a href="#">View published content</a>	► ADVANCED
<b>FORMAT</b> Format: <a href="#">Unformatted list</a>   <a href="#">Settings</a> Show: <a href="#">Fields</a>   <a href="#">Settings</a>	<b>HEADER</b> <a href="#">Add</a>	
<b>FIELDS</b> <a href="#">Add</a>	<b>FOOTER</b> <a href="#">Add</a>	
<a href="#">Content: Title</a>   <a href="#">Aggregation settings</a> <a href="#">Content revision: Authored by</a>   <a href="#">Aggregation settings</a>	<b>NO RESULTS BEHAVIOR</b> <a href="#">Add</a>	
<b>FILTER CRITERIA</b> <a href="#">Add</a>	<b>PAGER</b> Use pager: <a href="#">Full</a>   <a href="#">Paged, 10 items</a> <a href="#">More link: No</a> <a href="#">Link display: None</a>	
<a href="#">Content: Publishing status (= Yes)</a>   <a href="#">Aggregation settings</a> AND <a href="#">Content: Type (= Article)</a>   <a href="#">Aggregation settings</a> AND <a href="#">Content: Sticky at top of lists (= Yes)</a>   <a href="#">Aggregation settings</a> OR <a href="#">Content: Changed (&amp;gt;= -7 days)</a>   <a href="#">Aggregation settings</a>	<b>LANGUAGE</b> Rendering Language: <a href="#">Content language of view row</a>	
<b>SORT CRITERIA</b> <a href="#">Add</a> <a href="#">Content: Authored on (desc)</a>   <a href="#">Aggregation settings</a>		

Save | Cancel

Configure aggregation settings for field `<em class="placeholder">Content revision: Authored by</em>` ✕

**Aggregation type**

- Group results together
- Count
- Count DISTINCT
- Sum
- Average
- Minimum
- Maximum
- Standard deviation

Bundle

Language

Entity\_type

Entity ID

Target\_id

Select any additional columns of this field to include in the query and to group on.

# Chapter 8: Theming Essentials

## Appearance ☆

List

Update

Settings


[Home](#) » [Administration](#)

Set and configure the default theme for your website. Alternative [themes](#) are available.

You can place blocks for each theme on the [block layout](#) page.

[+ Install new theme](#)

### Installed themes




### Bartik 8.3.4 (default theme)

A flexible, recolorable theme with many regions and a responsive, mobile-first layout.

[Settings](#)


## Installed themes



### Bartik 8.3.4 (default theme)

A flexible, recolorable theme with many regions and a responsive, mobile-first layout.

[Settings](#)



### Seven 8.3.4 (administration theme)

The default administration theme for Drupal 8 was designed with clean lines, simple blocks, and sans-serif font to emphasize the tools and tasks at hand.

[Settings](#) | [Set as default](#)

## Uninstalled theme



### Stark 8.3.4

An intentionally plain theme with no styling to demonstrate default Drupal's HTML and CSS. Learn how to build a custom theme from Stark in the [Theming Guide](#).

[Install](#) | [Install and set as default](#)

## Appearance settings ☆

List Update Settings

Global settings Bartik Seven

[Home](#) » [Administration](#) » [Appearance](#)

Control default display settings for your site, across all themes. Use theme-specific settings to override these defaults.

### ▼ PAGE ELEMENT DISPLAY

- User pictures in posts
- User pictures in comments
- User verification status in comments
- Shortcut icon

### ▼ LOGO IMAGE

- Use the logo supplied by the theme

### ▼ FAVICON

Your shortcut icon, or favicon, is displayed in the address bar and bookmarks of most browsers.

- Use the favicon supplied by the theme

## Bootstrap

[View](#) [Version control](#)

Posted by [wundo](#) on 18 May 2008

“ Sleek, intuitive, and powerful mobile first front-end framework for faster and easier web development. Bootstrap has become one of the most popular front-end frameworks and open source projects in the world.

This base theme bridges the gap between Drupal and the [Bootstrap Framework](#).

### Features

- [jsDelivr CDN](#) for "out-of-the-box" styling and faster page load times.
- [Bootswatch](#) theme support, if using the CDN.
- Glyphicons support via [Icon API](#).
- Extensive integration and template/preprocessor overrides for most of the [Bootstrap Framework](#) CSS, Components and JavaScript
- Theme settings to further enhance the Drupal Bootstrap integration:
  - [Breadcrumbs](#)
  - [Navbar](#)
  - [Popovers](#)
  - [Tooltips](#)
  - [Wells](#) (per region)



**Bootstrap 3**  
for Drupal

- ▶ core
- ▶ modules
- ▶ profiles
- ▶ sites
- ▼ themes
  - ▶ bootstrap

# Welcome to Mastering Drupal 8

No front page content has been created yet.

- [Add content](#)

[Subscribe to](#)

Search

### Tools

[Add content](#)






- ▼ **twiggy**
  - ▼ **css**
    - styles.css
  - ▼ **js**
    - scripts.js
  - ▼ **templates**
    - html.html.twig
    - page.html.twig
    - screenshot.png
  - twiggy.info.yml
  - twiggy.libraries.yml

## Chapter 9: Working with Twig

### Welcome to Mastering Drupal 8



```
<!-- THEME HOOK: 'block' -->
<!-- FILE NAME SUGGESTIONS:
 * block--twiggy-page-title.html.twig
 * block--page-title-block.html.twig
 * block--core.html.twig
 * block.html.twig
-->
<!-- BEGIN OUTPUT from 'core/themes/classy/templates/block/block.html.twig' -->
<div id="block-twiggy-page-title" class="contextual-region block block-core block-page-title-block">
  <div data-contextual-id="block:block=twiggy_page_title:langcode=en" class="contextual" role="form">_</div>
  <!-- THEME DEBUG -->
  <!-- THEME HOOK: 'page_title' -->
  <!-- BEGIN OUTPUT from 'core/themes/classy/templates/content/page-title.html.twig' -->
  <h1 class="js-quickedit-page-title page-title">Welcome to Mastering Drupal 8 /h1> == $0
  <!-- END OUTPUT from 'core/themes/classy/templates/content/page-title.html.twig' -->
```

- css
  - bootstrap-theme.css
  - bootstrap-theme.css.map
  - bootstrap-theme.min.css
  - bootstrap-theme.min.css.map
  - bootstrap.css
  - bootstrap.css.map
  - bootstrap.min.css
  - bootstrap.min.css.map
- fonts
  - glyphicons-halflings-regular.eot
  - glyphicons-halflings-regular.svg
  - glyphicons-halflings-regular.ttf
  - glyphicons-halflings-regular.woff
  - glyphicons-halflings-regular.woff2
- js
  - bootstrap.js
  - bootstrap.min.js
  - npm.js
- templates
  - html.html.twig
  - page.html.twig
  - screenshot.png
  - twiggy.info.yml
  - twiggy.libraries.yml
  - twiggy.theme

### Welcome to Mastering Drupal 8

No front page content has been created yet.



```
@import url("/themes/twiggy/css/bootstrap.min.css?oskhp4");
@import url("/themes/twiggy/css/bootstrap-theme.min.css?oskhp4");
```

# Hello, world!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting pieces of content. Use it as a starting point to create something more unique.

[Learn more »](#)

## Heading

Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.

[View details »](#)

## Heading

Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.

[View details »](#)

## Heading

Donec sed odio dui. Cras justo odio, dapibus ac facilisis in, egestas eget quam. Vestibulum id ligula porta felis euismod semper. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus.

[View details »](#)

# Welcome to Mastering Drupal 8

No front page content has been created yet.

- [Add content](#)



## Headline

Hello, World!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting piece of content. Use it as a starting point to create something more unique.

## Button

[Learn more](#)

## Homepage

[View](#) [Edit](#) [Delete](#) [Revisions](#)

Homepage placeholder

### Headline

Hello, World!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting piece of content. Use it as a starting point to create something more unique.

### Button

[Learn more](#)

```

<!-- FILE NAME SUGGESTIONS:
  * node--5--full.html.twig
  * node--5.html.twig
  * node--page--full.html.twig
  * node--page.html.twig
  * node--full.html.twig
  x node.html.twig
-->
<!-- BEGIN OUTPUT from 'core/themes/classy/templates/content/node.html.twig'
-->
▶<article data-history-node-id="5" data-quickedit-entity-id="node/5" role=
"article" class="contextual-region node node--type-page node--view-mode-full"
about="/node/5" typeof="schema:WebPage" data-quickedit-entity-instance-id="0">
...</article> == $0
<!-- END OUTPUT from 'core/themes/classy/templates/content/node.html.twig' -

```

```

<!-- FILE NAME SUGGESTIONS:
  * block--myjumbotron.html.twig
  * block--block-content--8afffa8e-7bf2-40a7-9fd4-b7a86db91049.html.twig
  * block--block-content.html.twig
  * block--block-content.html.twig
  x block.html.twig
-->
<!-- BEGIN OUTPUT from 'core/themes/classy/templates/block/block.html.twig' -->
▶<div data-quickedit-entity-id="block_content/2" id="block-myjumbotron" class="contextual-region block
block-block-content block-block-content8afffa8e-7bf2-40a7-9fd4-b7a86db91049" data-quickedit-entity-
instance-id="0">...</div> == $0
<!-- END OUTPUT from 'core/themes/classy/templates/block/block.html.twig' -->

```

# Headline Hello, World!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting piece of content. Use it as a starting point to create something more unique.

**Button**  
[Learn more](#)

# Hello, World!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting piece of content. Use it as a starting point to create something more unique.

[Learn more](#)

```
<!-- FILE NAME SUGGESTIONS:
 * field--block-content--field-button--jumbotron.html.twig
 * field--block-content--field-button.html.twig
 * field--block-content--jumbotron.html.twig
 * field--field-button.html.twig
 * field--link.html.twig
 x field.html.twig
-->
<!-- BEGIN OUTPUT from 'core/themes/classy/templates/field/field.html.twig' -->
▶<div data-quickedit-field-id="block_content/2/field_button/en/full" class="field field--name-field-
button field--type-link field--label-hidden field__item">...</div>
<!-- END OUTPUT from 'core/themes/classy/templates/field/field.html.twig' -->
```

# Hello, World!

This is a template for a simple marketing or informational website. It includes a large callout called a jumbotron and three supporting piece of content. Use it as a starting point to create something more unique.

[Learn more](#)

## Chapter 10: Extending Drupal

```
[vagrant@localhost public]$ drush php
Psy Shell v0.6.1 (PHP 5.6.17 - cli) by Justin Hileman
>>> $query = \Drupal::entityQuery('node');
=> Drupal\Core\Entity\Query\Sql\Query {#10930
  +"conjunction": "AND",
  }
>>> $query->execute();
=> [
  11 => "11",
  ]
>>> █
```

```
[vagrant@localhost modules]$ drupal generate:module

// Welcome to the Drupal module generator

Enter the new module name:
> Mastering Drupal 8

Enter the module machine name [mastering_drupal_8]:
>

Enter the module Path [/modules/custom]:
>

Enter module description [My Awesome Module]:
> Mastering Drupal 8

Enter package name [Custom]:
>

Enter Drupal Core version [8.x]:
>

Do you want to generate a .module file (yes/no) [no]:
>

Define module as feature (yes/no) [no]:
>

Do you want to add a composer.json file to your module (yes/no) [yes]:
>

Would you like to add module dependencies (yes/no) [no]:
>

Do you confirm generation? (yes/no) [yes]:
>

Generated or updated files
Site path: /vagrant/public
1 - modules/custom/mastering_drupal_8/mastering_drupal_8.info.yml
2 - modules/custom/mastering_drupal_8/composer.json
```

```

[vagrant@localhost public]$ drupal generate:plugin:block

// Welcome to the Drupal Plugin Block generator
Enter the module name [entity_rest_extra]:
> mastering_drupal_8

Plugin class name [DefaultBlock]:
> TestBlock

Plugin label [Test block]:
>

Plugin id [test_block]:
>

Theme region to render Plugin Block [ ]:
>

Do you want to load services from the container (yes/no) [no]:
>

You can add input fields to create special configurations in the block.
This is optional, press enter to continue

Do you want to generate a form structure? (yes/no) [yes]:
>

Type [ ]:
>

Do you confirm generation? (yes/no) [yes]:
>

Generated or updated files
Site path: /vagrant/public
1 - modules/custom/mastering_drupal_8/src/Plugin/Block/TestBlock.php
// cache:rebuild

Rebuilding cache(s), wait a moment please.

```

[OK] Done clearing cache(s).

The screenshot displays the Drupal 8 administration interface. A 'Place block' dialog box is open, showing a search for 'test' and a table of results. The table has three columns: BLOCK, CATEGORY, and OPERATIONS. The result is 'Test block' from the 'Mastering Drupal 8' category, with a 'Place block' button next to it. The background shows the standard Drupal 8 admin layout with a top navigation bar and a left sidebar with various menu items.

BLOCK	CATEGORY	OPERATIONS
Test block	Mastering Drupal 8	Place block



Manage Shortcuts admin Edit

Content Structure Appearance Extend Configuration People Reports Help

My account Log out

# Mastering Drupal 8

Home

Search

Tools

[Add content](#)

## Welcome to Mastering Drupal 8

### Test block

Implement TestBlock.  
No front page content has been created yet.  
[Add content](#)



Powered by [Drupal](#)

Contact

```
[vagrant@localhost public]$ drupal generate:service
// Welcome to the Drupal service generator
Enter the module name [ctools]:
> mastering_drupal_8

Enter the service name [mastering_drupal_8.default]:
> mastering_drupal_8.weather_underground

Enter the Class name [DefaultService]:
> WeatherUnderground

Create an interface (yes/no) [yes]:
> no

Do you want to load services from the container (yes/no) [no]:
> yes

Type the service name or use keyup or keydown.
This is optional, press enter to continue

Enter your service [ ]:
> http_client
Enter your service [ ]:
>

Do you confirm generation? (yes/no) [yes]:
>

Generated or updated files
Site path: /vagrant/public
1 - modules/custom/mastering_drupal_8/mastering_drupal_8.services.yml
2 - modules/custom/mastering_drupal_8/src/WeatherUnderground.php
// cache:rebuild

Rebuilding cache(s), wait a moment please.
```

[OK] Done clearing cache(s).

```

1 <?php
2
3 /**
4  * @file
5  * Contains \Drupal\mastering_drupal_8\WeatherUnderground.
6  */
7
8 namespace Drupal\mastering_drupal_8;
9
10 use GuzzleHttp\Client;
11
12 /**
13  * Class WeatherUnderground.
14  *
15  * @package Drupal\mastering_drupal_8
16  */
17 class WeatherUnderground {
18
19     /**
20      * GuzzleHttp\Client definition.
21      *
22      * @var GuzzleHttp\Client
23      */
24     protected $http_client;
25
26     /**
27      * Constructor.
28      */
29     public function __construct(Client $http_client) {
30         $this->http_client = $http_client;
31     }
32 }

```

```

    /**
     * Returns information about current hurricanes and tropical storms.
     *
     * @return ResponseInterface
     */
    public function getcurrentHurricane() {
        return $this->http_client->get('http://api.wunderground.com/api/{key}/currenthurricane/view.json');
    }

```

```
[vagrant@localhost public]$ drupal generate:plugin:block
```

```
// Welcome to the Drupal Plugin Block generator
```

```
Enter the module name [ctools]:
```

```
> mastering_drupal_8
```

```
Plugin class name [DefaultBlock]:
```

```
> CurrentHurricanes
```

```
Plugin label [Current hurricanes]:
```

```
>
```

```
Plugin id [current_hurricanes]:
```

```
>
```

```
Theme region to render Plugin Block [ ]:
```

```
>
```

```
Do you want to load services from the container (yes/no) [no]:
```

```
> yes
```

```
Type the service name or use keyup or keydown.
```

```
This is optional, press enter to continue
```

```
Enter your service [ ]:
```

```
> mastering_drupal_8.weather_underground
```

```
Enter your service [ ]:
```

```
>
```

```
You can add input fields to create special configurations in the block.
```

```
This is optional, press enter to continue
```

```
Do you want to generate a form structure? (yes/no) [yes]:
```

```
> no
```

```
Do you confirm generation? (yes/no) [yes]:
```

```
>
```

```
Generated or updated files
```

```
Site path: /vagrant/public
```

```
1 - modules/custom/mastering_drupal_8/src/Plugin/Block/CurrentHurricanes.php
```

```
// cache:rebuild
```

```
Rebuilding cache(s), wait a moment please.
```

```
[OK] Done clearing cache(s).
```

Search

Tools

[Add content](#)

**Current hurricanes**  
Implement CurrentHurricanes.

## Welcome to Mastering Drupal 8

**Test block**  
Implement TestBlock.  
No front page content has been created yet.  
[Add content](#)



```
/**
 * {@inheritdoc}
 */
public function build() {
  $current_hurricanes = json_decode($this->mastering_drupal_8_weather_underground->getCurrentHurricane()->getBody());
  $build = [];

  $build['list'] = [
    '#theme' => 'item_list',
    '#items' => [],
  ];

  foreach ($current_hurricanes->currenthurricane as $hurricane) {
    $build['list']['#items'][] = $hurricane->stormName_Nice;
  }

  if (0 === sizeof($current_hurricanes->currenthurricane)) {
    $build['list']['#items'][] = 'None';
  }

  return $build;
}
```

**Username \***

Enter your Mastering Drupal 8 username.

**Password \***

Enter the password that accompanies your username.








### Test



Submitted by [admin](#) on Sun, 03/20/2016 - 23:24  
test

#### Add new comment

Subject

Comment \*








**B** *I*       Format -  Source

Text format Basic HTML  [About text formats](#) 



Title	Content type	Author	Status	Updated	Operations
<a href="#">Test</a> <b>New</b>	Article	<a href="#">admin</a>	published	04/05/2016 - 22:48	<input type="button" value="Edit"/>

Title \*

#### Body (Edit summary)

**B** *I*       Format -  Source

test

Text format Basic HTML  [About text formats](#) 

Tags

Enter a comma-separated list. For example: Amsterdam, Mexico City, "Cleveland, Ohio"

Image

 No file chosen

One file only.

50 MB limit.

Allowed types: png gif jpg jpeg.

Home

Search

Test Test 2

Test:

Tools  
[Add content](#)



Home


Search

+ Test

Test:

Tools  
[Add content](#)





```
[vagrant@localhost public]$ drupal generate:event:subscriber
Enter the module name [ctools]:
> mastering_drupal_8

Enter the service name [mastering_drupal_8.default]:
> mastering_drupal_8.event_subscriber

Class name [DefaultSubscriber]:
> MasteringDrupal8EventSubscriber

Type the event name or use keyup or keydown.
This is optional, press enter to continue

Enter event name [ ]:
> kernel.terminate

Callback function name to handle event [kernel_terminate]:
> onTerminate

Enter event name [ ]:
>
Do you want to load services from the container (yes/no) [no]:
>

Do you confirm generation? (yes/no) [yes]:
>

Generated or updated files
Site path: /vagrant/public
1 - modules/custom/mastering_drupal_8/src/EventSubscriber/MasteringDrupal8EventSubscriber.php
2 - modules/custom/mastering_drupal_8/mastering_drupal_8.services.yml
// cache:rebuild

Rebuilding cache(s), wait a moment please.
```

```
[OK] Done clearing cache(s).
```

```

namespace Drupal\mastering_drupal_8\EventSubscriber;

use Symfony\Component\EventDispatcher\EventSubscriberInterface;
use Symfony\Component\EventDispatcher\Event;

/**
 * Class MasteringDrupal8EventSubscriber.
 *
 * @package Drupal\mastering_drupal_8
 */
class MasteringDrupal8EventSubscriber implements EventSubscriberInterface {

    /**
     * Constructor.
     */
    public function __construct() {

    }

    /**
     * {@inheritdoc}
     */
    static function getSubscribedEvents() {
        $events['kernel.terminate'] = ['onTerminate'];

        return $events;
    }

    /**
     * This method is called whenever the kernel.terminate event is
     * dispatched.
     *
     * @param GetResponseEvent $event
     */
    public function onTerminate(Event $event) {
        drupal_set_message('Event kernel.terminate thrown by Subscriber in module mastering_drupal_8.', 'status', TRUE);
    }
}

```



## Chapter 11: Working with Forms and the Form API

```
[[vagrant@localhost public]$ drupal generate:form

// Welcome to the Drupal form generator
Enter the module name [ctools]:
[ > mastering_drupal_8

Enter the Form Class name [DefaultForm]:
[ > TestForm

Enter the Form id [test_form]:
[ >

Do you want to load services from the container (yes/no) [no]:
[ >

Do you want to generate a form structure? (yes/no) [yes]:
[ >

Type [ ]:
[ > textfield

Input label:
[ > First name

Input machine name [first_name]:
[ >

Maximum amount of characters [64]:
[ >

Width of the textfield (in characters) [64]:
[ >

Description [ ]:
[ >

Default value [ ]:
[ >

Weight for input item [0]:
[ >
```

Manage Shortcuts admin Edit

Content Structure Appearance Extend Configuration People Reports Help

My account Log out

# Mastering Drupal 8

Home

Home

Search

Tools

[Add content](#)

First name

Last name

Submit

Admin menu Manage Shortcuts admin Edit

Content Structure Appearance Extend Configuration People Reports Help

My account Log out

# Mastering Drupal 8

Home

Home

Search

Tools

[Add content](#)

## Are you sure you want to proceed?

This action cannot be undone.

Confirm Cancel

Manage Shortcuts admin Edit

Content Structure Appearance Extend Configuration People Reports Help

My account Log out

# Mastering Drupal 8

Home

Home

Search

Name

Save configuration

Tools

[Add content](#)

Home Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Single export

Synchronize Import Export

Full archive Single item

Home » Administration » Configuration » Development » Synchronize

Choose a configuration item to display its YAML structure.

Configuration type


Simple configuration

Configuration name

mastering\_drupal\_8.settings

Here is your configuration:

```
name: 'Mastering Drupal 8'
```



▼ Name

**Value**

Mastering Drupal 8

Action 1

Action 2

### Mastering Drupal 8

English

Spanish

✓ - Not specified -

- Not applicable -

Save configuration

[Mastering Drupal 8](#)

Save configuration

[More](#)

Save configuration

1 2 3 4 5 6 7 8 9 ... [Next »](#) [Last »](#)

Path


Save configuration

<input type="checkbox"/>	Column one	Column two
<input type="checkbox"/>	Row	One
<input type="checkbox"/>	Row	Two
<input type="checkbox"/>	Row	Three
<input type="checkbox"/>	Row	Four
<input type="checkbox"/>	Row	Five

Save configuration

Url

Save configuration

 Please enter a URL.



# Mastering Drupal 8

Home

[Home](#)

Search



Tools

[Add content](#)

▼ Rows

URL 0

URL 1

URL 2

Add row

Save configuration

# Chapter 12: RESTful Services

http://localhost:8080/node/11?\_format=hal\_json

GET http://localhost:8080/node/11?\_format=hal\_json

Authorization: Basic YWRtaW46YWRtaW4=

Status: 200 OK Time: 1117 ms

```
1 {
2   "_links": {
3     "self": {
4       "href": "http://localhost:8080/node/11?_format=hal_json"
5     },
6     "type": {
7       "href": "http://localhost:8080/rest/type/node/article"
8     },
9     "http://localhost:8080/rest/relation/node/article/uid": [
10      {
11        "href": "http://localhost:8080/user/1?_format=hal_json",
12        "lang": "en"
13      }
14    ],
15    "http://localhost:8080/rest/relation/node/article/revision_uid": [
16      {
17        "href": "http://localhost:8080/user/1?_format=hal_json"
18      }
19    ]
20  },
21 }
```

http://localhost:8080/node/11?\_format=hal\_json

GET http://localhost:8080/node/11?\_format=hal\_json

Authorization: Basic YWRtaW46YWRtaW4=

Status: 200 OK Time: 1117 ms

```
43 },
44   "_embedded": {
45     "http://localhost:8080/rest/relation/node/article/uid": [
46       {
47         "_links": {
48           "self": {
49             "href": "http://localhost:8080/user/1?_format=hal_json"
50           },
51           "type": {
52             "href": "http://localhost:8080/rest/type/user/user"
53           }
54         },
55         "uuid": [
56           {
57             "value": "deca671a-d0bc-407f-8c47-718d86843804"
58           }
59         ],
60         "lang": "en"
61       }
62     ],
63   },
64 }
```

▼ WEB SERVICES

- HAL** ▶ Serializes entities using Hypertext Application Language.
- HTTP Basic Authentication** ▶ Provides the HTTP Basic authentication provider
- RESTful Web Services** ▶ Exposes entities and other resources as RESTful web API
- Serialization** ▶ Provides a service for (de)serializing data to/from formats such as JSON and XML

Install

VIEW BASIC INFORMATION

View name \*

User posts  Machine name: user\_posts [\[Edit\]](#)

Description

VIEW SETTINGS

Show:  of type:  tagged with:  sorted by:

PAGE SETTINGS

Create a page

BLOCK SETTINGS

Create a block

REST EXPORT SETTINGS

Provide a REST export

REST export path

OTHER

Show: Entity

FIELDS

The selected style or r

FILTER CRITERIA

Content: Publishing sta

SORT CRITERIA

Content: Authored on

Save Cancel

Preview

Preview with contextua

Query

Title

Path

Query build time

Query execute time

View render time

Auto pre

Add relationships

For:  Search:  Type:

Relationship	Content Type	Description
<input type="checkbox"/> Image (field_image:target_id)	Content	Appears in: article.
<input type="checkbox"/> Taxonomy term referenced from field_tags	Content	Appears in: article.
<input type="checkbox"/> Taxonomy terms on node	Content	Relate nodes to taxonomy terms, specifying which vocabulary or vocabularies to use. This relationship will cause duplicated records if there are multiple terms.
<input type="checkbox"/> Content	Content revision	The node ID.
<input type="checkbox"/> Content	Content revision	The node revision ID.
<input checked="" type="checkbox"/> User	Content revision	The username of the content author.
<input type="checkbox"/> File	File Usage	A file that is associated with this node, usually because it is in a field on the node.
<input type="checkbox"/> Content with term	Taxonomy term	Relate all content tagged with a term.

Selected: User

Apply (all displays) Cancel



### Add contextual filters

For: All displays | Search: | Type: - All -

<input type="checkbox"/>	Updated date	User	The time that the user was last edited.
<input type="checkbox"/>	Updated date	User	Date in the form of CCYYMMDD.
<input type="checkbox"/>	Updated day	User	Date in the form of DD (01 - 31).
<input type="checkbox"/>	Updated month	User	Date in the form of MM (01 - 12).
<input type="checkbox"/>	Updated week	User	Date in the form of WW (01 - 53).
<input type="checkbox"/>	Updated year	User	Date in the form of YYYY.
<input type="checkbox"/>	Updated year + month	User	Date in the form of YYYYMM.
<input checked="" type="checkbox"/>	User ID	User	The user ID.
<input type="checkbox"/>	User status	User	Whether the user is active or blocked.
<input type="checkbox"/>	UUID	User	The user UUID.

Selected: User ID

Apply (all displays) | Cancel

### Configure contextual filter: User: User ID

For: All displays

The user ID.

Relationship: User

This display does not have a source for contextual filters, so no contextual filter value will be available unless you select 'Provide default'.

**WHEN THE FILTER VALUE IS NOT AVAILABLE**

**Default actions**

- Display all results for the specified field
- Provide default value

**Type**

Content ID from URL

- Show "Page not found"
- Display a summary
- Display contents of "No results found"
- Display "Access Denied"

EXCEPTIONS

Skip default argument for view URL  
Select whether to include this default argument when constructing the URL for this view. Skipping default arguments is useful e.g. in the case of feeds.

Apply (all displays) | Cancel | Remove

http://localhost:8081/node + No environment

GET http://localhost:8081/node/1?\_format=hal\_json Params Send Save

Authorization Headers (1) Body Pre-request Script Tests Generate Code

Authorization Basic YWRtaW46YWRtaW4= Presets


key value Bulk Edit

Body Cookies Headers (16) Tests Status: 200 OK Time: 848 ms

Pretty Raw Preview JSON

```

1- {
2-   "_links": {
3-     "self": {
4-       "href": "http://localhost:8081/node/5?_format=hal_json"
5-     },
6-     "type": {
7-       "href": "http://localhost:8081/rest/type/node/page"
8-     },
9-     "http://localhost:8081/rest/relation/node/page/uid": [
10-      {
11-        "href": "http://localhost:8081/user/1?_format=hal_json",
12-        "lang": "en"
13-      }
14-    ],
15-     "http://localhost:8081/rest/relation/node/page/revision_uid": [
16-      {
17-        "href": "http://localhost:8081/user/1?_format=hal_json"
18-      }
19-    ]
20-   },
  
```



http://localhost/node/10 + No environment 👁

**PATCH** ⌵ http://localhost/node/10 Params Send ⌵ Save ⌵

Authorization ● **Headers (2)** Body Pre-request Script Tests Generate Code

<input checked="" type="checkbox"/>	Authorization	Basic YWRtaW46YWRtaW4=	⋮ ×	<span>Presets</span> <span>⌵</span>
<input checked="" type="checkbox"/>	Content-Type	application/hal+json	⋮ ×	
	key	value	<span>Bulk Edit</span>	

Body Cookies **Headers (14)** Tests Status: 204 No Content Time: 2403 ms

**Cache-Control** → must-revalidate, no-cache, post-check=0, pre-check=0, private

**Connection** → close

**Content-Type** → text/html; charset=UTF-8

**Content-language** → en

**Date** → Mon, 21 Mar 2016 02:52:56 GMT

http://localhost/node/10 + No environment 👁

**DELETE** ⌵ http://localhost/node/10 Params Send ⌵ Save ⌵

Authorization ● **Headers (1)** Body Pre-request Script Tests Generate Code

<input checked="" type="checkbox"/>	Authorization	Basic YWRtaW46YWRtaW4=	⋮ ×	<span>Presets</span> <span>⌵</span>
	key	value	<span>Bulk Edit</span>	

Body Cookies **Headers (18)** Tests Status: 204 No Content Time: 1541 ms

**Accept-Ranges** → bytes

**Age** → 0

**Cache-Control** → must-revalidate, no-cache, post-check=0, pre-check=0, private

**Connection** → keep-alive

**Content-Type** → text/html; charset=UTF-8

**Content-language** → en

**Date** → Mon, 21 Mar 2016 03:11:10 GMT

```

[vagrant@localhost public]$ drupal generate:plugin:rest:resource

// Welcome to the Drupal Plugin Rest Resource generator
Enter the module name [entity_rest_extra]:
> mastering_drupal_8

Enter the plugin rest resource name [DefaultRestResource]:
> UserPostsResource

Enter the plugin rest resource id [user_posts_resource]:
>

Enter the plugin rest resource label [User posts resource]:
>

Enter the plugin rest resource url:
> user/{user}/posts

Please select what REST States implement in your resource (GET is selected by default):
[0] GET
[1] PUT
[2] POST
[3] DELETE
[4] PATCH
[5] HEAD
[6] OPTIONS
> 0

Do you confirm generation? (yes/no) [yes]:
>

Generated or updated files
Site path: /vagrant/public
1 - modules/custom/mastering_drupal_8/src/Plugin/rest/resource/UserPostsResource.php
// cache:rebuild

Rebuilding cache(s), wait a moment please.

```

```
[OK] Done clearing cache(s).
```

```

/**
 * Responds to GET requests.
 *
 * Returns a list of bundles for specified entity.
 *
 * @throws \Symfony\Component\HttpKernel\Exception\HttpException Throws exception expected.
 */
public function get($user) {
    $page = \Drupal::request()->query->has('page') ? \Drupal::request()->query->get('page') : 0;

    // Load all nodes authored by the user
    $nids = \Drupal::entityQuery('node')
        ->condition('uid', $user)
        ->sort('created', 'ASC')
        ->pager()
        ->execute();

    // Load the nodes
    $nodes = Node::loadMultiple($nids);

    $response = new ResourceResponse($nodes);

    // Add URL cache context
    $metadata = new CacheableMetadata();
    $metadata->addCacheContexts(['url']);
    $response->addCacheableDependency($metadata);

    return $response;
}

```

```

/**
 * Responds to GET requests.
 *
 * Returns a list of bundles for specified entity.
 *
 * @throws \Symfony\Component\HttpKernel\Exception\HttpException
 *   Throws exception expected.
 */
public function get($user) {
    $page = \Drupal::request()->query->has('page') ? \Drupal::request()->query->get('page') : 0;

    // Get count of all nodes authored by the user
    $count = \Drupal::entityQuery('node')
        ->condition('uid', $user)
        ->count()
        ->execute();

    $pages = floor($count / 10);

    // Load all nodes authored by the user
    $nids = \Drupal::entityQuery('node')
        ->condition('uid', $user)
        ->sort('created', 'ASC')
        ->pager()
        ->execute();

    // Load the nodes
    $nodes = (sizeof($nids)) ? Node::loadMultiple($nids) : [];

    $links = [
        'self' => [ 'href' => $this->getPagerLink($user, $page) ],
        'start' => [ 'href' => $this->getPagerLink($user, 0) ],
        'last' => [ 'href' => $this->getPagerLink($user, $pages) ],
    ];

    if (0 < $page) {
        $links['prev'] = [ 'href' => $this->getPagerLink($user, ($page - 1)) ];
    }
    if (0 < $pages && $page != $pages) {
        $links['next'] = [ 'href' => $this->getPagerLink($user, ($page + 1)) ];
    }

    $response = new ResourceResponse([
        '_links' => $links,
        'total' => $count,
        'posts' => array_values($nodes)
    ]);

    // Add URL cache context
    $metadata = new CacheableMetadata();
    $metadata->addCacheContexts([ 'url.query_args:page' ]);
    $response->addCacheableDependency($metadata);

    return $response;
}

```

```

/**
 * Responds to GET requests.
 *
 * Returns a list of bundles for specified entity.
 *
 * @throws \Symfony\Component\HttpKernel\Exception\HttpException Throws exception expected.
 */
public function get($user) {
    $page = \Drupal::request()->query->has('page') ? \Drupal::request()->query->get('page') : 0;

    // Load the user being requested
    $request_user = User::load($user);

    $filter_unpublished = !$this->canSeeUnpublished($request_user);

    // Get count of all nodes authored by the user
    $count_query = \Drupal::entityQuery('node')
        ->condition('uid', $user);

    if ($filter_unpublished) {
        $count_query->condition('status', 1);
    }

    $count_query->count()
        ->addTag('node_access')
        ->addMetadata('op', 'view')
        ->addMetadata('account', $this->currentUser->getAccount());

    $count = $count_query->execute();

    // Load all nodes authored by the user
    $node_query = \Drupal::entityQuery('node')
        ->condition('uid', $user);

    if ($filter_unpublished) {
        $node_query->condition('status', 1);
    }

    $node_query->sort('created', 'ASC')
        ->pager()
        ->addTag('node_access')
        ->addMetadata('op', 'view')
        ->addMetadata('account', $this->currentUser->getAccount());

    $nids = $node_query->execute();

    // Load the nodes
    $nodes = Node::loadMultiple($nids);

    $links = [
        'self' => [ 'href' => $this->getPagerLink($user, $page) ],
        'start' => [ 'href' => $this->getPagerLink($user, 0) ],
        'last' => [ 'href' => $this->getPagerLink($user, (ceil($count / 10) - 1)) ],
    ];

    $response = new ResourceResponse([
        'links' => $links,
        'total' => $count,
        'posts' => array_values($nodes)
    ]);

    // Add URL cache context
    $metadata = new CacheableMetadata();
    $metadata->addCacheContexts(['url.query_args:page']);
    $response->addCacheableDependency($metadata);

    return $response;
}

```

```

public function get($user) {
    $page = \Drupal::request()->query->has('page') ? \Drupal::request()->query->get('page') : 0;

    // Load the user being requested
    $request_user = User::load($user);

    // Ensure the requesting user is able to view the requested user
    $entity_access = $request_user->access('view', $this->currentUser, TRUE);
    if (!$entity_access->isAllowed()) {
        throw new AccessDeniedHttpException();
    }

    $filter_unpublished = !$this->canSeeUnpublished($request_user);

    // Get count of all nodes authored by the user
    $count_query = \Drupal::entityQuery('node')
        ->condition('uid', $user);

    if ($filter_unpublished) {
        $count_query->condition('status', 1);
    }

    $count_query->count()
        ->addTag('node_access')
        ->addMetaData('op', 'view')
        ->addMetaData('account', $this->currentUser->getAccount());

    $count = $count_query->execute();

    // Load all nodes authored by the user
    $node_query = \Drupal::entityQuery('node')
        ->condition('uid', $user);

    if ($filter_unpublished) {
        $node_query->condition('status', 1);
    }

    $node_query->sort('created', 'ASC')
        ->pager()
        ->addTag('node_access')
        ->addMetaData('op', 'view')
        ->addMetaData('account', $this->currentUser->getAccount());

    $snids = $node_query->execute();

    // Load the nodes
    $nodes = Node::loadMultiple($snids);

    $links = [
        'self' => [ 'href' => $this->getPagerLink($user, $page) ],
        'start' => [ 'href' => $this->getPagerLink($user, 0) ],
        'last' => [ 'href' => $this->getPagerLink($user, ceil($count / 10) - 1) ],
    ];

    $response = new ResourceResponse([
        'links' => $links,
        'total' => $count,
        'posts' => array_values($nodes)
    ]);

    // Add URL cache context
    $metadata = new CacheableMetadata();
    $metadata->addCacheContexts(['url.query_args.page']);
    $response->addCacheableDependency($metadata);
    $response->addCacheableDependency($entity_access);

    return $response;
}

```

# Chapter 13: Multilingual Capabilities

## ▼ MULTILINGUAL

- Configuration Translation** ▶ Provides a translation interface for configuration.
- Content Translation** ▶ Allows users to translate content entities.
- Interface Translation** ▶ Translates the built-in user interface.
- Language** ▶ Allows users to configure languages and apply them to content.

◀ Back to site   Manage   ★ Shortcuts   admin   ? Tour

Content   Structure   Appearance   Extend   Configuration   People   Reports   Help

## Languages ☆

List   Detection and selection

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#)

Reorder the configured languages to set their order in the language switcher block and, when editing content, in the list of selectable languages. This ordering does not impact [detection and selection](#).

The site default language can also be set. It is not recommended to change the default language on a working site. [Configure the Selected language](#) setting on the detection and selection page to change the fallback language for language selection.

Interface translations are automatically imported when a language is added, or when new modules or themes are enabled. The report [Available translation updates](#) shows the status. Interface text can be customized in the [user interface translation](#) page.

[+ Add language](#)

[Show row weights](#)

NAME	DEFAULT	INTERFACE TRANSLATION	OPERATIONS
✚ English	<input checked="" type="radio"/>	not applicable	<a href="#">Edit</a> ▼
✚ Spanish	<input type="radio"/>	<a href="#">8111/8168 (99.3%)</a>	<a href="#">Edit</a> ▼
✚ French	<input type="radio"/>	<a href="#">7646/8168 (93.61%)</a>	<a href="#">Edit</a> ▼
✚ Hungarian	<input type="radio"/>	<a href="#">8111/8168 (99.3%)</a>	<a href="#">Edit</a> ▼

[Save configuration](#)



## Add language ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Languages](#)

Add a language to be supported by your site. If your desired language is not available, pick *Custom language...* at the end and provide a language code and other details manually.

### Language name

- Afrikaans
- Albanian
- Amharic
- Arabic
- Armenian
- Asturian
- Azerbaijani
- Bahasa Malaysia
- Basque
- Belarusian
- Bengali
- Bosnian
- Bulgarian
- Burmese
- Catalan
- Chinese, Simplified
- Chinese, Traditional
- Croatian
- Czech
- Danish
- Dutch
- Dzongkha
- Esperanto
- Estonian

## Add language ☆

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Languages](#)

Add a language to be supported by your site. If your desired language is not available, pick *Custom language...* at the end and provide a language code and other details manually.

### Language name

### Language code \*

Use language codes as defined by the W3C for interoperability. Examples: "en", "en-gb" and "zh-hant".

### Language name \*

### Direction \*

Left to right

Right to left

Direction that text in this language is presented.

[Add custom language](#)

## Detection and selection ☆

[List](#) [Detection and selection](#)

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Languages](#)

Define how to decide which language is used to display page elements (primarily text provided by modules, such as field labels and help text). This decision is made by evaluating a series of detection methods for languages; the first detection method that gets a result will determine which language is used for that type of text. Be aware that some language detection methods are unreliable under certain conditions, such as browser detection when page-caching is enabled and a user is not currently logged in. Define the order of evaluation of language detection methods on this page. The default language can be changed in the [list of languages](#).

### Interface text language detection

Order of language detection methods for interface text. If a translation of interface text is available in the detected language, it will be displayed.

[Show row weights](#)

DETECTION METHOD	DESCRIPTION	ENABLED	OPERATIONS
+ Account administration pages	Account administration pages language setting.	<input type="checkbox"/>	
+ URL	Language from the URL (Path prefix or domain).	<input checked="" type="checkbox"/>	<a href="#">Configure</a>
+ Session	Language from a request/session parameter.	<input type="checkbox"/>	<a href="#">Configure</a>
+ User	Follow the user's language preference.	<input type="checkbox"/>	
+ Browser	Language from the browser's language settings.	<input type="checkbox"/>	<a href="#">Configure</a>
+ Selected language	Language based on a selected language.	<input checked="" type="checkbox"/>	<a href="#">Configure</a>

### Content language detection

Order of language detection methods for content. If a version of content is available in the detected language, it will be displayed.

Customize *Content* language detection to differ from interface text language detection settings

[Save settings](#)

▼ LANGUAGE SETTINGS

Site language  
English

This account's preferred language for emails. This is also assumed to be the primary language of this account's profile information.

Administration pages language  
- No preference -

## URL language detection configuration ☆

Home » Administration » Configuration » Regional and language » Languages » Detection and selection

Part of the URL that determines language

- Path prefix
- Domain

▼ PATH PREFIX CONFIGURATION

Language codes or other custom text to use as a path prefix for URL language detection. For the selected fallback language, this value may be left blank. **Modifying this value may break existing URLs. Use with caution in a production environment.** Example: Specifying "deutsch" as the path prefix code for German results in URLs like "example.com/deutsch/contact".

**English (en) path prefix (Default language)**  
https://dr2o3.ply.st/

**Spanish (es) path prefix**  
https://dr2o3.ply.st/

**French (fr) path prefix**  
https://dr2o3.ply.st/

**Hungarian (hu) path prefix**  
https://dr2o3.ply.st/

Save configuration

## Session language detection configuration ☆

Home » Administration » Configuration » Regional and language » Languages » Detection and selection

Determine the language from a request/session parameter. Example: "http://example.com?language=de" sets language to German based on the use of "de" within the "language" parameter.

Request/session parameter

Name of the request/session parameter used to determine the desired language.

Save configuration

BROWSER LANGUAGE CODE	SITE LANGUAGE	OPERATIONS
<input type="text" value="no"/>	Norwegian Bokmål	Delete
<input type="text" value="pt"/>	Portuguese, Portugal	Delete
<input type="text" value="zh"/>	Chinese, Simplified	Delete
<input type="text" value="zh-tw"/>	Chinese, Traditional	Delete
<input type="text" value="zh-hk"/>	Chinese, Traditional	Delete
<input type="text" value="zh-mo"/>	Chinese, Traditional	Delete
<input type="text" value="zh-cht"/>	Chinese, Traditional	Delete
<input type="text" value="zh-cn"/>	Chinese, Simplified	Delete
<input type="text" value="zh-sg"/>	Chinese, Simplified	Delete
<input type="text" value="zh-chs"/>	Chinese, Simplified	Delete

ADD A NEW MAPPING

Browser language code

Use language codes as defined by the W3C for interoperability. Examples: "en", "en-gb" and "zh-hant".

Site language  
English

Save configuration

### Selected language configuration

Home » Administration » Configuration » Regional and language » Languages » Detection and selection  
Changing the selected language here (and leaving this option as the last among the detection and selection options) is the easiest way to change the fallback language for the website, if you need to change how your site works by default (e.g., when using an empty path prefix or using the default domain). Changing the site's default language itself might have other undesired side effects.

Language  
Site's default language (English)

Save configuration

## Content language detection

Order of language detection methods for content. If a version of content is available in the detected language, it will be displayed.

Customize *Content* language detection to differ from Interface text language detection settings

Show row weights

DETECTION METHOD	DESCRIPTION	ENABLED	OPERATIONS
✚ Content language	Determines the content language from a request parameter.	<input type="checkbox"/>	
✚ URL	Language from the URL (Path prefix or domain).	<input type="checkbox"/>	<button>Configure</button>
✚ Session	Language from a request/session parameter.	<input type="checkbox"/>	<button>Configure</button>
✚ User	Follow the user's language preference.	<input type="checkbox"/>	
✚ Browser	Language from the browser's language settings.	<input type="checkbox"/>	<button>Configure</button>
✚ Interface	Use the detected interface language.	<input checked="" type="checkbox"/>	
✚ Selected language	Language based on a selected language.	<input type="checkbox"/>	<button>Configure</button>

Save settings

Home Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

### Configure block ☆

Configure block Translate block

Home » Administration » Structure » Block layout

With multiple languages configured, registered users can select their preferred language and authors can assign a specific language to content.

**Block description:** Language switcher

**Title \***

Language switcher Machine name: demotheme\_languageswitcher

Display title

**Visibility**

<b>Language</b> Not restricted	<b>Language selection</b> <input type="checkbox"/> English <input type="checkbox"/> Spanish <input type="checkbox"/> French <input type="checkbox"/> Hungarian <small>Select languages to enforce. If none are selected, all languages will be allowed.</small>
<b>Content types</b> Not restricted	
<b>Pages</b> Not restricted	
<b>Roles</b> Not restricted	

**Region**

Sidebar second

Select the region where this block should be displayed.

Save block Delete

## Exciting destinations

Stunning Views in Sydney



Make This Your New Office



Explore Egypt by Air



Tropical Paradise at Reasonable Rates



Travel to London for Less



All Trails Lead to Portland



[English](#)  
[Español](#)  
[Français](#)  
[magyar](#)

### Explore with us

There are many exciting destinations in the world! Explore our [trips](#) to learn about these wonderful places and experiences. When you are ready to book your trip, [contact us](#) and we'll make sure you have a vacation of a lifetime.

### Drupal 8 Demo

*Travel the World* is a demonstration site for the [Drupal 8 Multilingual Initiative \(D8MI\)](#). Some sample content is copied from the [Demo Framework](#). Content is machine translated, please forgive the errors.

Home » Administration » Structure » Content types

### Name \*

Basic page Machine name: page

The human-readable name of this content type. This text will be displayed as part of the list on the *Add content* page. This name must be unique.

### Description

Use `<em>basic pages</em>` for your static content, such as an 'About us' page.

This text will be displayed on the *Add new content* page.

#### Submission form settings

Title

#### Default language

Site's default language (English)

Explanation of the language options is found on the [languages list page](#).

Show language selector on create and edit pages

Enable translation

#### Language settings

Site's default language (English),  
Enable translation

#### Display settings

Don't display post information

#### Menu settings

[Save content type](#)

[Delete](#)

[Back to site](#)
[Manage](#)
[Shortcuts](#)
[admin](#)

[Content](#)
[Structure](#)
[Appearance](#)
[Extend](#)
[Configuration](#)
[People](#)
[Reports](#)
[Help](#)

## Translations of *New page* ☆

[View](#)
[Edit](#)
[Delete](#)
[Translate](#)

[Home](#) » [Node](#) » [Test](#)

LANGUAGE	TRANSLATION	STATUS	OPERATIONS
English (Original language)	<a href="#">New page</a>	Published	<a href="#">Edit</a>
Spanish	n/a	Not translated	<a href="#">Add</a>
French	n/a	Not translated	<a href="#">Add</a>
Hungarian	n/a	Not translated	<a href="#">Add</a>

[Home](#)
[Manage](#)
[Shortcuts](#)
[admin](#)
[Tour](#)

[Content](#)
[Structure](#)
[Appearance](#)
[Extend](#)
[Configuration](#)
[People](#)
[Reports](#)
[Help](#)

## User interface translation ☆

[Translate](#)
[Import](#)
[Export](#)
[Settings](#)

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#)

This page allows a translator to search for specific translated and untranslated strings, and is used when creating or editing translations. (Note: Because translation tasks involve many strings, it may be more convenient to export strings for offline editing in a desktop Gettext translation editor.) Searches may be limited to strings in a specific language.

▼ FILTER TRANSLATABLE STRINGS

String contains

Leave blank to show all strings. The search is case sensitive.

Translation language: Spanish
 Search in: Both translated and untr
[Filter](#)
[Reset](#)

SOURCE STRING	TRANSLATION FOR SPANISH
An AJAX HTTP error occurred.	<input type="text" value="Se produjo un error HTTP AJAX."/>
HTTP Result Code: Istatus	<input type="text" value="Código de Resultado HTTP: Istatus"/>
An AJAX HTTP request terminated abnormally.	<input type="text" value="Una solicitud HTTP de AJAX terminó de manera anormal."/>
Debugging information follows.	<input type="text" value="A continuación se detalla la información de depuración."/>
Path: !uri	<input type="text" value="Ruta: !uri"/>
StatusText: IstatusText	<input type="text" value="StatusText: IstatusText"/>

# Chapter 14: Configuration Management

your sync directory with the active configuration before completing the import.

### View changes of block.block.bartik\_content

ACTIVE		STAGED	
	theme: bartik	theme: bartik	
	region: content	region: content	
-	weight: -4	+	weight: 0
	provider: null	provider: null	
	plugin: system_main_block	plugin: system_main_block	

[Back to 'Synchronize configuration' page.](#)

Back to site | Manage | Shortcuts | admin

Content | Structure | Appearance | Extend | Configuration | People | Reports | Help

## Synchronize

Synchronize | Import | Export

Home » Administration » Configuration » Development

Compare the configuration uploaded to your sync directory with the active configuration before completing the import.

**5 changed**

NAME	OPERATIONS
block.block.bartik_content	<a href="#">View differences</a>
block.block.bartik_local_actions	<a href="#">View differences</a>
block.block.bartik_local_tasks	<a href="#">View differences</a>
block.block.bartik_page_title	<a href="#">View differences</a>
block.block.views_block__articles_block_1	<a href="#">View differences</a>

[Import all](#)

## Single export

Synchronize Import Export

Full archive Single item

Home » Administration » Configuration » Development » Synchronize

Choose a configuration item to display its YAML structure.

### Configuration type

Simple configuration

### Configuration name

system.site

### Here is your configuration:

```
luid: 6e238c46-ba43-4025-a002-2f4e6d594b59
name: Mastering Drupal 8
mail: whurley@forumone.com
slogan: ""
page: ""
  403: ""
  404: ""
front: /node
admin_compact_mode: false
weight_select_max: 100
langcode: en
default_langcode: en
-core:
  default_config_hash: yXadRE77Va-G6dxhd2kPYapAvbn5vTF6hO4oXioEynl
```

Filename: system.site.yml

## Single import

Synchronize Import Export

Full archive Single item

Home » Administration » Configuration » Development » Synchronize

Import a single configuration item by pasting its YAML structure into the text field.

### Configuration type \*

Simple configuration

### Configuration name \*

system.site

Enter the name of the configuration file without the .yml extension. (e.g. system.site)

### Paste your configuration here \*

ADVANCED

Import



## Export

Synchronize Import Export

Full archive Single item

Home » Administration » Configuration » Development » Synchronize

Export and download the full configuration of this site as a gzipped tar file.

Export

## Import

Synchronize Import Export

Full archive Single item

Home » Administration » Configuration » Development » Synchronize

Upload a full site configuration archive to the sync directory. It can then be compared and imported on the Synchronize page.

Configuration archive

Choose File No file chosen

Allowed types: tar.gz tar.bz2.

Upload

## Basic site settings

Settings Translate system information

Home » Administration » Configuration » System

### SITE DETAILS

Site name \*  
multilingual\_demo 8.x-1.x

Slogan  
Find exciting destinations  
How this is used depends on your site's theme.

Email address \*  
rrixa@simplytest.me

The From address in automated emails sent during registration and new password requests, and other notifications. (Use an address ending in your site's domain to help prevent this email being flagged as spam.)

Home Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Translations for *System information* ☆

Settings Translate system information

Home » Administration » Configuration » System » Basic site settings

LANGUAGE	OPERATIONS
English (original)	<a href="#">Edit</a>
Spanish	<a href="#">Add</a>
French	<a href="#">Add</a>
Hungarian	<a href="#">Add</a>

Home Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Add Spanish translation for *System information* ☆

Home » Administration » Configuration » System » Basic site settings » Translate

**Site name**  
multilingual\_demo 8.x-1.x

**Site name**

**Slogan**  
Find exciting destinations

**Slogan**

[Save translation](#)

Back to site Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Configuration translation ☆

Home » Administration » Configuration » Regional and language

This page lists all configuration items on your site that have translatable text, like your site name, role names, etc.

LABEL	OPERATIONS
Block	<a href="#">List</a>
Comment fields	<a href="#">List</a>
Comment type	<a href="#">List</a>
Contact form	<a href="#">List</a>
Contact message fields	<a href="#">List</a>
Content fields	<a href="#">List</a>
Content type	<a href="#">List</a>
Custom block fields	<a href="#">List</a>
Custom block type	<a href="#">List</a>

[Home](#) » [Administration](#) » [Configuration](#) » [Regional and language](#) » [Configuration translation](#)

**Search**

BLOCK	THEME	CATEGORY	OPERATIONS
Page title	Bartik	core	<a href="#">Translate</a>
Primary admin actions	Bartik	core	<a href="#">Translate</a>
Tabs	Bartik	core	<a href="#">Translate</a>
Search	Bartik	Forms	<a href="#">Translate</a>
Help	Bartik	Help	<a href="#">Translate</a>
Footer menu	Bartik	Menus	<a href="#">Translate</a>
Main navigation	Bartik	Menus	<a href="#">Translate</a>

[Configure block](#)
[Translate block](#)

[Home](#) » [Administration](#) » [Structure](#) » [Block layout](#) » [Configure block](#)

LANGUAGE	OPERATIONS
English (original)	<a href="#">Edit</a>
Spanish	<a href="#">Edit</a> ▼
French	<a href="#">Edit</a> ▼
Hungarian	<a href="#">Edit</a> ▼

## User interface translation ☆

Translate Import Export Settings

Home » Administration » Configuration » Regional and language

This page allows a translator to search for specific translated and untranslated strings, and is used when creating or editing translations. (Note: Because translation tasks involve many strings, it may be more convenient to [export](#) strings for offline editing in a desktop Gettext translation editor.) Searches may be limited to strings in a specific language.

### ▼ FILTER TRANSLATABLE STRINGS

**String contains**

destinations

Leave blank to show all strings. The search is case sensitive.

**Translation language**

Spanish

**Search in**

Both translated and untr

Filter

Reset

### SOURCE STRING

### TRANSLATION FOR SPANISH

Find exciting destinations

This is a test

Exciting destinations

Save translations

# Chapter 15: Site Migration

[Back to site](#) [Manage](#) [Shortcuts](#) [admin](#)

[Content](#) [Structure](#) [Appearance](#) [Extend](#) [Configuration](#) [People](#) [Reports](#) [Help](#)

## Extend ☆

[List](#) [Uninstall](#)

[Home > Administration](#)

Download additional [contributed modules](#) to extend your site's functionality.

Regularly review available updates to maintain a secure and current site. Always run the [update script](#) each time a module is updated. Enable the [Update Manager module](#) to update and install modules and themes.

Enter a part of the module name or description

[Return to site content](#)

▼ CORE (EXPERIMENTAL)

- Migrate** ▶ Handles migrations
- Migrate Drupal** ▶ Contains migrations from older Drupal versions.
- Migrate Drupal UI** ▶ Provides a user interface for migrating from older Drupal versions.

[Install](#)

[Back to site](#) [Manage](#) [Shortcuts](#) [admin](#)

[Content](#) [Structure](#) [Appearance](#) [Extend](#) [Configuration](#) [People](#) [Reports](#) [Help](#)

## Drupal Upgrade ☆

[Home](#)

Upgrade a Drupal site by importing it into a clean and empty new install of Drupal 8. You will lose any existing configuration once you import your site into it. See the [upgrading handbook](#) for more detailed information.

1. **Back up the database for this site.** Upgrade will change the database for this site.
2. Make sure that the host this site is on has access to the database for your previous site.
3. If your previous site has private files to be migrated, a copy of your files directory must be accessible on the host this site is on.
4. In general, enable all modules on this site that are enabled on the previous site. For example, if you have used the book module on the previous site then you must enable the book module on this site for that data to be available on this site.
5. Put this site into [maintenance mode](#).

This upgrade can take a long time. It is better to import a local copy of your site instead of directly importing from your live site.

[Continue](#)

[Home](#)

**▼ SOURCE DATABASE**

Provide credentials for the database of the Drupal site you want to upgrade.

**Database type \***

MySQL, MariaDB, Percona Server, or equivalent  
 SQLite

**Database host \***

**Database name \***

**Database username \***

**Database password**

▶ **ADVANCED OPTIONS**

▶ **SOURCE FILES**

[Review upgrade](#)

**Are you sure?** ☆

[Home](#)

- 13 available upgrade paths
- 111 missing upgrade paths

**Upgrade analysis report**

**Missing upgrade paths**

The following items will not be upgraded. For more information see [Upgrading from Drupal 6 or 7 to Drupal 8](#).

SOURCE	DESTINATION
addanother	Missing
admin_menu	Missing
admin_menu_toolbar	Missing
backup_migrate	Missing
blockify	Missing
ccl	Missing

Back to site Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

▼ AVAILABLE UPGRADE PATHS

SOURCE	DESTINATION
block	block block_content
dblog	dblog
field	field
file	file
filter	filter
image	image
menu	menu_link_content menu_ui system
node	node
path	path
search	search
taxonomy	taxonomy
text	text
user	user

Perform upgrade Cancel

Manage Shortcuts admin Edit

Content Structure Appearance Extend Configuration People Reports Help

My account Log out

Mastering Drupal 8

Home

✓ Completed 40 upgrade tasks successfully  
1 upgrade failed

Search

Tools

[Add content](#)

## Welcome to Mastering Drupal 8

No front page content has been created yet.  
[Add content](#)

Back to site Manage Shortcuts admin

Content Structure Appearance Extend Configuration People Reports Help

## Taxonomy

Home » Administration » Structure

Taxonomy is for categorizing content. Terms are grouped into vocabularies. For example, a vocabulary called "Fruit" would contain the terms "Apple" and "Banana".

[+ Add vocabulary](#)

[Show row weights](#)

VOCABULARY NAME	OPERATIONS
+ Data Scale	List terms
+ File type	List terms
+ Nexus Tags	List terms
+ Organization	List terms
+ Region	List terms
+ Resource type	List terms
+ Tags	List terms
+ Theme	List terms

Save

## Manage fields ☆

Edit Manage fields Manage form display Manage display

Home » Administration » Structure » Content types » Resource profile

+ Add field

LABEL	MACHINE NAME	FIELD TYPE	OPERATIONS
Data Scale	field_data_scale	Entity reference	Edit ▾
File size	field_file_size	Text (formatted)	Edit ▾
File type	field_file_type	Entity reference	Edit ▾
Nexus Tags	field_nexus_tags	Entity reference	Edit ▾
Organization	field_organization	Entity reference	Edit ▾
Publication date	field_pub_date	Date	Edit ▾
Regional/Country focus	field_regional_focus	Entity reference	Edit ▾
Resource Link	field_resource_url	Link	Edit ▾



## Chapter 16: Debugging and Profiling

```
[vagrant@localhost default]$ drupal site:mode dev
```

```
Configuration name: system.performance
```

Configuration key	Original Value	Override Value
cache.page.use_internal	false	false
css.preprocess	false	false
css.gzip	false	false
js.preprocess	false	false
js.gzip	false	false
response.gzip	false	false

```
Configuration name: views.settings
```

Configuration key	Original Value	Override Value
ui.show.sql_query.enabled	true	true
ui.show.performance_statistics	true	true

```
Configuration name: system.logging
```

Configuration key	Original Value	Override Value
error_level	all	all

```
Services files /vagrant/public/sites/default/services.yml was overwritten
```

```
New services settings
```

Service	Parameter	Value
twig.config	auto_reload	true
twig.config	cache	true
twig.config	debug	true

```
// settings:set
```

```
[OK] Setting checked was set to true
```

```
// cache:rebuild
```

```
Rebuilding cache(s), wait a moment please.
```

```
[OK] Done clearing cache(s).
```

```

297 <!-- THEME DEBUG -->
298 <!-- THEME HOOK: 'region' -->
299 <!-- FILE NAME SUGGESTIONS:
300   x region--header.html.twig
301   * region.html.twig
302 -->
303 <!-- BEGIN OUTPUT from 'core/themes/bartik/templates/region--header.html.twig' -->
304 <div class="clearfix region region-header">
305
306
307 <!-- THEME DEBUG -->
308 <!-- THEME HOOK: 'block' -->
309 <!-- FILE NAME SUGGESTIONS:
310   * block--bartik-branding.html.twig
311   x block--system-branding-block.html.twig
312   * block--system.html.twig
313   * block.html.twig
314 -->
315 <!-- BEGIN OUTPUT from 'core/themes/bartik/templates/block--system-branding-block.html.twig' -->
316 <div id="block-bartik-branding" class="contextual-region clearfix site-branding block block-system block-system-branding-block">
317
318   <div data-contextual-id="block:block=bartik_branding:langcode=en"></div>
319   <a href="/" title="Home" rel="home" class="site-branding__logo">
320     
321   </a>
322   <div class="site-branding__text">
323     <div class="site-branding__name">
324       <a href="/" title="Home" rel="home">Mastering Drupal 8</a>
325     </div>
326   </div>
327 </div>
328
329 <!-- END OUTPUT from 'core/themes/bartik/templates/block--system-branding-block.html.twig' -->
330
331 </div>
332
333
334 <!-- END OUTPUT from 'core/themes/bartik/templates/region--header.html.twig' -->

```

The screenshot shows the Drupal 8 interface with the developer toolbar open. The 'Twig context array (14)' is expanded, showing the following structure:

- 'menu\_name' => string (4) "main"
- 'items' => array (1)
  - 'standard.front\_page' => array (8)
    - 'is\_expanded' => bool FALSE
    - 'is\_collapsed' => bool FALSE
    - 'in\_active\_trail' => bool FALSE
    - 'attributes' => object Drupal\Core\Template\Attribute (1)
      - object (1) Available methods (17) Iterator contents (0)
    - protected storage -> array (0)
    - 'title' => string (4) "Home"
    - 'url' => object Drupal\Core\Url (11)
      - object (11) Available methods (35)
        - protected urlGenerator -> NULL
        - protected urlAssembler -> NULL
        - protected accessManager -> NULL
        - protected routeName -> string (7) "<front>"
        - protected routeParameters -> array (0)
        - protected options -> array (1)
          - 'set\_active\_class' => bool TRUE
        - protected external -> bool FALSE
        - protected unrouted -> bool FALSE
        - protected uri -> NULL
        - protected internalPath -> NULL

The screenshot shows the user permissions page for the 'Devel kint' permission. The page includes a navigation bar with 'Back to site', 'Manage', 'Shortcuts', 'admin', and 'Devel'. Below the navigation bar are tabs for 'Content', 'Structure', 'Appearance', 'Extend', 'Configuration', 'People', 'Reports', and 'Help'. The main content area shows the 'PERMISSION' table with columns for 'ANONYMOUS USER', 'AUTHENTICATED USER', and 'ADMINISTRATOR'. The 'Devel kint' permission is listed with the following access settings:

PERMISSION	ANONYMOUS USER	AUTHENTICATED USER	ADMINISTRATOR
Devel <a href="#">kint</a>			<input checked="" type="checkbox"/>
Access kint information	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Warning: Give to trusted roles only; this permission has security implications. View developer debug output.			

```
array (1)
  'data' => array (3)
    'id' => string (4) "body"
    'type' => object Drupal\Core\StringTranslation\TranslatableMarkup (5)
      object (5) Available methods (14)
      protected string -> string (23) "@type (module: @module)"
      protected translatedMarkup -> NULL
      protected options -> array (0)
      protected stringTranslation -> object Drupal\webprofiler\StringTranslation\TranslationManagerWrapper (7)
        object (7) Available methods (13)
        private translationManager -> NULL
        private translated -> NULL
        private untranslated -> NULL
        protected translators -> array (1)
          '30' => array (1)
            *DEPTH TOO GREAT*
        protected sortedTranslators -> NULL
        protected defaultLangcode -> string (2) "en"
        public _serviceId -> string (18) "string_translation"
      protected arguments -> array (2)
    '@type' => object Drupal\Core\StringTranslation\TranslatableMarkup (5)
      object (5) Available methods (14)
```

#### + \$input array (21)

- ```
Called from <ROOT>/modules/devel/devel.module:664 [kprint_r()]
1. <ROOT>/modules/devel/devel.module:794 [kprint_r()]
2. <ROOT>/core/modules/field_ui/src/FieldStorageConfigListBuilder.php:87 [debug_backtrace()]
3. <ROOT>/core/lib/Drupal/Core/Entity/EntityListBuilder.php:224 [Drupal\field_ui\FieldStorageConfigListBuilder->buildHeader()]
4. <ROOT>/core/lib/Drupal/Core/Entity/Controller/EntityListController.php:27 [Drupal\Core\Entity\EntityListBuilder->render()]
5. <ROOT>/core/lib/Drupal/Core/EventSubscriber/EarlyRenderingControllerWrapperSubscriber.php:128 [call_user_func_array()]
6. <ROOT>/core/lib/Drupal/Core/Render/Renderer.php:577 [Drupal\Core\EventSubscriber\EarlyRenderingControllerWrapperSubscriber->Drupal\Core\EventSubscriber\{closure}()]
7. <ROOT>/core/lib/Drupal/Core/EventSubscriber/EarlyRenderingControllerWrapperSubscriber.php:129 [Drupal\Core\Render\Renderer->executeInRenderContext()]
8. <ROOT>/core/lib/Drupal/Core/EventSubscriber/EarlyRenderingControllerWrapperSubscriber.php:182 [Drupal\Core\EventSubscriber\EarlyRenderingControllerWrapperSubscriber->wrapControllerExecutionInRenderContext()]
9. <ROOT>/vendor/symfony/http-kernel/HttpKernel.php:139 [call_user_func_array()]
10. <ROOT>/vendor/symfony/http-kernel/HttpKernel.php:62 [Symfony\Component\HttpKernel\HttpKernel->handleRaw()]
11. <ROOT>/core/lib/Drupal/Core/StackMiddleware/Session.php:62 [Symfony\Component\HttpKernel\HttpKernel->handle()]
12. <ROOT>/core/lib/Drupal/Core/StackMiddleware/KernelPreHandle.php:53 [Drupal\Core\StackMiddleware\Session->handle()]
13. <ROOT>/core/modules/page_cache/src/StackMiddleware/PageCache.php:183 [Drupal\Core\StackMiddleware\KernelPreHandle->handle()]
14. <ROOT>/core/modules/page_cache/src/StackMiddleware/PageCache.php:82 [Drupal\page_cache\StackMiddleware\PageCache->pass()]
15. <ROOT>/core/lib/Drupal/Core/StackMiddleware/ReverseProxyMiddleware.php:51 [Drupal\page_cache\StackMiddleware\PageCache->handle()]
16. <ROOT>/modules/devel/webprofiler/src/StackMiddleware/WebprofilerMiddleware.php:42 [Drupal\Core\StackMiddleware\ReverseProxyMiddleware->handle()]
17. <ROOT>/core/lib/Drupal/Core/StackMiddleware/NegotiationMiddleware.php:55 [Drupal\webprofiler\StackMiddleware\WebprofilerMiddleware->handle()]
18. <ROOT>/vendor/stack/builder/src/Stack/StackedHttpKernel.php:23 [Drupal\Core\StackMiddleware\NegotiationMiddleware->handle()]
19. <ROOT>/core/lib/Drupal/Core/DrupalKernel.php:637 [Stack\StackedHttpKernel->handle()]
20. <ROOT>/index.php:19 [Drupal\Core\DrupalKernel->handle()]
```

```

 $input_array (21)
20: DrupalFieldUiFieldStorageConfigListBuilder->buildHeader()
19: DrupalCoreEntityEntityListBuilder->render()
18: DrupalCoreEntityControllerEntityListController->listing()
17: call_user_func_array()

#file
"core/modules/field_ui/src/FieldStorageConfigListBuilder.php:87"
"core/lib/Drupal/Core/Entity/EntityListBuilder.php:224"
"core/lib/Drupal/Core/Entity/Controller/EntityListController.php:27"

args
array(1) "field_storage_config"
string(20) "field_storage_config"
array(2)
array(2)
object DrupalCoreEntityControllerEntityListController(14)
object (14) Available methods (29)
public static create(Symfony\Component\DependencyInjection\Co
[inheritDoc]
Inherited from DrupalCoreControllerControllerBase
Defined in <ROOT>/core/lib/Drupal/Core/Controller/ControllerBase.ph
public listing($entity_type) -> array
Provides the listing page for any entity type.
@param string $entity_type
The entity type to render.
@return array
A render array as expected by drupal_render().
Defined in <ROOT>/core/lib/Drupal/Core/Entity/Controller/EntityList
public setLinkGenerator(DrupalCoreUtilityLinkGeneratorInte
Sets the link generator service.
@param \DrupalCoreUtilityLinkGeneratorInterface $generator
The link generator service.
@return $this
Inherited from DrupalCoreControllerControllerBase
Defined in <ROOT>/core/lib/Drupal/Core/Routing/LinkGeneratorTrait.p
public setRedirectDestination(DrupalCoreRoutingRedirectDestin
Sets the redirect destination service.
@param \DrupalCoreRouting\RedirectDestinationInterface $redirect
The redirect destination service.
@return $this
Inherited from DrupalCoreControllerControllerBase
Defined in <ROOT>/core/lib/Drupal/Core/Routing/RedirectDestinationT
public setStringTranslation(DrupalCoreStringTranslationVtr
Sets the string translation service to use.
@param \DrupalCoreStringTranslation\TranslationInterface $transla
The string translation service.
@return $this

```

8.0.3 200 12854 ms / 44.8 MB 12864 ms 568 admin 1 14 1 48 74 / 176 10

## Webprofiler

[Home](#) » [Administration](#) » [Reports](#)

Profiles stored with *Database storage service*.

Method 
Limit

| TOKEN  | IP       | METHOD | URL                                                                           | TIME                    |
|--------|----------|--------|-------------------------------------------------------------------------------|-------------------------|
| 32643c | 10.0.2.2 | GET    | http://localhost:8081/admin/people/permissions?q=admin%2Fpeople%2Fpermissions | Wed, 03/09/2016 - 22:35 |
| b36878 | 10.0.2.2 | GET    | http://localhost:8081/admin/people?q=admin%2Fpeople                           | Wed, 03/09/2016 - 22:35 |
| 06be74 | 10.0.2.2 | GET    | http://localhost:8081/?q=                                                     | Wed, 03/09/2016 - 22:32 |


## Request

| GET Parameters | Value |
|----------------|-------|
| q              |       |

| Attributes                     | Value                                         |
|--------------------------------|-----------------------------------------------|
| _controller                    | <a href="#">D:\v\R\ViewController::handle</a> |
| _title                         |                                               |
| view_id                        | frontpage                                     |
| display_id                     | page_1                                        |
| _view_display_show_admin_links | true                                          |
| _route                         | view.frontpage.page_1                         |
| _route_object                  | Object(Symfony\Component\Routing\Route)       |

## Timeline



## Database

Caller Query type Slow queries SWAP PLACEHOLDERS  
Caller Any Any

```
SELECT session FROM sessions WHERE sid = :sid LIMIT 0, 1
```

Time: 0.34 ms Caller: [S\C\H\S\S\H\WriteCheckSessionHandler::read](#) Target: default

[EXPLAIN](#) [INFO](#) [SWAP PLACEHOLDERS](#)

## Database

Caller Query type Slow queries SWAP PLACEHOLDERS  
Caller Any Any

```
SELECT session FROM sessions WHERE sid = 'ApQQbd0ZSU2gJanjoWek073Cqss47Qilz6kHkwylsZE' LIMIT 0, 1
```

Time: 0.34 ms Caller: [S\C\H\S\S\H\WriteCheckSessionHandler::read](#) Target: default

[EXPLAIN](#) [INFO](#) [SWAP PLACEHOLDERS](#)

| id | select_type | table    | type  | possible_keys | key     | key_len | ref   | rows | Extra |
|----|-------------|----------|-------|---------------|---------|---------|-------|------|-------|
| 1  | SIMPLE      | sessions | const | PRIMARY       | PRIMARY | 130     | const | 1    |       |

## Database

Caller Query type Slow queries SWAP PLACEHOLDERS  
Caller Any Any

```
SELECT session FROM sessions WHERE sid = 'ApQQbd0ZSU2gJanjoWek073Cqss47Qilz6kHkwylsZE' LIMIT 0, 1
```

Time: 0.34 ms Caller: [S\C\H\S\S\H\WriteCheckSessionHandler::read](#) Target: default

[EXPLAIN](#) [INFO](#) [SWAP PLACEHOLDERS](#)

## Views

| name    | display | build time | execute time | render time | Action               |
|---------|---------|------------|--------------|-------------|----------------------|
| content | page_1  | 0.21 ms    | 0.01 ms      | 0.03 ms     | <a href="#">Edit</a> |